





# Indicator Monitoring for a new railway PAradigm in seamlessly integrated Cross modal Transport chains – Phase 2



### Deliverable D 7.1

# Requirements Specification for Freight related Topics integrated in Integration Layer

Project acronym:	IMPACT-2
Starting date:	01/09/2017
Duration (in months):	60
Call (part) identifier:	H2020-S2RJU-CFM-2017
Grant agreement no:	777513
Due date of deliverable:	Month 30
Actual submission date:	07-02-2020
Responsible/Author:	Thales (THA)
Dissemination level:	PU
Status:	Final

This project has received funding from the European Union's Horizon 2020 Programme Research and Innovation action under grant agreement No 777513.

This document reflects the views of the author(s) and does not necessarily reflect the views or policy of the European Commission. Whilst efforts have been made to ensure the accuracy and completeness of this document, the IMPACT-2 consortium shall not be liable for any errors or omissions, however caused.

GA 777513 Page 1 | 157







		Document history
Revision	Date	Description
1	07/02/2020	First issue

	Report contributors
Name	Details of contribution
Thales (THA)	Coordinator, overall author and editor
Cem Ormesher-Hussein	Section 13 Container Management System
Allan Young	
HaCon (HC)	Section 6 ETA monitoring and calculation
Mahnam Saeednia	
Rolf Goossmann	
INDRA (IND)	Section 7 Traffic-Node Coordination Module
José Antonio Sánchez Pérez	Section 8 Dynamic Crossing Analysis Module
Hitachi Rail STS (STS)	Section 9 Freight Wagon On Board Monitoring System
Claudio Cavalletti	Section 10 Optimal Time Slot and Itinerary for Dangerous Goods
Trafikverket (TRV/ RISE)	Section 11 Timetable Optimization Module
Martin Kjellin	
Martin Joborn	
Sara Gestrelius	
SIEMENS (SIE)	Section 12 Conflict Detection
Stefan Wegele	
Bombardier Transportation	Section 14 Automated Mining Train Operation
Sweden AB (BT)	
Roland Kuhn Paul Dhillon	

G A 777513 Page 2 | 157







### **Table of Contents**

1	Exe	cutiv	e summary	13
2	Ab	brevi	ations and acronyms	14
3	Bad	ckgro	und	15
4	Ob	jectiv	es/aims	16
	4.1	Ain	1	16
	4.2	Doo	cument Structure	16
5	Int	erfac	es for Freight related Topics	18
6	ETA	A mo	nitoring and calculation	22
	6.1	Use	Case summary	22
	6.2	Inte	erface summary	23
	6.3	Dat	a published by external systems to Integration Layer	25
	6.3	.1	ETA-1 Train Data	25
	6.3	.2	ETA-2 Proposed Path data	29
	6.3	.3	ETA-3 Train Run data	31
	6.4	Dat	a published by ETA to Integration Layer	34
	6.4	.1	ETA-4 ETA/ETI data	34
7	Tra	ffic-N	Node Coordination Module	37
	7.1	Use	Case summary	37
	7.2	Inte	erface Summary	38
	7.3	Dat	a Published by Traffic-Node Coordination Module (TNCM)	41
	7.3	.1	TNCM-1 Train Target Timetable	41
	7.3	.2	TNCM-2 Rolling Stock Target Formation	41
	7.3	.3	TNCM-3 Train Staff Target Crew	42
	7.3	.4	TNCM-4 Proposed Node Plan	43
	7.4	Dat	a read or subscribed by Traffic-Node Coordination Module (TNCM)	45
	7 /	1	TNCM-5 Train Identification	15







	7.4	.2	TNCM-6 Train Target Timetable	45
	7.4	.3	TNCM-7 Train Audited Timetable	46
	7.4	.4	TNCM-8 Train Forecasted Timetable	47
	7.4	.5	TNCM-9 Rolling Stock Target Formation	48
	7.4	.6	TNCM-10 Rolling Stock Audited Formation	49
	7.4	.7	TNCM-11 Train Staff Target Crew	49
	7.4	.8	TNCM-12 Train Staff Audited Crew	50
	7.4	.9	TNCM-13 Train Path Audited Location	51
	7.4	.10	TNCM-14 Expected Node Plan	52
	7.4	.11	TNCM-15 Audited Node Plan	54
8	Dyr	nami	c Crossing Analysis Module	56
	8.1	Use	e Case summary	56
	8.2	Inte	erface Summary	57
	8.3	Dat	a Published by Dynamic Crossing Analysis Module (DCAM)	60
	8.3	.1	DCAM-1 Establish Temporary Speed Restriction	60
	8.3	.2	DCAM-2 Activate Temporary Speed Restriction	61
	8.3	.3	DCAM-3 Deactivate Temporary Speed Restriction	61
	8.3	.4	DCAM-4 Remove Temporary Speed Restriction	62
	8.4	Dat	a Read or Subscribed to by Dynamic Crossing Analysis Module (DCAM)	63
	8.4	.1	DCAM-5 Train Identification	63
	8.4	.2	DCAM-6 Train Target Timetable	64
	8.4	.3	DCAM-7 Train Audited Timetable	65
	8.4	.4	DCAM-8 Train Forecasted Timetable	66
	8.4	.5	DCAM-9 Train Path Audited Location	66
	8.4	.6	DCAM-10 Status of the Track elements	67
	8.4	.7	DCAM-11 Status of the Signal elements	68
	8.4	.8	DCAM-12 Status of the Axle Counters elements	69
	8.4	.9	DCAM-13 Status of the Track Circuit elements	70
	8.4	.10	DCAM-14 Temporary Speed Restriction	70
9	Fre	ight \	Wagon On Board Monitoring System	72
	9.1	Use	e Case summary	72







9.	.2 Ir	iterface Summary	73
9.	.3 D	ata Published by On board monitoring system to Integration Layer	75
	9.3.1	BMS-1 Data standard message with wagon stationary	75
	9.3.2	BMS-2 Data standard message with wagon in motion	76
	9.3.3	BMS-3 Alarm message	78
9.	.4 D	ata Read or Subscribed by BMS system to Integration Layer	79
	9.4.1	BMS-4 Wagon safety procedure	79
10	Opt	imal Time Slot and Itinerary for Dangerous Goods	81
10	0.1	Use Case summary	81
10	0.2	Interface Summary	81
	0.3 itegrati	Data Published by Optimal Time Slot and Itinerary for Dangerous Goods (OTlion Layer	•
	10.3.1	OTI-7 Optimal Itinerary and Time Slot	84
	0.4 OTI) to	Data Read or Subscribed by Optimal Time Slot and Itinerary for Dangerous G Integration Layer	
	10.4.1	OTI-1 General-Data	85
	10.4.2	OTI-2 Wagons-Data	86
	10.4.3	OTI-3 Itin-Infra	87
	10.4.4	OTI-4 Itin-Social	88
	10.4.5	OTI-5 Itin-Clima	89
	10.4.6	OTI-6 Itin-Emergency	91
11	Tim	etable Optimization Module	92
1	1.1	Use Case summary	92
1	1.2	Interface Summary	92
1	1.3	Data Published by Timetable Optimization Module to Integration Layer	95
	11.3.1	TOM-1 Optimized Timetable	95
1	1.4	Data Read or Subscribed to by the TOM from the Integration Layer	97
	11.4.1	TOM-2 Delivery Commitment Request	97
	11.4.2	TOM-3 Planning Conditions	99
	11.4.3	TOM-4 Input Timetable	103
12	Con	flict Detection and Resolution	105







-	12.1	Use Case summary	105
-	12.2	Interface summary	105
-	12.3	Interface details	108
	12.3.1	DDS-1 Change requests	. 108
	12.3.2	DDS-2 Sandbox content	. 109
	12.3.3	DSS-3 Representation of the Real Time Traffic Plan	. 110
	12.3.4	DSS-4 Train positions and speeds	. 111
	12.3.5	DSS-5 Detected conflicts.	. 112
13	Con	tainer Management System	. 115
-	13.1	Use Case summary	115
-	13.2	Interface Summary	115
-	13.3	Data Published by CMS system to Integration Layer	117
	13.3.1	CMS-1 Container Journey	. 117
	13.3.2	CMS-2 Container Contents	. 119
	13.3.3	CMS-3 Physical Container Details	. 120
	13.3.4	CMS-4 Container Journey Leg	. 122
	13.3.5	CMS-5 Request Schedule Modification	. 124
-	L3.4	Data Read or Subscribed by CMS system to Integration Layer	125
	13.4.1	CMS-6 Train to Container Assignment	. 125
	13.4.2	CMS-7 Actual Train Position	. 127
	13.4.3	CMS-8 Train Forecast	. 129
14	Auto	omated Mining Train Operation	. 131
-	L4.1	Use Case summary	131
-	L4.2	Interface Summary	131
-	14.3	Data Published by TCC to Integration Layer	136
	14.3.1	TCC-T1 Loading-Unloading Status	. 136
	14.3.2	TCC-T2 Loading Area in Use	. 136
	14.3.3	TCC-T3 Mission Status	. 137
	14.3.4	TCC-T4 ATO Remote Control	. 137
	14.3.5	TCC-T5 Movement Authority	. 138
	14.3.6	TCC-T6 Position Report Request	. 139







	14.3.7	TCC-T7 Stop Train	140
	14.3.8	TCC-T8 Emergency Alert	140
	14.3.9	TCC-T9 Revoke Emergency Alert	141
:	14.4 [	Data Read or Subscribed by TCC from the Integration Layer	141
	14.4.1	TCC-I1 Loading Area Data	141
	14.4.2	TCC-I2 Location Status	142
	14.4.3	TCC-I3 Desk In Control	142
	14.4.4	TCC-I4 Movement Request	143
	14.4.5	TCC-I5 Train Status	144
	14.4.6	TCC-I6 Loading Finished	144
	14.4.7	TCC-I7 Load Profile	145
	14.4.8	TCC-I8 Position Report	145
	14.5 E	Blocks for TCC and AOS	146
	14.5.1	ACOUSTIC_SIGNAL	146
	14.5.2	ATO_PROFILE_CONTROL	146
	14.5.3	ATO_STOP_POSITION	147
	14.5.4	BALISE_DATA	147
	14.5.5	CEILING_SPEED_DATA	147
	14.5.6	GRADIENT_DATA	147
	14.5.7	LOCATION_DATA	147
	14.5.8	PANTOGRAPH_SHIFT	147
	14.5.9	PANTO_START_POSITION	148
	14.5.10	TRACK_DATA	148
	14.5.11	TRACK_DATA_ITEM	148
15	Conc	lusions	149
16	Refer	ences	150
17	Antit	rust Statement	151
18	APPE	NDIX A: Updated Use Cases	152
:	18.1 A	Automated dispatch of an Available Train	152
	18.2 F	Remote Controlled Train Loading	154
:	18.3 A	Automated Train Unloading	155







# Table of figures

Figure 5-1 Use Cases vs Applications	21
Figure 6-1 Interface Summary ETA monitoring and calculation	23
Figure 7-1 Traffic-Node Coordination Module Interface Summary	38
Figure 8-1 Dynamic Crossing Analysis Module Interface Summary	57
Figure 9-1 Freight Wagon On Board Monitoring System (BMS)	72
Figure 9-2 Interface Overview – On Board Monitoring System	73
Figure 10-1 Interface Overview - Optimal Time Slot and Itinerary for Dangerous Goods	82
Figure 11-1 Interface Overview – Timetable Optimization Module	93
Figure 12-1 Interface overview - Decision Support System	106
Figure 13-1 Interface Overview - Container management System	115
Figure 14-1 - Interface Overview - Automated Mining Train Operation	132
Table of tables	
Table 4-1 Example Properties Table	17
Table 6-1 ETA monitoring and calculation Interface Summary	
Table 6-2 ETA-1 Properties	
Table 6-3 ETA-1 Data	
Table 6-4 ETA-2 Properties	30
Table 6-5 ETA-2 Data	31
Table 6-6 ETA-3 Properties	32
Table 6-7ETA-3 Data	34
Table 6-8 ETA-4 Properties	35
Table 6-9 ETA-4 Data	36
Table 7-1 Traffic-Node Coordination Module Interface Summary	39
Table 7-2 TCNM-1 Properties	41
Table 7-3 TCNM-2 Properties	42
Table 7-4TCNM-3 Properties	43







Table 7-5 TCNM-4 Properties	44
Table 7-6 TCNM-4 Data	45
Table 7-7 Proposed Node Operation	45
Table 7-8 TCNM-5 Properties	45
Table 7-9TCNM-6 Properties	46
Table 7-10TCNM-7 Properties	47
Table 7-11 TCNM-8 Properties	48
Table 7-12 TCNM-9 Rolling Stock Target Formation Properties	48
Table 7-13 TCNM-10 Rolling Stock Audited Formation Properties	49
Table 7-14 TCNM-11 Train Staff Target Crew Properties	50
Table 7-15 TCNM-12 Train Staff Audited Crew Properties	51
Table 7-16 TCNM-13 Train Path Audited Location Proprrties	52
Table 7-17 TCNM-14 Expected Node Plan Properties	53
Table 7-18 Expected Node Operation	53
Table 7-19 Expected Node Plan	53
Table 7-20 TCNM-15 Aduited Node Plan Properties	54
Table 7-21 Audited Node Operation	55
Table 7-22 Audited Node Plan	55
Table 8-1 Dynamic Crossing Analysis Module Interface Summary	58
Table 8-2 Request - Establish Temporary Speed Restriction Properties	
Table 8-3 Activate - Establish Temporary Speed Restriction Properties	61
Table 8-4 Deactivate - Establish Temporary Speed Restriction Properties	62
Table 8-5 Remove - Establish Temporary Speed Restriction Properties	63
Table 8-6 Train Identification Properties	64
Table 8-7 Target Timetable Properties	65
Table 8-8 Audited Timetable Properties	65
Table 8-9 Forecasted Timetable Properties	66
Table 8-10 Train Path Audited Location Properties	67
Table 8-11 Status of the Track elements Properties	68
Table 8-12 Status of the Signal elements Properties	69
Table 8-13 Status of the Axle Counters elements Properties	69
Table 8-14 Status of the Track Circuit elements Properties	70
Table 8-15 Temporary Speed Restriction Properties	71
Table 9-1 Freight Wagon On Board Monitoring System Interface Summary	
Table 9-2 BMS-1 Data standard message with wagon stationary Properties	
Table 9-3 BMS-1 "Data standard message with wagon stationary" Data	
Table 9-4 BMS-2 Data standard message with wagon in motion Properties	
Table 9-5 BMS-2 "Data standard message with wagon in motion" Data	







Table 9-6 BMS-3 Alarm message Properties	78
Table 9-7 BMS-3 "Alarm message" Data	79
Table 9-8 BMS-4 Wagon safety procedure Properties	80
Table 9-9 BMS-4 "Wagon safety procedure" Data	80
Table 10-1 Optimal Time Slot and Itinerary for Dangerous Goods Interface Summary	83
Table 10-2 OPT-7 Optimal Itinerary and Time Slot Properties	84
Table 10-3 OTI-7 "Optimal Itinerary and Time Slot" Data	85
Table 10-4 OTI-1 General-Data Properties	86
Table 10-5 "General-Data" Data	86
Table 10-6 OTI-2 Wagons-Data Properties	87
Table 10-7 "Wagons-Data" Data	87
Table 10-8 ITI-3 Itin-Infra Properties	88
Table 10-9 "Itin-Infra" Data	88
Table 10-10 OTI-4 Itin-Social Properties	89
Table 10-11 "Itin-Social" Data	89
Table 10-12 OTI-5 Itin-Clima Properties	90
Table 10-13 "Itin-Clima" Data	91
Table 10-14 OTI-6 Itin-Emergency Properties	91
Table 10-15 "Itin-Emergency" Data	91
Table 11-1 Timetable Optimization Module Interface Summary	94
Table 11-2 TOM-1 Optimized Timetable Properties	95
Table 11-3 TOM-1 "Optimized Timetable" (Timetable Control Point) Data	96
Table 11-4 TOM-1 "Optimized Timetable" (Train Timetable) Data	96
Table 11-5 TOM-1 "Optimized Timetable" (Full Timetable) Data	97
Table 11-6 TOM-2 Delivery Commitment Request Properties	97
Table 11-7 TOM-2 "Delivery Commitment Request" (Requested Timetable Control Data	,
Table 11-8 TOM-2 "Delivery Commitment Request" (Requested Train Timetable Part) D	ata 98
Table 11-9 TOM-2 "Delivery Commitment Request" (Requested Train Timetable) Data	99
Table 11-10 TOM-2 "Delivery Commitment Request" (Trains Restriction) Data	99
Table 11-11 TOM-3 Planning Conditions Properties	100
Table 11-12 TOM-4 Input Timetable Properties	104
Table 12-1 Conflict Detection and Resolution Interface Summary	107
Table 12-2 Change request Properties	108
Table 12-3 Change request data	109
Table 12-4 Sandbox content properties	110
Table 12-5 Trip properties	110
Table 12-6 Trip Data	111







Table 12-7 Train position properties	111
Table 12-8 Train position data	112
Table 12-9 Conflicts properties	112
Table 12-10 Conflict data	114
Table 13-1 Container Management System Interface Summary	116
Table 13-2 CMS-1 Container Journey Properties	118
Table 13-3 CMS-1 "Container Journey" Data	118
Table 13-4 CMS-2 Container Contents Properties	119
Table 13-5 CMS-2 Container Contents Data	120
Table 13-6 CMS-3 Physical Container Details Properties	121
Table 13-7 CMS-3 Physical Container Details Data	122
Table 13-8 CMS-4 Container Journey Leg Properties	123
Table 13-9 CMS-4 Container Journey Leg Data	124
Table 13-10 CMS-4 Container Loaded Position Data	124
Table 13-11 CMS-5 Request Schedule Modification Properties	125
Table 13-12 CMS-6 Train to Container Assignment Properties	126
Table 13-13 CMS-6 Train to Container Assignment Data	127
Table 13-14 CMS-7 Actual Train Position Properties	128
Table 13-15 CMS-7 Actual Position of Train Data	129
Table 13-16 CMS-8 Train Forecast Properties	129
Table 13-17 CMS-8 Train Forecast Data	130
Table 14-1 Automated Mining Train Operation Interface Summary	135
Table 14-2 TCC-T1 Loading-Unloading Status Properties	136
Table 14-3 TCC-T1 Loading-Unloading Status Data	136
Table 14-4 TCC-T2 Loading Area in Use Properties	137
Table 14-5 TCC-T2 Loading Area in Use Data	137
Table 14-6 TCC-T3 Mission Status Properties	137
Table 14-7 TCC-T3 Mission Status Data	137
Table 14-8 TCC-T4 ATO Remote Control Properties	138
Table 14-9 TCC-T4 ATO Remote Control Data	138
Table 14-10 TCC-T5 Movement Authority Properties	138
Table 14-11 TCC-T5 Movement Authority Data	139
Table 14-12 TCC-T6 Position Report Request Properties	140
Table 14-13 TCC-T6 Position Report Request Data	
Table 14-14 TCC-T7 Stop Train Properties	
Table 14-15 TCC-T7 Stop Train Data	
Table 14-16 TCC-T8 Emergency Alert Properties	
Table 14-17 TCC-T8 Emergency Alert Data	141







Table 14-18 TCC-T9 Revoke Emergency Alert Properties	141
Table 14-19 TCC-T9 Revoke Emergency Alert Data	141
Table 14-20 TCC-I1 Loading Area Data Properties	142
Table 14-21 TCC-I1 Loading Area Data Data	142
Table 14-22 TCC-I2 Location Status Properties	142
Table 14-23 TCC-I2 Location Status Data	142
Table 14-24 TCC-I3 Desk In Control Properties	143
Table 14-25 TCC-I3 Desk In Control Data	143
Table 14-26 TCC-I4 Movement Request Properties	143
Table 14-27 TCC-I4 Movement Request Data	144
Table 14-28 TCC-I5 Train Status Properties	144
Table 14-29 TCC-I5 Train Status Data	144
Table 14-30 TCC-I6 Loading Finished Properties	145
Table 14-31 TCC-I6 Loading Finished Data	145
Table 14-32 TCC-I7 Load Profile Properties	145
Table 14-33 TCC-I7 Load Profile Data	145
Table 14-34 TCC-I8 Position Report Properties	146
Table 14-35 TCC-I8 Position Report Data	146
Table 14-36 ACOUSTIC_SIGNAL Data	146
Table 14-37 ATO_PROFILE_CONTROL Data	146
Table 14-38 ATO_STOP_POSITION Data	147
Table 14-39 BALISE_DATA Data	147
Table 14-40 CEILING_SPEED_DATA Data	147
Table 14-41 GRADIENT_DATA Data	147
Table 14-42 LOCATION_DATA Data	147
Table 14-43 PANTOGRAPH_SHIFT Data	148
Table 14-44 PANTO_START_POSITION Data	148
Table 14-45 TRACK_DATA Data	148
Table 1/L/16 TRACK DATA ITEM Data	1/12







### 1 Executive summary

One of the overall aims of the Impact-2 project is to develop a common platform for the intelligent mobility management by taking advantage of the Integration Layer (IL) developed in the In2Rail project [4] and the Conceptual Data Model (CDM) to support the standardisation of data being exchanged between applications. This Integration Layer is being further developed within In2Smart [5] and X2Rail2 [3] and this work will feed into this deliverable.

This integration of data is a step towards the seamless and fully-automated process integration of railway related services and other modes of transport. The focus of this deliverable, Impact-2 D7.1 "Requirements Specification for Freight", is to enhance the already developed requirements for Integration Layer Topics (groups of data to be exchanged over the IL) with a focus on the necessary constituents needed to link Freight Operations to the overall process.

To this end, this deliverable contains the Data structures and requirements of data exchanges over the IL needed to facilitate the Use Cases developed in Impact-2 D7.2 "Use-Cases for advanced Freight operation" [1]. This can be used to inform the development of the overall CDM, by providing the required data, and requirements to define different Topics for the CDM, and for prototypes developed by partners for Impact-2. This can then be refined and developed further in the FINE-2 project ("Furthering Improvements in Integrated Mobility Management (I2M), Noise and Vibration, and Energy in Shift2Rail").







## 2 Abbreviations and acronyms

	<u> </u>
Abbreviation / acronym	Description
AOS	Automated Onboard Systems (ATP+ATO)
CA	Collaboration Agreement
CPS	Customer Production and Follow up system
DG	Dangerous Goods
DMP	Data Management Plan
DoA	Description of Action
FRU	Freight Railway Undertaking
GA	Grant Agreement
IM	Infrastructure Manager
IMPACT-2	Indicator Monitoring for a new railway PAradigm in seamlessly integrated Cross modal Transport chains – Phase 2
JU	Joint Undertaking
MCU	Master Control Unit
OPCS	Interface to DCS for train control.
PM	Project Manager (coordinator)
RS	Request System
S2R	Shift2Rail
SPD	System Platform Demonstrator
TCC	Train Control Centre
TMS	Traffic Management System
TMT	Technical Management Team
ТОМ	Timetable Optimization Module
TPS	Timetable Planning System
WP	Work Package







### 3 Background

The work within the Shift2Rail project is structured around five Innovation Programs (IPs) interconnected by cross cutting activities (CCAs). The CCAs ensure the interactions between the IPs and different subsystems and thus their connectivity. The work within the CCAs is organized in six Work Areas (WAs). The IMPACT2 project collects all available inputs from different IPs and analyses the synergies between them, taking the societal and economical needs of the future railway system into account.

WP7 of the IMPACT2 project contributes to WA4.2, focussing on the inclusion and linking of freight operations in the overall TMS framework designed in X2Rail2-WP6. The present document constitutes the Deliverable D7.1 "Requirements Specification for Freight" as part of WP7. The objective of this task is to specify and implement the data structures and necessary subroutines into the specific sub-layer foreseen for the data exchange between TMS and Freight Management Systems.

This deliverable identifies the data required for the interfaces between the TMS and Freight management systems within the use cases described in IMPACT2 D7.2 "Use cases for advanced freight operations". It uses the X2Rail2 D6.1 "System Requirement Specification (SRS) for the Integration Layer" [3] as an input to ensure the data structures described are informed by those delivered as part of IP2.







### 4 Objectives/aims

### 4.1 Aim

This document has been prepared to provide functional and non-functional requirements for Freight related Topics integrated into the Integration Layer. This includes interfaces to Freight Management Systems, Field systems and TMS.

For the purpose of this document "Topics" are considered as follows: "Topics are a group of data used for the exchange of data between the different systems" [2].

This document will provide functional requirements for the interfaces that these topics are exchanged over by analysing the data that needs to be exchanged between applications over the Integration Layer. It will also identify non-functional requirements based on the properties of this exchange.

The interfaces analysed and presented in the deliverable are based on the interfaces to the applications and use cases in Impact 2 D7.2 [1] that enable improved freight operations.

The scope of the requirements in this document is to feed into Prototypes created in Impact-2 and into further work during FINE-2.

### 4.2 Document Structure

This document will contain a chapter for applications used within use cases in D7.2 [1]. For each application, the interfaces related to the use cases in D7.2 will be assessed to understand the data that will be exchanged, and the properties of the exchange.

Each chapter will include the following:

- A summary of the use case(s) with a diagram of the interfaces
- A summary of the interfaces being defined.
- The properties of each interface.
- The data being exchanged for each interface.

The following properties will be described.

	Interface Properties
Interface ID	Interface ID
Interface Title	Interface Title
Publisher	REQ System publishing the Data
Publish Trigger	REQ(s) Events that cause the system to publish/re-publish the data (as required by the use case)

GA 777513 Page 16 |







Expected	Static/Dynamic + Approx. publishing frequency
Frequency	
Subscriber	List of systems subscribing to the Data
Filter	REQ(s)
	How should the data be able to be filter for a reader/subscriber.
Persistence	REQ
	How long should the data be persisted on the IL
Length of Validity	REQ
	When should the data be identified as no longer valid by the IL.
Historical Depth	REQ
	How many historical values must be maintained in the IL.
Safety Related	REQ
	Are there safety related requirements for this data.

**Table 4-1 Example Properties Table** 

These properties will be from the perspective of the specific use case. Therefore a publisher may have more triggers than those listed in this document, as use cases outside the scope of this document may need data to be published in different situations.







# 5 Interfaces for Freight related Topics

this document. Each application makes up a following section of the document. The table below shows the relationship between use cases in Impact-2 D7.2 [1] and the applications within those use cases that are included in

							×			Crossing between two
							×			Freight Train without Crossing (IND) (5.3.6)
								×		Node Plan Optimization (IND) (5.3.5)
								×		Update information to Node Management System (IND) (5.3.4)
								×		Update information to Traffic Management System (IND) (5.3.3)
									×	Planning a train request (HC) (5.3.2)
									×	Terminal slot planning (HC) (5.3.1)
Operation		Resolutio n			itinerary for DG	monitoring system	Module			
Train	system system	and	Review	Module	slot and	wagon on board	Analysis	Module	Module	Use Case vs Application
Automated		Conflict	Freight	Timetable	Optimal	Freight	Dynamic	Traffic-Node	ETA	







Use Case vs Application (D7.2 Section Reference)	ETA Module	Traffic-Node Coordination Module	Dynamic Crossing Analysis Module	Freight Wagon on board monitoring system	Optimal time slot and itinerary for DG	Timetable Optimization Module	Freight Transport Review	Conflict Detection and Resolutio	Container management system	Automated Mining Train Operation
Freight Trains (IND) (5.3.7)										
Crossing between a Passenger Train and a Freight Train (IND) (5.3.8)			×							
Freight Train entry to High-Speed line (IND) (5.3.9)			×							
Wagon Axle box Temperature (STS) (5.3.10)				×						
Optimal Time slot and Itinerary (STS) (5.3.11)					×					
Wagon Bogie Vibration (STS) (5.3.12)				×						
Wagon tank pressure (STS) (5.3.13)				×						
Optimize timetable region (TRV/RISE) (5.3.14)						×				







Use Case vs Application (D7.2 Section Reference)	ETA Module	Traffic-Node Coordination Module	Dynamic Crossing Analysis Module	Freight Wagon on board monitoring system	Optimal time slot and itinerary for DG	Timetable Optimization Module	Freight Transport Review	Conflict Detection and Resolutio n	Container management system	Automated Mining Train Operation
Add train to timetable (TRV/RISE) (5.3.15)						×				
Monitoring of staff, locomotive and wagon							NA*			
transport status (TRV/RISE) (5.3.16)										
Conflict detection (SIE) (5.3.17)								×		
Conflict resolution (SIE) (5.3.18)								×		
Optimizing container delivery to ports (THA) (5.3.19)									×	
Automated dispatch of an Available Train (BT)										*
Remote Controlled Train Loading (BT) (5.3.20)										***
Automated Train Unloading (BT) (5.3.21)										***







# Figure 5-1 Use Cases vs Applications

- included in this document. \* NOTE: The "Monitoring of staff, locomotive and wagon transport status" use case is not being progressed beyond D7.2 and is therefore not
- cases (5.3.20 and 5.3.21). \*\* NOTE: The "Automated dispatch of and Available Train" has been added in this deliverable (found in section 18.1) to extend the related use
- unloading area (Car Dumper)" in D7.2 (updated use case in section 18.3 in this deliverable). \*\*\* NOTE: The "Remote Controlled Train Loading" Use case has been renamed from "Movement Control in Train Dispatch Area" in D7.2 (updated use case in section 18.2 of this deliverable), and "Automated Train Unloading" has been renamed from "Movement control in

GA 777513 Page 21 | 157







### 6 ETA monitoring and calculation

### 6.1 Use Case summary

### Use Case (D7.2 5.3.1): Terminal Slot Planning

Assignment of loading and unloading slots at the terminals is usually planned at the tactical planning level according to the requests of Freight Railway Undertakings (FRU). This plan may be modified if a freight train cannot fulfil its schedule or in case of a newly planned train trip at short notice.

If a freight train is delayed, it loses its right to use the unloading slot at the arrival terminal. In this case, the terminal operator plans, a new slot for the loading/unloading process and looks for other options to use the capacity being released by the non-used slot. Therefore, the involved terminal actors (e.g. terminal IM, RU, ...) receive the updated ETA (an interface to the ETA module will facilitate exchanging the updated ETA in real time). The locomotive and the wagons will be late for their next planned trips and therefore should be rescheduled (in most cases, by the FRU).

Depending on the organization of the terminal operations, some or all of the mentioned actors will be involved. This use-case is valid also for cross border and cross network situations. In such cases, the train waits ahead of the border where the space allows.

The duration of terminal operations, such as loading/unloading and shunting operations represents the main component of the overall freight train travel time. Therefore, real-time and efficient management of terminal operations considering delayed trains minimizes their negative effect on the overall ETA of freight trains, thereby enhancing the overall performance of rail freight operations.

### Use Case (D7.2 5.3.2): Planning a train request

Freight train operator may request modifications to the currently planned train path or may request a path for a new service. Note that, depending on the case, multiple connected paths may be suggested for fulfilling the planned train request. The connection here may involve handling or cross border operations. For instance, if the start of a freight train is delayed more than a certain threshold, it may not be able to use its planned path and in this case, the freight train operator will ask for a new train path for the delayed train. In such cases, special considerations should be given to the specifications and constraints of the freight train (e.g. weight, etc.).

Since a requested new or changed path may comply with the definition of an existing non-allocated pre-arranged path (slot), this can be offered (allocated) instead of individual (re-) planning of the path. The scheduling module will receive updated ETA calculation results via interfaces regarding the available resources required for planning a new train. Any none-valid paths/slots are cancelled and the capacity /slot is released accordingly.

GA 777513 Page 22 |







Note that all communications in the above mentioned process are carried out via the web interface attached to the TMS Integration Layer. Therefore, the involved parties are able to communicate their needs in real time and the negotiation processes can be carried out effectively. The digitalized path request process allows for web-based ad-hoc train path requests via a web browser, using for instance, a web application. TAF TSI is expected to be used as a basic element of path request integrated into the web app. In addition, tight integration of process status of terminal operations into ETA calculation functions will enhance the accuracy of ETA calculation.

Below, the different interfaces allowing for the required data exchange are described.

### **6.2** Interface summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side.




Figure 6-1 Interface Summary ETA monitoring and calculation

G A 777513 Page 23 |







The table below shows a summary of the interfaces related to the data exchange during the different processes of use cases.

attribute data being published. This will also allow the ETA module to apply certain logic for consolidation of redundant attribute being data leaving certain data attributes empty if data is not available. For each sending party/system an identifier will be used and assigned to the to Table 6.6 only as far as being available from each of these parties/systems. However, the same data structure might be used for all actors Note that, where there are more than one publisher of the data (fields marked with \*), the publishers are expected to provide data according

published for one train by more than one actor.

Interface ID	Publisher	Subscriber	Topic	Interface Description	Data Description	Related Use Case Steps	Prototy ped
ETA function	ETA function Subscribing	g					
L-YL3	FRU/RU	ATA	Train	Data related to train characteristics, wagons,	6.2.1	UC 5.3.1steps	~
		module,TM S/IM	data	containers, blocks and locomotive.		3,4,5,6, UC5.3.2steps	
						2,3,5	
ETA-2	M	ETA	Propos	Data published by the IM to be used by the ETA	6.2.2	UC5.3.2 steps 2,3	Υ
		module	ed	module for calculating/Updating the ETA/ETI of a			
			path	requested/changed path for containers, wagons and			
			data	blocks on the train.			
E-AT3	TMS, IM,	ATA	Train-	Data required by the ETA module to	6.3.1	UC5.3.1 step 1	<b>Y</b>
	FRU/RU,	module	run	calculate/upgrade/monitor the estimated arrival		UC5.3.2 steps 2,3	
	ТО		data	times of trains and wagons			
ETA function	<b>ETA function Publishing</b>						
ETA-4	ETA	TMS, IM,	ETA/E	Data published by the ETA module regarding the	6.3.2	UC5.3.1 steps	~
	module	FRU/RU/TO	TI data	arrival time of trains/wagons at final or intermediate		1,2,5, and 6	
				stations		UC5.3.2 step 2	

Table 6-1 ETA monitoring and calculation Interface Summary

GA 777513 Page 24 | 157







### 6.3 Data published by external systems to Integration Layer

This is the data published by freight external systems for TMS, ETA module and other systems to use. The data is related to train specifications and other information required for carrying out the different steps of the two use cases mentioned above (details available in D7.2, IMPACT2 [1]). Note that for all the described interfaces, the access rights need to be checked and it has not been considered as part of the interface description.

### 6.3.1 ETA-1 Train Data

The data includes the information related to train specifications, as well as containers, wagons, blocks and locomotives including their physical characteristics.

### 6.3.1.1 Properties of the interface for train related data exchange

	Interface ETA-1 Properties
Interface ID	ETA-1
Interface Title	Train Data
Publisher	The FRU/RU shall be able to publish the data related to their train for TMS and ETA module. They publish the data within section 13.3.1.2 to the integration layer.
Publish Trigger	When a freight train operator requests a path for a new service.  When train attributes such as wagons, locomotive characteristics, etc. change requiring any special considerations that should be given to the specifications and constraints of the freight train (e.g. weight, etc.).  When there is a request e.g. by the ETA module for updating the ETA/ETI.
Expected Frequency	One time occurrence at every update/request.
Subscribers	TO, IM, TMS, ETA
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train data" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Train data" at least until the "train journey" concluded.
Length of Validity	The Integration Layer shall identify the Train Data as valid until it is deleted.
Historical Depth	The Integration Layer shall provide the "Train Data" when a read request is made.

**Table 6-2 ETA-1 Properties** 

GA 777513 Page 25 |







### 6.3.1.2 *Train Data*

	Data Grouping H	Heading	
Attribute	Attribute description	Data type	Related Use Case
Train Identifier	Identification of a train, this ID (Number/character) is used as a reference for further information related to the train on the IL	String	1,2
	Note: Usually this ID is a composition of - Operation Train ID		
	-Operating day - Start time of the train (sometimes required in larger networks)		
Train composition	This information is sent from the RU to the IM informing the composition of the proposed train. This information is covered by the TrainComposition element of TAF TSI	Numeric (business key reference for shared train composition master data)	1,2
WagonNumber	Unique identifier for Wagon	12 character EVN	WagonNumber
WagonTrainPosition	Identifies position of wagon within train formation. Sequential numbers. Front of train is 1.	Numeric	1,2
WagonLoadingGaugeType	Code to define Loading Gauge Type of Vehicle	Alphanumeric	1,2
WagonTrackGaugeType	Code to define Track Gauge Type of	Alphanumeric	1,2







	Vehicle		T
WagonLength	Length of the Wagon in [cm]	Numeric	1,2
WagonMaximumSpeed	Maximum speed of wagon [km/h]	Numeric	1,2
WagonGrossWeight	Total Weight of goods in wagon or transportation unit. (booked weight of goods included packing) in [kg]	Numeric	1,2
WagonLoadStatus	Code to indicate load status	Alphanumeric Code e.g. E = Empty	1,2
WagonType	Code to define Wagon Type	Alphanumeric	1,2
UltimateDestination	Final Location of the Wagon	{Location}	2
CommodityCode	Code indicating type of material the wagon is carrying	Alphanumeric	1,2
CrippleCode	Code to indicate a problem with the wagon if one exists.	Alphanumeric	1,2
WagonBrakeForce	Brake force of Wagon	Numeric (0-99)	1,2
WagonBrakeType	Code to indicate the brake type	Alphanumeric	1,2
WagonBrakeSetting	Code to indicate the setting of the wagon's brake	Alphanumeric	1,2
WagonDangerousGoods	Details of dangerous goods carried by wagon	{DangerGoods}	1,2
SpecialHandlingCode	If wagon has special handling requirements.	Code	1,2
SpecialCharacteristics	Special	Code	1,2
		i .	i







	characteristics Code		
WagonContainers	Wagons carrying more than one container	N x {Containers}	1,2
ContainerNumber	Container number	Numeric	1,2
ContainerPosition	Distance of Container from front of Wagon.	UnitOfMeasurement: Alphanumeric	1,2
ContainerType	Code to identify container type	Alphanumeric Code	1,2
Container Dangerous Goods	Information if container is carrying dangerous goods.	{DangerousGoods}	1,2
SpecialHandlingCode	Code if special handling is required	Alphanumeric Code	1,2
ContainerLength	Length of container	UnitOfMeasurement: Alphanumeric	1,2
		Value: Numeric	
ContainerHeight	Container Height	UnitOfMeasurement: Alphanumeric	1,2
		Value: Numeric	
ContainerWidth	Container Width	UnitOfMeasurement: Alphanumeric	1,2
		Value: Numeric	
TrainCommunication	Train communication method and contact details (radio type etc)	Alphanumeric	1,2
Locomotive Identifier (s)	Identifier of the locomotive (s) in sequence from train's top	N x String	1,2
Block ID	Informartion on the block specifications such as number, ID and types of wagons included in the block,	N x {BlockNumber}	1,2







	etc.		
RestrictedMaximumSpeed	Restricted maximum speed of the Locomotive in [km/h]	Numeric	2
LocomotiveBrakeForce	Brake force of Locomotive in [kN]	Numeric (0-99)	1,2

Table 6-3 ETA-1 Data

### 6.3.2 ETA-2 Proposed Path data

The data that is exchanged though this interface includes the information required to calculate/update the ETA of a newly-planned train service or an updated path for an already planned train published by the IM. The ETA module will access this information to estimate the arrival time of a train at its final/intermediate stations. The ETA module obtains the Train Data through the ETA-1 interface.

### 6.3.2.1 Properties of the interface for proposed path data exchange

Interface ETA-1 Properties		
Interface ID	ETA-2	
Interface Title	Proposed Path Data	
Publisher	The IM publishes the data related to their suggestion for a new/modified train path, in response to a request received from the FRU/RU. The ETA module accesses this information for calculating/updating a train's ETA/ETI.	
Publish Trigger	When a freight train operator requests modifications to the currently planned train path (for example due to delays along a line or at a terminal).  When a freight train operator requests a path for a new service.  When train attributes such as wagons, locomotive characteristics, etc. change requiring any special considerations that should be given to the specifications and constraints of the freight train (e.g. weight, etc.). As a result, the train path should be re-calculated.	
Expected Frequency	One time occurrence at every update	
Subscribers	ETA	
Filter	The Integration Layer shall provide the publisher with the ability to publish "Proposed Path Data" related to a particular Path ID.	
	The Integration Layer shall provide the subscriber with the ability to receive "Proposed Path Data" i.e. the data specifying the path for a train service.	

GA 777513 Page 29 |







	The Integration Layer shall provide the subscriber with the ability to receive "Train Data" related to a particular Train ID.
Persistence	The Integration Layer shall persist "Proposed Path" data until the status of a path changes to "confirmed/denied".
Length of Validity	The Integration Layer shall identify the proposed path data as Valid until a path is confirmed/denied for a request.
Historical Depth	The Integration Layer shall provide the "proposed path" data when a read request is made.

**Table 6-4 ETA-2 Properties** 

### 6.3.2.2 Proposed Path Data

Data Grouping Heading			
Attribute	Attribute description	Data type	Related Use Case
Train Identifier	Identification of a train, this ID (Number/character) is used as a reference for further information related to the train on the IL	String	1,2
	Note: Usually this ID is a composition of - Operation Train ID		
	-Operating day - Start time of the train (sometimes required in larger networks)		
Proposed Path Identifier	Identification of the suggested train path as being requested earlier, this number is used as a reference of further information related to the train path on the IL (e.g. TrainOperationalIdentification)	string	1,2
WagonNumber	Unique identifier for Wagon	12 character EVN	1,2
Train composition	This information is sent from the RU to the IM informing the composition of the proposed train. This information is covered by the TrainComposition	Numeric (business key reference for shared train composition master	1,2







	element of TAF TSI	data)	
Locomotive Identifier	Identifier of the locomotive	String	1,2
Proposed Path Departure Time and Date	Suggested planned time when the freight train is able to use the route	DateTime	2
Proposed Path Handling	List of references to handling points of the freight train and required minimum handling / maximum waiting times for departing path. First handling point = departing location, last handling point = destination location.	N x (location ID, minimum handling time in [datetime], maximum waiting time in [datetime])	2

Table 6-5 ETA-2 Data

### 6.3.3 ETA-3 Train Run data

The data includes the information related a train run required by the ETA module to upgrade/monitor the estimated arrival times of running trains and wagons at their final or intermediate stations. The ETA module has access to the Train Data related a particular Train ID through ETA-1 interface.

### 6.3.3.1 Properties of the interface for Train Run data exchange

Interface ETA-1 Properties	
Interface ID	ETA-3
Interface Title	Train-Run Data
Publisher	The information concerning a running train is published by different parties (IM, TMS, FRU, TO) for the ETA module to update or monitor a train's ETA/ETI. The data within section 13.3.1.2 is published to the integration layer.
Publish Trigger	When there is an update regarding the status of a running train such as delays (at lines/stations), change in composition, etc.
	When there is an update in the infrastructure status (TSR put in place, etc.)
	When there is an update in terminal operations related to one of a running train's intermediate handling points.
Expected Frequency	Dynamic every 5 to 30 seconds (the interval depends on the network status such as size, traffic frequency, etc.)

GA 777513 Page 31 |







Subscribers	ETA
Filter	The Integration Layer shall provide the subscriber with the ability to read data related to a particular "Path ID"
	The Integration Layer shall provide the subscriber with the ability to read "Train Run" data related to a particular "Train ID"
Persistence	The Integration Layer shall persist "Train Run" data until a new update is available/the train service is concluded/cancelled.
Length of Validity	The Integration Layer shall identify the "Train Run" data as Valid until an update is published.
Historical Depth	The Integration Layer shall provide the subscriber with the latest update of "Train Run" data.

**Table 6-6 ETA-3 Properties** 

### 6.3.3.2 Train Run Data

Data Grouping Heading			
Attribute	Attribute description	Data type	Related Use Case
Train Identifier	Identification of a train, this ID (Number/character) is used as a reference for further information related to the train on the IL	String	1,2
	Note: Usually this ID is a composition of - Operation Train ID		
	-Operating day - Start time of the train (sometimes required in larger networks)		
WagonNumber	Unique identifier for Wagon	12 character EVN	1,2
Train composition	This information is sent from the RU to the IM informing the composition of the proposed train. This	Numeric (business key reference for shared train composition master data)	1,2







	information is covered by the TrainComposition element of TAF TSI		
Location DateTime	DateTime at the location when the train is located at the location.	Timestamp	ETA module
Location Source	Provider of the location data.	Listed [GPS, UTM, RBC, Occupancies]	ETA module
Location GPS Coordinates	Global Positioning System coordinates where the train is located at location DateTime.	Complex [GPS Coordinates]	ETA module
Location UTM Coordinates	Universal Transverse Mercator coordinates where the train is located at location DateTime.	Complex [UTM Coordinates]	ETA module
Location Current Speed	Current speed of train at location in [km/h]	Numeric	ETA module
Location KP – Line Section	Kilometric Point at Line Section the train is located on.	Complex [Numeric, String]	ETA module
Path Temporary Speed Restriction identifier	Identifier of the path TSRs included in the system by the TSR management system.	N x {TSR}	2, ETA module
TSR Maximum Speed	Maximum Speed of the TSR.	Numeric	ETA module
TSR Start Point	Location element where the TSR starts to affect the running of the train.	Complex [Location]	ETA module
TSR Start DateTime	DateTime when the TSR starts to affect the running of the train.	Timestamp	ETA module
TSR End Point	Location element where the TSR leaves to affect the running of the train.	Complex [Location]	ETA module
TSR End DateTime	DateTime when the TSR leaves to affect the	Timestamp	ETA module







	running of the train.		
Train's speed profile	Code identifying shared speed profile data	Alphanumeric	ETA module
Remaining distance to the destination	Distance to the destination [cm]	Numeric	ETA module
Speed limit	Permanent speed limits on train path [km/h]	Numeric	ETA module
Locomotive ID	to feed runtime calculation and route compliance checks	String	ETA module
Temporary Speed Restriction Identifier	Identifier of a TSR included in the system by the TSR management system.	String	2, ETA module
Estimated Terminal Handling Time	Estimation of the time required to handle a train at each intermediate terminal	N x {NumberofTerminals} Numeric	2, ETA module

Table 6-7ETA-3 Data

### 6.4 Data published by ETA to Integration Layer

### 6.4.1 ETA-4 ETA/ETI data

The data includes the information published by the ETA module regarding the calculation/upgrading/monitoring the estimated arrival times of trains and wagons at their final or intermediate stations.

### 6.4.1.1 Properties of the interface for ETA/ETI data exchange

Interface ETA-1 Properties	
Interface ID	ETA-4
Interface Title	ETA/ETI Data
Publisher	The information concerning a running train/a newly planned service published by the ETA module regarding an update or calculation of the estimated arrival time of a train/wagons at intermediate stations or their final destinations. They publish the data within section 13.3.1.2 to the integration layer.
Publish Trigger	The ETA module calculates a train run at specific intervals including the following instances:  When there is an update regarding the status of a running train such as delays

G A 777513 Page 34 |







	(line, station, etc.), change in composition, etc.
	When there is an update in the infrastructure status (TSR put in place, etc.)
	When there is a path proposal in place in response to a path request.
Expected	Dynamic every 5 to 30 second (the interval depends on the network status such
Frequency	as size, traffic frequency, etc.)
Subscribers	FRU/RU, IM, TO
Filter	The Integration Layer shall provide the subscriber with the ability to read data related to a particular "Train ID"
	The Integration Layer shall provide the subscriber with the ability to read data related to a particular "Wagon ID"
	The Integration Layer shall provide the subscriber with the ability to read data related to a particular "Block ID"
Persistence	The Integration Layer shall persist "ETA/ETI" data until there is an update published by the ETA module.
Length of Validity	The Integration Layer shall identify the "ETA/ETI" data as Valid until an update is published.
Historical Depth	The Integration Layer shall provide the subscriber with the latest update of train arrival times.

**Table 6-8 ETA-4 Properties** 

### 6.4.1.2 *ETA/ETI Data*

Data Grouping Heading				
Attribute	Attribute description	Data type	Related Use Case	
Path Identifier	Identification of the suggested train path as being requested earlier, this number is used as a reference of further information related to the train path on the IL (e.g.  TrainOperationalIdentification)	string	1,2	
Train Identifier	Identification of a train, this ID (Number/character) is used as a reference for further	String	1,2	

G A 777513 Page 35 |







	information related to the train on the IL Note: Usually this ID is a composition of - Operation Train ID -Operating day - Start time of the train (sometimes required in larger networks)		
Estimated time of arrival of the train (ETA/ETI)	Forecast of further train run for the interrupted trains, the requested forecasts for train arrival at a specific location may be stored under this topic (including the minimum handling and maximum waiting times)  The related information includes those stored under attributes such as 'Forecasted Arrival Time' "Forecasted Departure Time", and "Train Location ID" on the IL.	DateTime	1,2
Wagon ETA/ETI	Information of the Estimated time of arrival and handling of the wagon	N x {wagonNumber}  DateTime	2
Block ETA/ETI	Information of the Estimated time of arrival and handling of the wagon	N x {BlockNumber}  DateTime	2
Path Confirmation Status	Path confirmed, refused	Binary (0 if not)	2
Wagon Order (Optional)	Information indicating the order of the wagons by sequenced wagon IDs	N x {wagonNumber}	1

Table 6-9 ETA-4 Data







### 7 Traffic-Node Coordination Module

### 7.1 Use Case summary

### Use Case ID (D7.2 5.3.3): Update information to Traffic Management System

The use case describes an innovative scenario for interaction between the Mainline and Nodes, which are managed by different systems sharing information between them. The new Traffic-Node Coordination Module (TNCM) uses information provided by the Traffic management System (TMS) and the Node Management System (NMS) and is able to provide the TMS with the updated data related to the border between the Node and the Mainline. This information is accurately provided by TNCM according to complete knowledge of the current situation within the Node.

In this way, this module allows:

- To provide improved information to TMS based on the knowledge of the current situation within the Node.
- To isolate the TMS of the specific operation mode of the Node:
  - o The internal movements and activities within the Node.
  - The behaviour and integration capabilities of the systems of the Node.

### Use Case ID (D7.2. 5.3.4): Update information to Node Management System

The use case describes an innovative scenario for interaction between the Mainline and the information and movements within a Node. The Mainline is managed by the TMS, and each Node is individually managed by specific systems deployed for each Node. The new TNCM is able to provide to NMS updated data related to the border between the Node and the Mainline using information provided by the TMS and the NMS. This information is accurately provided by TNCM according to complete knowledge of the current situation of the traffic in the Mainline.

In this way, this module allows:

- To provide improved information to NSM based on the knowledge of the current traffic situation into the Mainline.
- To possibly isolate the NMS of:
  - The specific operation mode of the TMS.
  - The behaviour and integration capabilities of the TMS.

#### Use Case ID (D7.2 5.3.5): Node Plan Optimization

The use case describes an innovative scenario for interaction between the synchronization of both areas of management (Mainline and node), which is based on the scheduled and expected timetable of the trains arriving to the node and departing from the node. Taking into account that the management of both sides is performed by different actors, it is a key element that both sides remain informed about the updated information regarding the

GA 777513 Page 37 |







timetable of the trains in the borders. During the operation, several circumstances on the mainline or nodes could imply disturbances on the scheduled timetables. In these cases the tasks in the Node should be internally organized in order to comply at maximum with the current departure timetables scheduled to the Node.

These modifications required over the Node Plan must be carried out by the NMS, in charge of the operation within the Node. For supporting these actions, the TNCM is able to provide modification proposals for the current Node Plan, according to the updated information received from the TMS and from the NMS.

### 7.2 Interface Summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side.




Figure 7-1 Traffic-Node Coordination Module Interface Summary

GA 777513 Page 38 |







The table below shows a summary of the interfaces related to the Traffic-Node Coordination Module.

Interface ID	Publisher	Subscriber	Interface Title	Interface Description	Data Description	Related Use Case Steps	Prototyped
TNCM Publishing	ing						
			Train	Data related to Train			
			Scheduled	Timetable: Scheduled	X2R2 D6.1 8.2.1.2.2	D7.2 5.3.3	
TNCM-1	TNCM	TMS	Timetable	Timetable	"Scheduled Timetable"	D7.25.3.4	Υ
			Rolling Stock	Data related to Rolling			
			Scheduled	Stock: Scheduled	X2R2 D6.1 8.2.1.3.2	D7.2 5.3.3	
TNCM-2	TNCM	TMS	Formation	Formation	"Scheduled Formation"	D7.25.3.4	Υ
			Train Staff				
			Scheduled	Data related to Train Staff:	X2R2 D6.1 8.2.1.4.2	D7.2 5.3.3	
TNCM-3	TNCM	TMS	Crew	Scheduled Crew	"Scheduled Crew"	D7.2 5.3.4	Υ
				Proposed modifications on			
			Proposed	the expected node			
TNCM-4	TNCM	NMS	Node Plan	operations	7.3.4.2	D7.2 5.3.5	Υ
TNCM Subscribing	bing						
					X2R2 D6.1 8.2.1.1		
			Train	Data related to Train	"Data related to Train	D7.2 5.3.3	
TNCM-5	TMS	TNCM	Identification	Identification	Identification"	D7.25.3.4	Υ
				Data related to Train			
			Train Target	Timetable: Target	X2R2 D6.1 8.2.1.2.3	D7.2 5.3.3	
TNCM-6	TMS	TNCM	Timetable	Timetable	"Target Timetable"	D7.2 5.3.4	~







TNCM-15			TNCM-14			TNCM-13			TNCM-12		TNCM-11		TNCM-10			TNCM-9			TNCM-8			TNCM-7		
NMS			NMS			TMS			TMS		TMS		TMS			TMS			TMS			TMS		
TNCM			TNCM			TNCM			TNCM		TNCM		TNCM			TNCM			TNCM			TNCM		
Plan	Audited Node		Plan	Expected Node		Location	Audited	Train Path	Audited Crew	Train Staff	Target Crew	Train Staff	Formation	Audited	Rolling Stock	Formation	Target	Rolling Stock	Timetable	Forecasted	Train	Timetable	Train Audited	
inside the Node	timetable of the operations	Data related to real data	inside the Node	timetable of the operations	Data related to expected	Train Path	8.2.1.5.2 Audited	Data related to Train Path:	Audited Crew	Data related to Train Staff:	Target Crew	Data related to Train Staff:	Stock: Audited Formation	Data related to Rolling		Stock: Target Formation	Data related to Rolling		Timetable	Timetable: Forecasted	Data related to Train	Timetable	Timetable: Audited	Data related to Train
7.4.11.2			7.4.10.2			"Audited Train Path"	X2R2 D6.1 8.2.1.5.2		"Audited Crew"	X2R2 D6.1 8.2.1.4.6	"Target Crew"	X2R2 D6.1 8.2.1.4.4	"Audited Formation"	X2R2 D6.1 8.2.1.3.6		"Target Formation"	X2R2 D6.1 8.2.1.3.4		"Forecasted Timetable"	X2R2 D6.1 8.2.1.2.7		"Audited Timetable"	X2R2 D6.1 8.2.1.2.5	
D7.2 5.3.5			D7.2 5.3.5			D7.2 5.3.4	D7.2 5.3.3		D7.2 5.3.4	D7.25.3.3	D7.2 5.3.4	D7.2 5.3.3	D7.2 5.3.4	D7.2 5.3.3		D7.2 5.3.4	D7.2 5.3.3		D7.2 5.3.4	D7.2 5.3.3		D7.2 5.3.4	D7.2 5.3.3	
~			~			~			~		~		~			~			~			~		

**Table 7-1 Traffic-Node Coordination Module Interface Summary** 







### 7.3 Data Published by Traffic-Node Coordination Module (TNCM)

Data published by the Traffic-Node Coordination Module to the Integration Layer available for TMS or NMS.

#### 7.3.1 TNCM-1 Train Target Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

#### 7.3.1.1 Target Timetable Properties

	Interface TCNM-1 Properties
Interface ID	TNCM-1
Interface Title	Target Timetable
Publisher	The TNCM shall be able to publish the data to the integration layer.
Publish Trigger	TNCM provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line
Expected	Dynamic
Frequency	Approximately once per minute.
Subscribers	TMS (Others)
Filter	The Integration Layer shall modify data to systems with the ability to write "Target Timetable" referred to Train.
Persistence	The Integration Layer shall persist "Target Timetable" enough time for allowing the NMS or TMS process and actualise the new data for a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Target Timetable" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Target Timetable" data received when a read request is made.

## **Table 7-2 TCNM-1 Properties**

#### 7.3.1.2 Target Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.3 "Target Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 7.3.2 TNCM-2 Rolling Stock Target Formation

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

G A 777513 Page 41 |







### 7.3.2.1 Rolling Stock Target Formation Properties

	Interface TCNM-2 Properties
Interface ID	TNCM-2
Interface Title	Rolling Stock Target Formation
Publisher	The TNCM shall be able to publish the data to the integration layer.
Publish Trigger	TNCM provides new information to Integration Layer either when the traffic situation changes in the Node or the Main Line affecting the rolling stock assignment.
Expected	Dynamic
Frequency	Approximately once per minute.
Subscribers	TMS (Others)
Filter	The Integration Layer shall modify data to systems with the ability to write "Rolling Stock Target Formation" referred to Train.
Persistence	The Integration Layer shall persist "Rolling Stock Target Formation" enough time for allowing the NMS or TMS process and actualise the new data, a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Rolling Stock Target Formation" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Rolling Stock Target Formation" data received when a read request is made.

### **Table 7-3 TCNM-2 Properties**

# 7.3.2.2 Rolling Stock Target Formation Data

The data for this interface can be found in Chapter 8.2.1.3.4 "Target Formation" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 7.3.3 TNCM-3 Train Staff Target Crew

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

## 7.3.3.1 Train Staff Target Crew Properties

Interface TCNM-3 Properties				
Interface ID	TNCM-3			
Interface Title	Train Staff Target Crew			
Publisher	The TNCM shall be able to publish the data to the integration layer.			
Publish Trigger	TNCM provides new information to Integration Layer when the traffic situation			

GA 777513 Page 42 |







	changes either in the Node or the Main Line affecting the current train crew assignment.
Expected	Dynamic
Frequency	When it is the result of the analysis.
Subscribers	TMS (Others)
Filter	The Integration Layer shall modify data to systems with the ability to write "Train
	Staff Target Crew" referred to Train.
Persistence	The Integration Layer shall persist "Train Staff Target Crew" enough time for
	allowing the NMS or TMS process and actualise the new data, until a maximum
	time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Train Staff Target Crew" data as valid
	until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Train Staff Target Crew" data
	received when a read request is made.

**Table 7-4TCNM-3 Properties** 

### 7.3.3.2 Train Staff Target Crew Data

The data for this interface can be found in Chapter 8.2.1.4.4 "Target Crew" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

### 7.3.4 TNCM-4 Proposed Node Plan

This is the data published by the Traffic-Node Coordination Module to the Integration Layer available for NMS, "Proposed modifications on the expected node operations". The proposed node operations can be suggestions of modifications or deletion of expected node operations, and addition of new node operations.

#### 7.3.4.1 Proposed Node Plan Properties

	Interface TCNM-4 Properties
	The state of the s
Interface ID	TNCM-4
Interface Title	Proposed Node Plan
Publisher	The TNCM shall be able to publish the data to the integration layer.
Publish Trigger	TNCM analyses the information received from TMS and NMS and generates an improved plan recommendation to be provided to TMS.
Expected	Dynamic
Frequency	Approximately once per 10 minutes.
Subscribers	NMS

GA 777513 Page 43 |







Filter	The Integration Layer shall modify data to systems with the ability to write "Proposed Node Plan".
Persistence	The Integration Layer shall persist "Proposed Node Plan" as valid a maximum time of 24 hours or until the train has completed its journey. Then, it will be deleted
Length of Validity	The Integration Layer shall identify the "Proposed Node Plan" data as valid until new modifications are received.
Historical Depth	The Integration Layer shall provide the last "Proposed Node Plan" data received when a read request is made.

**Table 7-5 TCNM-4 Properties** 

# 7.3.4.2 Proposed Node Plan Data

	Proposed Node Ope	eration	
Attribute	Attribute description	Admitted values	Related Use Case
Node	Identifier of the Node where the operation is proposed.	String	D7.2 5.3.5
Expected Node Operation Reference	Order of the modified Expected Node Operation in Expected Node Plan.	Numeric	D7.2 5.3.5
Proposed Action	Action proposed regarding the node operation.	Listed [Modification, Deletion, Addition]	D7.2 5.3.5
Activity	Activity in the Node.	Listed [Loading, Unloading, Coupling, Reception, Arrival]	D7.2 5.3.5
Node Internal Control Point	Location where the activity is expected.	String	D7.2 5.3.5
Affected Train	Identifier of the Train affected by the activity.	String	D7.2 5.3.5
Affected Wagons	Identifiers of the Wagons affected by the activity.	Array [String]	D7.2 5.3.5
Affected Containers	Identifiers of the Containers affected by the activity.	Array [String]	D7.2 5.3.5
Proposed Activity Start	Audited DateTime of start of the activity.	Timestamp	D7.2 5.3.5
Proposed Activity	Audited DateTime of end of the	Timestamp	D7.2 5.3.5

G A 777513 Page 44 |







End	activity.	

#### Table 7-6 TCNM-4 Data

Table 7-7 Proposed Node Operation

# 7.4 Data read or subscribed by Traffic-Node Coordination Module (TNCM)

#### 7.4.1 TNCM-5 Train Identification

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

#### 7.4.1.1 Train Identification Properties

7.4.1.1 <b>Trumin</b>					
	Interface TCNM-5 Properties				
Interface ID	TNCM-5				
Interface Title	Train Identification				
Publisher	The TMS shall be able to publish the data to the integration layer.				
Publish Trigger	The TMS provides new information to Integration Layer each time a train property is modified.				
Expected	Dynamic				
Frequency	When it is the result of the analysis.				
Subscribers	TNCM (Others)				
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Identification" referred to Train.				
Persistence	Data will be available until the TNCM has processed the information or for a maximum time of 24 hours.				
Length of Validity	The Integration Layer shall identify the "Train Identification" data as valid until new data is received.				
Historical Depth	The Integration Layer shall provide the last "Train Identification" data received when a read request is made.				

#### **Table 7-8 TCNM-5 Properties**

### 7.4.1.2 Train Identification Data

The data for this interface can be found in Chapter 8.2.1.1 "Data related to Train Identification" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

### 7.4.2 TNCM-6 Train Target Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

GA 777513 Page 45 |







### 7.4.2.1 Target Timetable Properties

7.4.2.1 Turget Timetuble Properties				
	Interface TCNM-6 Properties			
Interface ID	TNCM-6			
Interface Title	Target Timetable			
Publisher	The TMS shall be able to publish the data to the integration layer.			
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line.			
Expected	Dynamic			
Frequency	Approximately once per minute.			
Subscribers	TNCM (Others)			
Filter	The Integration Layer shall provide the subscriber with the ability to read "Target Timetable" referred to Train.			
Persistence	The Integration Layer shall persist "Target Timetable" referred to Train until the TNCM has processed the information or for a maximum time of 24 hours.			
Length of Validity	The Integration Layer shall identify the "Target Timetable" data as valid until the train has completed its journey.			
Historical Depth	The Integration Layer shall provide the last "Target Timetable" data received when a read request is made.			

# **Table 7-9TCNM-6 Properties**

### 7.4.2.2 Target Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.3 "Target Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 7.4.3 TNCM-7 Train Audited Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 7.4.3.1 Audited Timetable Properties

Interface TCNM-7 Properties	
Interface ID	TNCM-7
Interface Title	Audited Timetable
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line.

GA 777513 Page 46 |







Expected	Dynamic
Frequency	Approximately once per minute.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read
	"Audited Timetable" referred to Train.
Persistence	The Integration Layer shall persist "Audited Timetable" referred to Train until the
	TNCM has processed the information or for a maximum time of 24 hours
Length of Validity	The Integration Layer shall identify the "Audited Timetable" data as valid until
	the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Audited Timetable" data received
	when a read request is made.

**Table 7-10TCNM-7 Properties** 

#### 7.4.3.2 Audited Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.5 "Audited Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 7.4.4 TNCM-8 Train Forecasted Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

#### 7.4.4.1 Forecasted Timetable Properties

Interface TCNM-8 Properties	
Interface ID	TNCM-8
Interface Title	Forecasted Timetable
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line.
Expected	Dynamic
Frequency	Approximately once per minute.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Forecasted Timetable" referred to Train
Persistence	The Integration Layer shall persist "Forecasted Timetable" referred to Train until the TNCM has processed the information or for a maximum time of 24 hours.

GA 777513 Page 47 |







Length of Validity	The Integration Layer shall identify the "Forecasted Timetable" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Forecasted Timetable" data received when a read request is made.

**Table 7-11 TCNM-8 Properties** 

#### 7.4.4.2 Audited Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.7 "Forecasted Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

### 7.4.5 TNCM-9 Rolling Stock Target Formation

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

# 7.4.5.1 Rolling Stock Target Formation Properties

Interface TCNM-9 Properties	
Interface ID	TNCM-9
Interface Title	Rolling Stock Target Formation
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line affecting the rolling stock assignment.
Expected Frequency	Dynamic Once per minute
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Rolling Stock Target Formation" enough time for allowing the NMS or TMS process and actualise the new data, a maximum time of 24 hours. After this time limit, it will be deleted
Persistence	The Integration Layer shall persist "Rolling Stock Target Formation" referred to Train.
Length of Validity	The Integration Layer shall identify the "Rolling Stock Target Formation" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Rolling Stock Target Formation" data received when a read request is made.

**Table 7-12 TCNM-9 Rolling Stock Target Formation Properties** 

G A 777513 Page 48 |







### 7.4.5.2 Rolling Stock Target Formation Data

The data for this interface can be found in Chapter 8.2.1.3.4 "Target Formation" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer" [3]

### 7.4.6 TNCM-10 Rolling Stock Audited Formation

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 7.4.6.1 Rolling Stock Audited Formation Properties

Interface TCNM-10 Properties	
Interface ID	TNCM-10
Interface Title	Rolling Stock Audited Formation
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer either when the traffic situation changes in the Node or the Main Line affecting the rolling stock assignment.
Expected	Dynamic
Frequency	Once per minute
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Rolling Stock Audited Formation" referred to Train.
Persistence	The Integration Layer shall persist "Rolling Stock Audited Formation" referred to Train enough time for allowing the NMS or TMS process and actualise the new data, a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Rolling Stock Audited Formation" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Rolling Stock Audited Formation" data received when a read request is made.

**Table 7-13 TCNM-10 Rolling Stock Audited Formation Properties** 

### 7.4.6.2 Rolling Stock Audited Formation Data

The data for this interface can be found in Chapter 8.2.1.3.6 "Audited Formation" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 7.4.7 TNCM-11 Train Staff Target Crew

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

G A 777513 Page 49 |







### 7.4.7.1 Train Staff Target Crew Properties

Interface TCNM-11 Properties	
Interface ID	TNCM-11
Interface Title	Train Staff Target Crew
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line affecting the current train crew assignment.
Expected	Dynamic
Frequency	When it is the result of the analysis.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Staff Target Crew" referred to Train.
Persistence	The Integration Layer shall persist "Train Staff Target Crew" referred to Train enough time for allowing the NMS or TMS process and actualise the new data, until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Train Staff Target Crew" data as valid
	until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Train Staff Target Crew" data received when a read request is made.

**Table 7-14 TCNM-11 Train Staff Target Crew Properties** 

# 7.4.7.2 Train Staff Target Crew Data

The data for this interface can be found in Chapter 8.2.1.4.4 "Target Crew" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 7.4.8 TNCM-12 Train Staff Audited Crew

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

## 7.4.8.1 Train Staff Audited Crew Properties

Interface TCNM-12 Properties	
Interface ID	TNCM-12
Interface Title	Train Staff Audited Crew
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation

GA 777513 Page 50 |







	changes either in the Node or the Main Line affecting the current train crew assignment.
Expected	Dynamic
Frequency	When it is the result of the analysis.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train
	Staff Audited Crew" referred to Train.
Persistence	The Integration Layer shall persist "Train Staff Audited Crew" referred to Train
	enough time for allowing the NMS or TMS process and actualise the new data,
	until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Train Staff Audited Crew" data as valid
	until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Train Staff Audited Crew" data
	received when a read request is made.

**Table 7-15 TCNM-12 Train Staff Audited Crew Properties** 

# 7.4.8.2 Train Staff Audited Crew Data

The data for this interface can be found in Chapter 8.2.1.4.6 "Audited Crew" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 7.4.9 TNCM-13 Train Path Audited Location

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 7.4.9.1 **Train Path Audited Location Properties**

Interface TCNM-13 Properties	
Interface ID	TNCM-13
Interface Title	Train Path Audited Location
Publisher	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line affecting the current train crew assignment
Publish Trigger	Train Position is generated for TMS and it publish the "Train Path Audited Location" data to the integration layer. The subscriber receive data.
Expected Frequency	Dynamic  When it is the result of the analysis/change in TMS.
Subscribers	TNCM (Others)

GA 777513 Page 51 |







Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Path Audited Location" referred to Train.
Persistence	The Integration Layer shall persist "Train Path Audited Location" referred to
	Train enough time for allowing the NMS or TMS process and actualise the new
	data, until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Train Path Audited Location" data as
	valid until the train has completed its journey
Historical Depth	The Integration Layer shall provide the last "Train Path Audited Location" data received when a read request is made.

**Table 7-16 TCNM-13 Train Path Audited Location Proprrties** 

#### 7.4.9.2 Train Path Audited Location Data

The data for this interface can be found in Chapter 8.2.1.5.2 "Audited Train Path" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

### 7.4.10 TNCM-14 Expected Node Plan

The Node Manager System provide Expected Node Plan to Integration Layer available for TNCM. The Node Plan details the schedule of operations to be performed within the Node

# 7.4.10.1 Expected Node Plan Properties

Interface TCNM-14 Properties	
Interface ID	TNCM-14
Interface Title	Expected Node Plan
Publisher	The NMS shall be able to publish the data to the integration layer.
Publish Trigger	TNCM analyses the information received from TMS and NMS and generates an improved plan recommendation to be provided to TMS.
Expected	Dynamic
Frequency	Approximately once per 10 minutes.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Expected Node Plan".
Persistence	The Integration Layer shall persist "Expected Node Plan" referred to Train as valid a maximum time of 24 hours or until the train has completed its journey. Then, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Expected Node Plan" data as valid until new modifications are received.
Historical Depth	The Integration Layer shall provide the last "Expected Node Plan" data received when a read request is made.

GA 777513 Page 52 |







### **Table 7-17 TCNM-14 Expected Node Plan Properties**

# 7.4.10.2 Expected Node Plan Data

This is the expected timetable of the operations inside the Node, including the arrival and departure train details. The Expected Node Plan if composed by a set of ordered Expected Node Operations.

	Expected Node Ope	eration	
Attribute	Attribute description	Admitted values	Related Use Case
Node	Identifier of the Node where the operation is expected.	String	D7.2 5.3.5
Activity	Activity in the Node.	Listed [Loading, Unloading, Coupling, Reception, Arrival]	D7.2 5.3.5
Node Internal Control Point	Location where the activity is expected.	String	D7.2 5.3.5
Affected Train	Identifier of the Train affected by the activity.	String	D7.2 5.3.5
Affected Wagons	Identifiers of the Wagons affected by the activity.	Array [String]	D7.2 5.3.5
Affected Containers	Identifiers of the Containers affected by the activity.	Array [String]	D7.2 5.3.5
Expected Activity Start	Expected DateTime of start of the activity.	Timestamp	D7.2 5.3.5
Expected Activity End	Expected DateTime of end of the activity.	Timestamp	D7.2 5.3.5

**Table 7-18 Expected Node Operation** 

	Expected Node P	lan	
Attribute	Attribute description	Admitted values	Related Use Case
N x Expected Node Operation	Set of ordered Expected Node Operations composing the complete Node Plan.	Array [Complex [Expected Node Operation]]	D7.2 5.3.5

**Table 7-19 Expected Node Plan** 

G A 777513 Page 53 |







#### 7.4.11 TNCM-15 Audited Node Plan

The Node Manager System provides the Expected Node Plan to Integration Layer available for TNCM. The Node Plan details the schedule of operations to be performed within the Node.

#### 7.4.11.1 Audited Node Plan Properties

	Interface TCNM-15 Properties
	'
Interface ID	TNCM-15
Interface Title	Audited Node Plan
Publisher	The NMS shall be able to publish the data to the integration layer.
Publish Trigger	TNCM analyses the information received from TMS and NMS and generates an improved plan recommendation to be provided to TMS.
Expected	Dynamic
Frequency	Approximately once per 10 minutes.
Subscribers	TNCM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Audited Node Plan".
Persistence	The Integration Layer shall persist "Audited Node Plan" referred to Train as valid a maximum time of 24 hours or until the train has completed its journey. Then, it will be deleted
Length of Validity	The Integration Layer shall identify the "Audited Node Plan" data as valid until new modifications are received
Historical Depth	The Integration Layer shall provide the last "Audited Node Plan" data received when a read request is made.

**Table 7-20 TCNM-15 Aduited Node Plan Properties** 

#### 7.4.11.2 Audited Node Plan Data

This is real data of the past events inside the Node. The Audited Node Plan is composed by a set of ordered Audited Node Operations.

	Audited Node Operation				
Attribute	Attribute description	Admitted values	Related Use Case		
Node	Identifier of the Node where the operation is audited.	String	D7.2 5.3.5		
Expected Node Operation Reference	Order of the referred Expected Node Operation in Expected	Numeric	D7.2 5.3.5		

GA 777513 Page 54 |







	Node Plan.		
Activity	Activity in the Node.	Listed [Loading, Unloading, Coupling, Reception, Arrival]	D7.2 5.3.5
Node Internal Control Point	Location where the activity is expected.	String	D7.2 5.3.5
Affected Train	Identifier of the Train affected by the activity.	String	D7.2 5.3.5
Affected Wagons	Identifiers of the Wagons affected by the activity.	Array [String]	D7.2 5.3.5
Affected Containers	Identifiers of the Containers affected by the activity.	Array [String]	D7.2 5.3.5
Audited Activity Start	Audited DateTime of start of the activity.	Timestamp	D7.2 5.3.5
Audited Activity End	Audited DateTime of end of the activity.	Timestamp	D7.2 5.3.5

**Table 7-21 Audited Node Operation** 

	Audited Node Pl	an	
Attribute	Attribute description	Admitted values	Related Use Case
N x Audited Node Operation	Set of ordered Audited Node Operations composing operations performed	Array [Complex [Audited Node Operation]]	D7.2 5.3.5

**Table 7-22 Audited Node Plan** 

GA 777513 Page 55 |







# 8 **Dynamic Crossing Analysis Module**

#### 8.1 Use Case summary

#### Use Case ID (D7.2 5.3.6): Freight Train without Crossing

The use case describes a Freight train running on a track of a high-speed line with two parallel tracks, one for each direction of traffic, without crossing any other Train running in the opposite direction. The running of the freight train is supervised in order to detect possible crossings with high-speed trains. If a possible crossing is not detected, then the system does not take any action. As a result, the traffic regulation is able to know in advance that it does not have to manage any crossing operation between trains, because the traffic is continuously supervised beforehand.

#### Use Case ID (D7.2 5.3.7): Crossing between two Freight Trains

The use case describes a Freight Train is running on a track of a High-Speed line with two parallels tracks, one for each direction of traffic. At same time, other Freight Train is running in the opposite direction on the other track. Both trains cross in a point of the line. The Dynamic Crossing Analysis Module (DCAM) supervises the circulation of the Freight Train, but along is journey it is concluded that it is not necessary any additional action because the Freight Train does not cross any High Speed Train.

The crosses between two Freight Trains do not require any additional action because the speed of both trains is not elevated.

### Use Case ID (D7.2 5.3.8): Crossing between a Passenger Train and a Freight Train

The use case describes a freight train is running on a track of a high-speed line with two parallels tracks, one for each direction of traffic. At same time, a high-speed passenger train is running in the opposite direction on the other track. The DCAM supervises the circulation of the freight train, detecting the future crossing between the freight train and a high-speed passenger train. The DCAM protects the future crossing.

Both trains cross in a point of the line. The crossing is protected by means of the actions proposed by the DCAM and provided to the Temporal Speed restriction Management System (TSRM) and the Traffic Management System (TMS).

### Use Case ID (D7.2 5.3.9): Freight Train entry to High-Speed line

The use case describes a Freight Train is running towards a track of the High-Speed Line from a non-High-Speed track. The High-Speed Line has two parallels tracks, one for each direction of traffic. On the other track, a High-Speed Passenger Train is running in the opposite direction.

The DCAM supervises the circulation of the Freight Train, first on the current non-High-Speed track and then on the High-Speed Line track, detecting a future crossing between the Freight Train and a High-Speed Passenger Train. The running of the Freight Train during the

GA 777513 Page 56|







non-High-Speed track requires to be supervised in order to guarantee that if the Freight Train crosses a High-Speed Passenger Train in the High-Speed Line, the cross will be safe, avoiding conflictive situations.

The future crossing is protected by means of the actions proposed by the DCAM and provided to the TSRM and the TMS. Both trains cross.

### 8.2 Interface Summary

Below is a diagram of the interfaces to show the flow of information in the above use cases. The diagram shows functions to publish (P) and subscribe (S).




Figure 8-1 Dynamic Crossing Analysis Module Interface Summary

The table below shows a summary of the interface related to the Dynamic Crossing Analysis Module.

GA 777513 Page 57 |







Interface ID	Publisher	Subscriber	Interface Title	Interface Description	Data Description	Related Use Case Steps	Prototype d
DCAM Publishing	ishing						
			Establish Temporary	Request to establish	X2R2 D6.1 8.4.2.1	D7.2 5.3.8	
DCAM-1	DCAM	TSRMS	Speed Restriction	Temporary Speed Restriction	"Establish a TSR"	D7.2 5.3.9	~
			Activate Temporary	Request to activate	X2R2 D6.1 8.4.2.2	D7.2 5.3.8	
DCAM-2	DCAM	TSRMS	Speed Restriction	Temporary Speed Restriction	"Activate a TSR"	D7.2 5.3.9	~
			Deactivate Temporary	Request to deactivate	X2R2 D6.1 8.4.2.3	D7.2 5.3.8	
DCAM-3	DCAM	TSRMS	Speed Restriction	Temporary Speed Restriction	"Deactivate a TSR"	D7.2 5.3.9	~
			Remove Temporary	Request to remove	X2R2 D6.1 8.4.2.4	D7.2 5.3.8	
DCAM-4	DCAM	TSRMS	Speed Restriction	estriction	"Remove a TSR"	D7.2 5.3.9	Υ
DCAM Subscribing	cribing						
					X2R2 D6.1 8.2.1.1	D7.2 5.3.6 D7.2 5.3.7	
				Data related to Train	"Data related to	D7.2 5.3.8	
DCAM-5	TMS	DCAM	Train Identification	Identification	Train Identification"	D7.2 5.3.9	~
						D7.2 5.3.6	
						D7.2 5.3.7	
			Train Timetable:	Data related to Train	X2R2 D6.1 8.2.1.2.3	D7.2 5.3.8	
DCAM-6	TMS	DCAM	Target Timetable	Timetable: Target Timetable	"Target Timetable"	D7.2 5.3.9	~
						D7.2 5.3.6	
				Data related to Train		D7.2 5.3.7	
			Train Timetable:	Timetable: Audited	X2R2 D6.1 8.2.1.2.5	D7.2 5.3.8	
DCAM-7	TMS	DCAM	Audited Timetable	Timetable	"Audited Timetable"	D7.2 5.3.9	~
						D7.2 5.3.6	
				Data related to Train	X2R2 D6.1 8.2.1.2.7	D7.2 5.3.7	
			Train Timetable:	Timetable: Forecasted	"Forecasted	D7.2 5.3.8	
DCAM-8	TMS	DCAM	Forecasted Timetable	Timetable	Timetable"	D7.2 5.3.9	~

GA 777513







DCAM-14	DCAM-13	DCAM-12	DCAM-11	DCAM-10	DCAM-9
TSRMS	TMS	TMS	TMS	TMS	TMS
DCAM	DCAM	DCAM	DCAM	DCAM	DCAM
Temporary Speed Restriction	Status of the signalling elements: Track Circuit	Status of the signalling elements: Axle Counter	Status of the signalling elements: Signal	Status of the signalling elements: Track	Data related to Train Path: Audited Location
Data related to Temporary Speed Restriction	Data related to Status of the signalling elements: Track Circuit	Data related to Status of the signalling elements: Axle Counter	Data related to Status of the signalling elements: Signal	Data related to Status of the signalling elements: Track	Data related to Train Path: Audited Location
X2R2 D6.1 8.4.1.1 "TSR"	X2R2 D6.1 8.7.1.3.7 "Track Circuits"	X2R2 D6.1 8.7.1.3.6 "Axle Counter"	X2R2 D6.1 8.7.1.3.3 "Signal"	X2R2 D6.1 8.7.1.3.1 "Track"	X2R2 D6.1 8.2.1.5.2 "Audited Train Path"
D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9	D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9	D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9	D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9	D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9	D7.2 5.3.6 D7.2 5.3.7 D7.2 5.3.8 D7.2 5.3.9
<	<	<	<	<	~

**Table 8-1 Dynamic Crossing Analysis Module Interface Summary** 

GA 777513







### 8.3 Data Published by Dynamic Crossing Analysis Module (DCAM)

The Dynamic Crossing Analysis Module does not provide any specific data through the Integration Layer by itself; but interact with other systems by means of invoking requests on the exposed command requests.

The requests that the Dynamic Crossing Analysis Module are provided by:

- The system in charge of the Temporary Speed Restrictions, in order to execute the operations designed for ensuring the crossing between the trains.
- The interlockings in charge of blocking and releasing signals for allowing stopping freight trains if it is necessary.

## 8.3.1 DCAM-1 Establish Temporary Speed Restriction

DCAM provide data to establish Temporary Speed Restrictions to operate.

### 8.3.1.1 Establish Temporary Speed Restriction Properties

	Interface DCAM-1 Properties
Interface ID	DCAM-1
Interface Title	Request - Establish Temporary Speed Restriction
Publisher	The DCAM publish Request to the integration layer.
Publish Trigger	DCAM requires new Temporary Speed Restrictions each time a traffic situation is modified and needs a TSR, and put data for the request to the integration layer.
Expected Frequency	Dynamic  Approximately, once per 10 minutes and each time a modification in the trains path takes place.
Subscribers	TSRMS
Filter	The Integration Layer shall create data to systems with the ability to write "Request - Establish Temporary Speed Restriction" referred to Train.
Persistence	The Integration Layer shall persist "Request - Establish Temporary Speed Restriction" until the TSRMS process the data or, at least, 24 hours.
Length of Validity	The Integration Layer shall identify the "Request - Establish Temporary Speed Restriction" data as valid for 10 minutes or new data is received.
Historical Depth	The Integration Layer shall provide the last "Request - Establish Temporary Speed Restriction" data received when a read request is made.

**Table 8-2 Request - Establish Temporary Speed Restriction Properties** 

GA 777513 Page 60 |







#### 8.3.1.2 Establish Temporary Speed Restriction Data

The data for this interface can be found in Chapter 8.4.2.1 "Establish a TSR" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 8.3.2 DCAM-2 Activate Temporary Speed Restriction

DCAM provide data to modify Temporary Speed Restrictions to operate.

#### 8.3.2.1 Activate Temporary Speed Restriction Properties

	Interface DCAM-2 Properties
Interface ID	DCAM-2
Interface Title	Activate - Establish Temporary Speed Restriction
Publisher	The DCAM publish Request to the integration layer.
Publish Trigger	DCAM requires adding or modifying Temporary Speed Restrictions each time a traffic situation is analysed and needs a TSR, and putting data to the integration layer.
Expected Frequency	Dynamic  Approximately, once per 10 minutes and each time a modification in the trains path takes place.
Subscribers	TSRMS
Filter	The Integration Layer shall modify data to systems with the ability to write "Activate - Establish Temporary Speed Restriction" referred to Train.
Persistence	The Integration Layer shall persist "Activate - Establish Temporary Speed Restriction" until the TSRMS process the data or, at least, 24 hours.
Length of Validity	The Integration Layer shall identify the "Activate - Establish Temporary Speed Restriction" data as valid for 10 minutes or new data is received. Then, it is deleted.
Historical Depth	The Integration Layer shall provide the last "Activate - Establish Temporary Speed Restriction" data received when a read request is made.

**Table 8-3 Activate - Establish Temporary Speed Restriction Properties** 

### 8.3.2.2 Activate Temporary Speed Restriction Data

The data for this interface can be found in Chapter 8.4.2.2"Activate a TSR" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

## 8.3.3 DCAM-3 Deactivate Temporary Speed Restriction

DCAM provide data to modify Temporary Speed Restrictions to operate.

GA 777513 Page 61 |







### 8.3.3.1 **Deactivate Temporary Speed Restriction Properties**

	Interface DCAM-3 Properties
Interface ID	DCAM-3
Interface Title	Deactivate - Establish Temporary Speed Restriction
Publisher	The DCAM publish Request to the integration layer.
Publish Trigger	DCAM requires to deactivate Temporary Speed Restrictions each time a traffic situation is analysed and the conflict has finished, and put data to the integration layer.
Expected Frequency	Dynamic  Approximately, once per 10 minutes and each time a conflict in a train path has finished.
Subscribers	TSRMS
Filter	The Integration Layer shall modify data to systems with the ability to write "Deactivate - Establish Temporary Speed Restriction" referred to Train.
Persistence	The Integration Layer shall persist "Deactivate - Establish Temporary Speed Restriction" until the TSRMS process the data or, at least, 24 hours.
Length of Validity	The Integration Layer shall identify the "Deactivate - Establish Temporary Speed Restriction" data as valid for 10 minutes or until new data is received. Then, it is deleted.
Historical Depth	The Integration Layer shall provide the last "Deactivate - Establish Temporary Speed Restriction" data received when a read request is made.

**Table 8-4 Deactivate - Establish Temporary Speed Restriction Properties** 

### 8.3.3.2 Deactivate Temporary Speed Restriction Data

The data for this interface can be found in Chapter 8.4.2.3 "Deactivate a TSR" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

### 8.3.4 DCAM-4 Remove Temporary Speed Restriction

DCAM provide data to remove Temporary Speed Restrictions to operate.

#### 8.3.4.1 Remove Temporary Speed Restriction Properties

	Interface DCAM-4 Properties
Interface ID	DCAM-4
Interface Title	Remove - Establish Temporary Speed Restriction
Publisher	The DCAM publish Request to the integration layer.

GA 777513 Page 62 |







Publish Trigger	DCAM requires to remove Temporary Speed Restrictions each time a traffic situation is analysed and the conflict has finished and put data to the integration layer.
Expected Frequency	Dynamic  Approximately, once per 10 minutes and each time a conflict in a train path has finished.
Subscribers	TSRMS
Filter	The Integration Layer shall delete data to systems with the ability to write "Remove - Establish Temporary Speed Restriction" referred to Train.
Persistence	The Integration Layer shall persist "Remove - Establish Temporary Speed Restriction" until the TSRMS process the data or, at least, 24 hours.
Length of Validity	The Integration Layer shall identify the "Remove - Establish Temporary Speed Restriction" data as valid for 10 minutes or until new data is received. Then, it is deleted
Historical Depth	The Integration Layer shall provide the last "Remove - Establish Temporary Speed Restriction" data received when a read request is made.

**Table 8-5 Remove - Establish Temporary Speed Restriction Properties** 

### 8.3.4.2 Remove Temporary Speed Restriction Data

The data for this interface can be found in Chapter 8.4.2.4 "Remove a TSR" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 8.4 Data Read or Subscribed to by Dynamic Crossing Analysis Module (DCAM)

#### 8.4.1 DCAM-5 Train Identification

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

# 8.4.1.1 Train Identification Properties

Interface DCAM-5 Properties	
Interface ID	DCAM-5
Interface Title	Train Identification
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provide new information to Integration Layer when the traffic situation changes either in the Node or the Main Line .
Expected Frequency	Dynamic

GA 777513 Page 63 |







	Approximately, once per minute and each time a new path is detected.
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Identification" referred to Train.
Persistence	The Integration Layer shall persist "Train Identification" referred to Train until the DCAM process the data or, at least, 24 hours.
Length of Validity	The Integration Layer shall identify the "Train Identification" data as valid for 10 minutes or until new data is received. Then, it is deleted
Historical Depth	The Integration Layer shall provide the last "Train Identification" data received when a read request is made.

**Table 8-6 Train Identification Properties** 

### 8.4.1.2 Train Identification Data

The data for this interface can be found in Chapter 8.2.1.1 "Data related to Train Identification" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 8.4.2 DCAM-6 Train Target Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

# 8.4.2.1 Target Timetable Properties

Interface DCAM-6 Properties	
Interface ID	DCAM-6
Interface Title	Target Timetable
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes in either the Node or the Main Line.
Expected	Dynamic
Frequency	Approximately once per minute
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Target Timetable" referred to Train.
Persistence	The Integration Layer shall persist "Target Timetable" referred to Train until the DCAM has processed the information or for a maximum time of 24 hours.

G A 777513 Page 64 |







Length of Validity	The Integration Layer shall identify the "Target Timetable" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Target Timetable" data received when a read request is made.

**Table 8-7 Target Timetable Properties** 

### 8.4.2.2 Target Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.3 "Target Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer" [3]

#### 8.4.3 DCAM-7 Train Audited Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 8.4.3.1 Audited Timetable Properties

8.4.3.1 Audited limetable Properties	
Interface DCAM-7 Properties	
Interface ID	DCAM-7
Interface Title	Audited Timetable
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes in either the Node or the Main Line.
Expected	Dynamic
Frequency	Approximately once per minute
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Audited Timetable" referred to Train.
Persistence	The Integration Layer shall persist "Audited Timetable" referred to Train.
Length of Validity	The Integration Layer shall identify the "Audited Timetable" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Audited Timetable" data received when a read request is made.

**Table 8-8 Audited Timetable Properties** 

### 8.4.3.2 Audited Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.5 "Audited Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

G A 777513 Page 65 |







#### 8.4.4 DCAM-8 Train Forecasted Timetable

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 8.4.4.1 Forecasted Timetable Properties

8.4.4.1 Forecusted nimetable Properties	
	Interface DCAM-8 Properties
Interface ID	DCAM-8
Interface Title	Forecasted Timetable
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes in either the Node or the Main Line.
Expected	Dynamic
Frequency	When it is the result of the analysis.
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Forecasted Timetable" referred to Train.
Persistence	The Integration Layer shall persist "Forecasted Timetable" referred to Train until the DCAM has processed the information or for a maximum time of 24 hours.
Length of Validity	The Integration Layer shall identify the "Forecasted Timetable" data as valid until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Forecasted Timetable" data received when a read request is made.

#### **Table 8-9 Forecasted Timetable Properties**

#### 8.4.4.2 Audited Timetable Data

The data for this interface can be found in Chapter 8.2.1.2.7 "Forecasted Timetable" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 8.4.5 DCAM-9 Train Path Audited Location

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

#### 8.4.5.1 Train Path Audited Location Properties

Interface DCAM-9 Properties	
Interface ID	DCAM-9
Interface Title	Train Path Audited Location

GA 777513 Page 66 |







Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides new information to Integration Layer when the traffic situation changes either in the Node or the Main Line affecting the current train crew assignment
Expected	Dynamic
Frequency	When it is the result of the analysis/change in TMS.
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Path Audited Location" referred to Train.
Persistence	The Integration Layer shall persist "Train Path Audited Location" referred to Train enough time for allowing the DCAM process and actualise the new data, until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Train Path Audited Location" data as valid for 10 minutes or until the train has completed its journey.
Historical Depth	The Integration Layer shall provide the last "Train Path Audited Location" data received when a read request is made.

**Table 8-10 Train Path Audited Location Properties** 

#### 8.4.5.2 Train Path Audited Location Data

The data for this interface can be found in Chapter 8.2.1.5.2 "Audited Train Path" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 8.4.6 DCAM-10 Status of the Track elements

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 8.4.6.1 Status of the Track elements Properties

Interface DCAM-10 Properties	
Interface ID	DCAM-10
Interface Title	Status of the Track elements
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provides the status of Interlocking elements and put data to the integration layer.
Expected Frequency	Dynamic  When it is the result of the analysis/change in TMS.

GA 777513 Page 67 |







Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Status of the Track elements" referred to Train.
Persistence	The Integration Layer shall persist "Status of the Track elements" referred to Train enough time for allowing the DCAM process and actualise the new data, until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Status of the Track elements" data as valid for 10 minutes or until the train has completed its journey .
Historical Depth	The Integration Layer shall provide the last "Status of the Track elements" data received when a read request is made.

**Table 8-11 Status of the Track elements Properties** 

## 8.4.6.2 Status of the Track elements Data

The data for this interface can be found in Chapter 8.7.1.3.1 "Track" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

# 8.4.7 DCAM-11 Status of the Signal elements

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 8.4.7.1 Status of the Signal elements Properties

Interface DCAM-11 Properties	
Interface ID	DCAM-11
Interface Title	Status of the Signal elements
Publisher	The TMS shall be able to publish the data to the integration layer.
Publish Trigger	TMS provide the status of Signal elements and put data to the integration layer
Expected Frequency	Dynamic  Each time signals changes.
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Status of the Signal elements" referred to Train.
Persistence	The Integration Layer shall persist "Status of the Signal elements" referred to Train enough time for allowing the DCAM process and actualise the new data, until a maximum time of 24 hours. After this time limit, it will be deleted.
Length of Validity	The Integration Layer shall identify the "Status of the Signal elements" data as valid until the train has completed its journey .

G A 777513 Page 68 |







Historical Depth

The Integration Layer shall provide the last "Status of the Signal elements" data received when a read request is made.

**Table 8-12 Status of the Signal elements Properties** 

### 8.4.7.2 Status of the Signal elements Data

The data for this interface can be found in Chapter 8.7.1.3.3 "Signal" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 8.4.8 DCAM-12 Status of the Axle Counters elements

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

## 8.4.8.1 Status of the Axle Counters elements Properties

Interface DCAM-12 Properties		
Interface ID	DCAM-12	
Interface Title	Status of the Axle Counters elements	
Publisher	The TMS shall be able to publish the data to the integration layer.	
Publish Trigger	TMS provide the status of Axle Counters elements and put data to the integration layer.	
Expected	Dynamic	
Frequency	When it is the result of the analysis/change in TMS.	
Subscribers	DCAM (Others)	
Filter	The Integration Layer shall provide the subscriber with the ability to read "Status of the Axle Counters elements" referred to Train.	
Persistence	The Integration Layer shall persist "Status of the Axle Counters elements" referred to Train enough time for allowing the DCAM process and actualise the new data, until a maximum time of 24 hours. After this time limit, it will be deleted.	
Length of Validity	The Integration Layer shall identify the "Status of the Axle Counters elements" data as valid until the train has completed its journey.	
Historical Depth	The Integration Layer shall provide the last "Status of the Axle Counters elements" data received when a read request is made.	

**Table 8-13 Status of the Axle Counters elements Properties** 

# 8.4.8.2 Status of the Axle Counters elements Data

The data for this interface can be found in Chapter 8.7.1.3.6 "Axle Counter" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

GA 777513 Page 69 |







#### 8.4.9 DCAM-13 Status of the Track Circuit elements

Train information of trains arriving or departing the Nodes in the border between the Node and the mainline.

### 8.4.9.1 Status of the Track Circuit elements Properties

Interface DCAM-13 Properties		
Interface ID	DCAM-13	
Interface Title	Status of the Track Circuit elements	
Publisher	The TMS shall be able to publish the data to the integration layer.	
Publish Trigger	TMS provide the status of Track Circuits elements and put data to the integration layer	
Expected	Dynamic	
Frequency	When it is the result of the analysis/change in TMS.	
Subscribers	DCAM (Others)	
Filter	The Integration Layer shall provide the subscriber with the ability to read "Status	
	of the Track Circuit elements" referred to Train.	
Persistence	The Integration Layer shall persist "Status of the Track Circuit elements" referred	
	to Train enough time for allowing the DCAM process and actualise the new data,	
	until a maximum time of 24 hours. After this time limit, it will be deleted	
Length of Validity	The Integration Layer shall identify the "Status of the Track Circuit elements"	
	data as valid until the train has completed its journey.	
Historical Depth	The Integration Layer shall provide the last "Status of the Track Circuit elements"	
	data received when a read request is made.	

**Table 8-14 Status of the Track Circuit elements Properties** 

### 8.4.9.2 Status of the Track Circuit elements Data

The data for this interface can be found in Chapter 8.7.1.3.7 "Track Circuits" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 8.4.10 DCAM-14 Temporary Speed Restriction

DCAM required the information about the Temporary Speed Restrictions to operate.

#### 8.4.10.1 Temporary Speed Restriction Properties

Interface DCAM-14 Properties		
Interface ID	DCAM-14	
Interface Title	Temporary Speed Restriction	

G A 777513 Page 70 |







Publisher	The TSRMS shall be able to publish the data to the integration layer.
Publish Trigger	TSRMS provide the status of Temporary Speed Restrictions each time a traffic
	situation is modified and needs a TSR and put data to the integration layer.
Expected	Dynamic
Frequency	Approximately, once per 10 minutes and each time a modification in the trains path takes place.
Subscribers	DCAM (Others)
Filter	The Integration Layer shall provide the subscriber with the ability to read "Status of the Track Circuit elements" referred to Train.
Persistence	The Integration Layer shall persist "Status of the Track Circuit elements" referred to Train until the TSRMS process the data or, at least, 24 hours
Length of Validity	The Integration Layer shall identify the "Status of the Track Circuit elements" data as valid for 10 minutes or new data is received.
Historical Depth	The Integration Layer shall provide the last "Status of the Track Circuit elements" data received when a read request is made.

**Table 8-15 Temporary Speed Restriction Properties** 

# 8.4.10.2 Temporary Speed Restriction Data

The data for this interface can be found in Chapter 8.4.1.1 "TSR" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

GA 777513 Page 71 |







# 9 Freight Wagon On Board Monitoring System

#### 9.1 Use Case summary

Use Case ID (D7.2 5.3.10) Wagon Axle box Temperature

Use Case ID (D7.2 5.3.12) Wagon Bogie Vibration

Use Case ID (D7.2 5.3.13) Wagon tank pressure

These use cases describe an innovative scenario for real time monitoring of health status and geographic position of a freight wagon carrying dangerous goods.

A demonstrator will be developed consisting of a on board diagnostic system composed of a Master Control Unit (MCU) communicating with a network of sensors wireless installed at sensible points of the wagon and with an GPS antenna to receive the position signal. The MCU provides TMS with by LTE communication. The TMS, following the data received, can make safety decisions to manage any dangerous situations and has constantly updated the position of the wagon.

The three use cases differ in the three different types of sensors chosen which consequently imply different safety decision that TMS have to undertake to manage the dangerous situations.

The Figure 9-1 shows the layout of the on board monitoring system with highlighted the data communication (wireless) between the sensor nodes and the MCU (Master Control Unit) and the data communication between the MCU and IL/TMS (GSM)




Figure 9-1 Freight Wagon On Board Monitoring System (BMS)

GA 777513 Page 72 |







# 9.2 Interface Summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side. Although some of the interfaces belong to TMS, as these are described from the perspective of this use case, they are all currently identified as "MCU" (Master Control Unit) interfaces.




Figure 9-2 Interface Overview – On Board Monitoring System







The table below shows a summary of the interface related to the On Board Monitoring System BMS and the use case.

Interface	Publisher	Subscriber	Interface Title	Interface Description	Data	Related Use Case	Prototyped
D					Description	Steps	
<b>BMS Publishing</b>	hing						
BMS-1	BMS	SML	Data standard	Data on position and diagnostic state of	9.3.1	D7.2	Υ
			message with	wagon and dangerous goods, without alarms		6.3.10/12/13 Step	
			wagon	and with the wagon stationary		<b>L</b>	
			stationary				
BMS-2	BMS	SMT	Data standard	Data on position and diagnostic state of	9.3.2	D7.2	Υ
			message with	wagon and dangerous goods, without alarms		6.3.10/12/13 Step	
			wagon in	and with the wagon in motion		1	
			motion				
BMS-3	BMS	TMS	Alarm message	Alarm notification on wagon or dangerous	9.3.3	D7.2	~
				goods.		6.3.10/12/13 Step	
						3, 4	
<b>BMS Subscribing</b>	ribing						
BMS-4	TMS	BMS	Wagon safety	Procedure to follow to secure the	9.4.1	D7.2	
			procedure	train/wagon		6.3.10/12/13 Step	
						5, 6, 7	

Table 9-1 Freight Wagon On Board Monitoring System Interface Summary

GA 777513 Page 74 | 157







# 9.3 Data Published by On board monitoring system to Integration Layer

This is the data published by the On board monitoring System to the Integration Layer available for a TMS and other systems to use.

# 9.3.1 BMS-1 Data standard message with wagon stationary

This is the data sent by MCU when the wagon is stationary. This includes details such as the position of the wagon, the type of wagon and of dangerous goods, finally all the data measured by sensors network on board the wagon.

# 9.3.1.1 Data standard message with wagon stationary Properties

	Interface BMS-1 Properties
Interface ID	BMS-1
Interface Title	Data standard message with wagon stationary
Publisher	The BMS shall be able to publish the data within section 9.3.1.2 to the integration layer.
Publish Trigger	When a train journey is created, the MCU is configured with the overall data of the journey, and with the data of the wagon in which it is installed.
	The MCU is equipped with an acceleration sensor.
	MCU will publish the "Data standard message with wagon stationary" data to the Integration Layer until the acceleration of the wagon is 0, which is until the wagon is stationary.
Expected	Dynamic
Frequency	Approx. published 1 time per 20 minutes, for as long as the wagon is stationary.
Subscribers	TMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Data standard message with wagon stationary" data related to a specified "Train ID" and "MCU ID"
Persistence	The Integration Layer shall persist "Data standard message with wagon
	stationary" data until it receives a new "Data standard message with wagon
	stationary" with the same "Train ID" and "MCU ID" or a new "Data standard
	message with wagon in motion" with the same "Train ID" and "MCU ID".
Length of Validity	The Integration Layer shall identify the "Data standard message with wagon
	stationary" data as Valid until it is overwritten.
Historical Depth	The Integration Layer shall provide the last "Data standard message with wagon
	stationary" data received when a read request is made.

Table 9-2 BMS-1 Data standard message with wagon stationary Properties

#### 9.3.1.2 Data standard message with wagon stationary Data

	, , , , , , , , , , , , , , , , , , , ,	
Data standard message with wagon stationary		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
MCU_ID	ID of the MCU or wagon	Integer

OPEN

GA 777513 Page 75 |







WTyp	Type of wagon	Integer (code)
DGTyp	Type of dangerous goods	Integer (code)
DGQuant	Quantity or weight	Integer
	of DG	
TimeStamp	Current Date and Time	DateTime
GPS_Lat	Current Latitude	String
GPS_Lon	Current Longitude	String
Speed	Current wagon speed	Float
Sensor Node_1 (*)	ID of the Sensor	Integer
Measure_1_1_Type	Measure 1 of sensor node 1 typology	Integer (code)
Measure_1_1_Alarm	Measure 1 of sensor node 1 Alarm severity	Integer (code)
Measure_1_1_Value	Measure 1 of sensor node 1 value	float
Measure_2_1_Type	Measure 2 of sensor node 1 typology	Integer (code)
Measure_2_1_Alarm	Measure 2 of sensor node 1 Alarm severity	Integer (code)
Measure_2_1_Value	Measure 2 of sensor node 1 value	float
Measure_M_1_Type	Measure M of sensor node 1 typology	Integer (code)
Measure_M_1_Alarm	Measure M of sensor node 1 Alarm	Integer (code)
	severity	
Measure_M_1_Value	Measure M of sensor node 1 value	float
Sensor Node_2 (*)	ID of the Sensor	Integer
{all measures of Sensor Node 2}		
Sensor Node_N (*)	ID of the Sensor	Integer
{all measures of Sensor Node N}		

<sup>(\*):</sup> The Attributes of Sensor Node 1 are to be replicated for the number of sensor nodes (N) connected to the MCU

Table 9-3 BMS-1 "Data standard message with wagon stationary" Data

### 9.3.2 BMS-2 Data standard message with wagon in motion

This is the data sent by MCU when the wagon is in motion. This includes details such as the position of the wagon, the speed of the wagon, the type of wagon and of dangerous goods, finally all the data measured by sensors network on board the wagon.

#### 9.3.2.1 Data standard message with wagon in motion Properties

Interface BMS-2 Properties	
Interface ID	BMS-2
Interface Title	Data standard message with wagon in motion
Publisher	The BMS shall be able to publish the data within section 9.3.2.2 to the
	integration layer.
Publish Trigger	When the acceleration sensor of MCU measures a value other than 0, that is the
	wagon is in motion, the MCU will publish the "Data standard message with
	wagon in motion" data to the Integration Layer, with the frequency detailed

OPEN

GA 777513 Page 76 |







	below, , for as long as the wagon is in motion.
Expected	Dynamic
Frequency	Approx. published 1 time per 5 minutes, for as long as the wagon is in motion
Subscribers	TMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Data
	standard message with wagon in motion" data related to a specified "Train ID"
	and "MCU ID"
Persistence	The Integration Layer shall persist "Data standard message with wagon in
	motion" data until it receives a new "Data standard message with wagon in
	motion" with the same "Train ID" and "MCU ID" or a new "Data standard
	message with wagon stationary" with the same "Train ID" and "MCU ID".
Length of Validity	The Integration Layer shall identify the "Data standard message with wagon in
	motion" data as Valid until it is overwritten.
Historical Depth	The Integration Layer shall provide the last "Data standard message with wagon
	in motion" data received when a read request is made.

Table 9-4 BMS-2 Data standard message with wagon in motion Properties

# 9.3.2.2 Data standard message with wagon in motion Data

Data standard message with wagon stationary		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
MCU_ID	ID of the MCU or wagon	Integer
WTyp	Type of wagon	Integer (code)
DGTyp	Type of dangerous goods	Integer (code)
DGQuant	Quantity or weight of DG	Integer
TimeStamp	Current Date and Time	DateTime
GPS_Lat	Current Latitude	String
GPS_Lon	Current Longitude	String
Speed	Current wagon speed	Float
Sensor Node_1 (*)	ID of the Sensor	Integer
Measure_1_1_Type	Measure 1 of sensor node 1 typology	Integer (code)
Measure_1_1_Alarm	Measure 1 of sensor node 1 Alarm severity	Integer (code)
Measure_1_1_Value	Measure 1 of sensor node 1 value	float
Measure_2_1_Type	Measure 2 of sensor node 1 typology	Integer (code)
Measure_2_1_Alarm	Measure 2 of sensor node 1 Alarm severity	Integer (code)
Measure_2_1_Value	Measure 2 of sensor node 1 value	float
Measure_M_1_Type	Measure M of sensor node 1 typology	Integer (code)
Measure_M_1_Alarm	Measure M of sensor node 1 Alarm severity	Integer (code)
Measure_M_1_Value	Measure M of sensor node 1 value	float
Sensor Node_2 (*)	ID of the Sensor	Integer

OPEN

GA 777513 Page 77 |







{all measures of Sensor Node 2}		
Sensor Node_N (*)	ID of the Sensor	Integer
{all measures of Sensor Node N}		

<sup>(\*):</sup> The Attributes of Sensor Node 1 are to be replicated for the number of sensor nodes (N) connected to the MCU

Table 9-5 BMS-2 "Data standard message with wagon in motion" Data

# 9.3.3 BMS-3 Alarm message

This is the data sent by MCU when one or more measures are out of limits, that is in alarm. This includes details such as the position of the wagon, the speed of the wagon, the type of wagon and of dangerous goods, finally the type, source and value of the measure(s) in alarm.

# 9.3.3.1 Alarm message Properties

	Interface BMS-3 Properties
Interface ID	BMS-3
Interface Title	Alarm message
Publisher	The BMS shall be able to publish the data within section 9.3.3.2 to the integration layer.
Publish Trigger	When the MCU measures a value or more value out of limits, the MCU will publish the "Alarm message" data to the Integration Layer, both with the wagon stationary and in motion.
Expected	BMS-3 is published only once per alarm.
Frequency	
Subscribers	TMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Alarm message" data related to a specified "Train ID" and "MCU ID"
Persistence	The Integration Layer shall persist "Alarm message" data until a read request is made.
Length of Validity	The Integration Layer shall identify the "Alarm message" data as Valid until a read request is made.
Historical Depth	The Integration Layer shall provide the last "Alarm message" data received when a read request is made.

**Table 9-6 BMS-3 Alarm message Properties** 

# 9.3.3.2 Alarm message Data

3.0.0.1		
Alarm message		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
MCU_ID	ID of the MCU or wagon	Integer

OPEN

G A 777513 Page 78 |







WТур	Type of wagon	Integer (code)
DGTyp	Type of dangerous goods	Integer (code)
DGQuant	Quantity or weight	Integer
	of DG	
TimeStamp	Current Date and Time	DateTime
GPS_Lat	Current Latitude	String
GPS_Lon	Current Longitude	String
Speed	Current wagon speed	Float
Sensor Node_Alarm (*)	ID of the Sensor that has detected the	Integer
	measure in alarm	
Measure_Alarm_Type	Measure 1 of sensor node 1 typology	Integer (code)
Measure_Alarm_Level	Measure 1 of sensor node 1 Alarm severity	Integer (code)
Measure_Alarm_Value	Measure 1 of sensor node 1 value	float

<sup>(\*):</sup> The Attributes of Sensor Node\_Alarm are to be replicated for any other sensors with in alarm measurements.

Table 9-7 BMS-3 "Alarm message" Data

# 9.4 Data Read or Subscribed by BMS system to Integration Layer

This is the data read or subscribed to by the On Board Monitoring System from the Integration Layer.

# 9.4.1 BMS-4 Wagon safety procedure

When TMS receives the notification of one or more alarms, following an analysis of these, if actions are needed to secure the train to which the wagon with active alarms belongs, TMS publish the "Wagon safety procedure" data.

# 9.4.1.1 Wagon safety procedure Properties

	Interface BMS-4 Properties
Interface ID	BMS-4
Interface Title	Wagon safety procedure
Publisher	The TMS shall be able to publish the data within section 9.4.1.2 to the integration layer.
Publish Trigger	When the TMS receives the notification of one or more alarms, following an analysis of these, if actions are needed to secure the train to which the wagon with active alarms belongs, TMS publish the "Wagon safety procedure" data to the Integration Layer.
Expected Frequency	BMS-4 is published only once per alarm.
Subscribers	TMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Wagon safety procedure" data related to a specified "MCU ID". The "MCU ID"

OPEN

GA 777513 Page 79 |







	must be relative to an MCU installed on the locomotive.
Persistence	The Integration Layer shall persist "Wagon safety procedure" data until a read
	request is made.
Length of Validity	The Integration Layer shall identify the "Wagon safety procedure" data as Valid
	until a read request is made.
Historical Depth	The Integration Layer shall provide the last "Wagon safety procedure" data
	received when a read request is made.

**Table 9-8 BMS-4 Wagon safety procedure Properties** 

# 9.4.1.2 Wagon safety procedure Data

Alarm message		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
MCU_ID	ID of the MCU installed on the locomotive	Integer
Wtyp_alarm	Type of wagon with alarm active	Integer (code)
DGTyp	Type of dangerous goods	Integer (code)
DGQuant	Quantity or weight of DG	Integer
TimeStamp	Current Date and Time	DateTime
Proc	Procedure to be performed	Integer (code)

Table 9-9 BMS-4 "Wagon safety procedure" Data







# 10 Optimal Time Slot and Itinerary for Dangerous Goods

# 10.1 Use Case summary

# Use Case ID (D7.2 5.3.11) Optimal Time slot and Itinerary for DG

The use case describes an innovative scenario to determine the optimal time window and the optimal itinerary to carry the dangerous goods from a starting point A to an arrival point B, also minimizing the risk of accidents along the railway resulting in damage of infrastructure, buildings and people.

The solution of this optimal allocation problem is based on the algorithm "Branch and Bound", and keeps in account parameters of wagons and dangerous goods, infrastructures near the railway, social and climatic aspects and emergency related items.

# **10.2 Interface Summary**

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side. Although some of the interfaces belong to TMS or the FRU, as these are described from the perspective of this use case, they are all currently identified as "OTI" interfaces.










Figure 10-1 Interface Overview - Optimal Time Slot and Itinerary for Dangerous Goods







The table below shows a summary of the interface related to Optimal Time Slot and Itinerary for Dangerous Goods

Interface ID	Publisher	Subscriber	Interface Title	Interface Description	Data Description	Related Use Case Steps	Prototyped
OTI Publishing	ning						
OTI-7	ОТІ	TMS, FRU	Optimal Itinerary	The optimal itinerary and time slot to carry	10.3.1	D7.2 5.3.11	~
			and Time slot	dangerous goods, calculated by OTI module		Step 3, 4	
OTI Subscribing	ibing						
OTI-1	SMT	OTI	General-Data	General data about the train journey	10.4.1	D7.2 5.3.11	~
						Steps 2	
OTI-2	FRU	OTI	Wagons-Data	Detailed data about wagons and dangerous	10.4.2	D7.2 5.3.11	Υ
				goods		Steps 2	
OTI-3	SMT	OTI	Itin-Infra	Factors related to railway infrastructure (for each	10.4.3	D7.2 5.3.11	~
				itinerary)		Steps 2	
OTI-4	TMS	OTI	Itin-Social	Factors related to social aspects (for each	10.4.4	D7.2 5.3.11	Υ
				itinerary)		Step 2	
OTI-5	TMS	OTI	Itin-Clima	Factors related to climatic aspects (for each	10.4.5	D7.2 5.3.11	~
				itinerary)		Steps 2	
OTI-6	TMS	OTI	Itin-Emergency	factors related to emergency response (for each	10.4.6	D7.2 5.3.11	~
				itinerary)		Steps 2	

Table 10-1 Optimal Time Slot and Itinerary for Dangerous Goods Interface Summary

OPEN

Page 83 | 157







# 10.3 Data Published by Optimal Time Slot and Itinerary for Dangerous Goods (OTI) to Integration Layer

This is the data published by the Optimal Time Slot and Itinerary for Dangerous Goods to the Integration Layer available for a TMS and other systems to use.

# 10.3.1 OTI-7 Optimal Itinerary and Time Slot

This is the Optimal Itinerary and Time Slot calculated by the algorithm "Branch and Bound", based on all the data available in input, detailed in the section 10.4, and published to the Integration Layer.

#### 10.3.1.1 **Optimal Itinerary and Time Slot Properties**

	Interface OTI-7 Properties
Interface ID	OTI-7
Interface Title	Optimal Itinerary and Time Slot
Publisher	The OTI shall be able to publish the data within section 10.3.1.2 to the
	integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS and FRU
	publishes to IL main characteristics of the train and of the dangerous goods
	(quantity and typology), all data related to population, cities, villages, countries,
	industrial sites of the areas where the railway lines pass.
	The OTI module using all the data available, estimates the optimal itinerary
	(among those available) and the optimum time slot in which carry out the
	established itinerary , to minimize the risk of accidents along the railway
	resulting in damage of infrastructure, buildings and people.
	The OTI module publishes the results to the Integration Layer.
Expected	OTI-7 is published once for each train carrying dangerous goods created in TMS
Frequency	TAGE FRU
Subscribers	TMS, FRU
Filter	The Integration Layer shall provide the subscriber with the ability to read
	"Optimal Itinerary and Time Slot" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Optimal Itinerary and Time Slot" until the
	"Opt_Date_time_end" is 48 hours in the past.
Length of Validity	The Integration Layer shall identify the "Optimal Itinerary and Time Slot" data as
	Valid until it is deleted, which occurs once the train number ID has reached its
	final destination.
Historical Depth	The Integration Layer shall provide the last "Optimal Itinerary and Time Slot"
	data received when a read request is made.

**Table 10-2 OPT-7 Optimal Itinerary and Time Slot Properties** 

GA 777513 Page 84 |







# 10.3.1.2 Optimal Itinerary and Time Slot Data

Optimal Itinerary and Time Slot		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
StartPointA	Latitude and Longitude of point A (start)	string
EndPointB	Latitude and Longitude of point B (arrival)	string
Opt_Itin	Number of the Optimum Itinerary	Integer (code)
Opt_Date_time_start	Optimum Date and Time to start the train journey	DateTime
Opt_Date_time_end	Optimum Date and Time to end the train journey	DateTime

Table 10-3 OTI-7 "Optimal Itinerary and Time Slot" Data

# 10.4 Data Read or Subscribed by Optimal Time Slot and Itinerary for Dangerous Goods (OTI) to Integration Layer

This is the data read or subscribed to by the "Optimal itinerary and time slot" from the Integration Layer.

#### 10.4.1 OTI-1 General-Data

When a train journey, with the train carrying dangerous goods, is created, TMS publish general data about the train journey to the Integration Layer, available for the OTI module.

#### 10.4.1.1 General-Data Properties

	Interface OTI-1 Properties
Interface ID	OTI-1
Interface Title	General-Data
Publisher	The TMS shall be able to publish the data within section 10.4.1.2 to the integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS publishes to IL main characteristics of the train and the number and codes of the possible itineraries that the train can pass through to go from point A (starting point) to point B (arrival point).
Expected Frequency	OTI-1 is published once for each train carrying dangerous goods created in TMS
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read "General-Data" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "General-Data" until the "Max_arrival_time" is 48 hours in the past.
Length of Validity	The Integration Layer shall identify the "General-Data" data as Valid until it is deleted, which occurs once the train number ID has reached its final destination.

GA 777513 Page 85 |







Historical Depth

The Integration Layer shall provide the last "General-Data" data received when a read request is made.

# **Table 10-4 OTI-1 General-Data Properties**

#### 10.4.1.2 General-Data Data

General Data		
Attribute	Attribute description	Admitted values
Train ID	Number of the Train	Integer
StartPointA	Latitude and Longitude of point A (start)	string
EndPointB	Latitude and Longitude of point B (arrival)	string
Nwag	Number N of wagons belonging to the train	Integer
Nwag_DG	Number N of wagons carrying dangerous goods belonging to the train	Integer
Mitin	Number M of possible itineraries to go from A to B	Integer
Itin-1-ID (*)	Code of Itinerary n.1	Integer
Itin-2-ID	Code of Itinerary n.2	Integer
Itin-M-ID	Code of Itinerary n.M	Integer

<sup>(\*):</sup> The Attribute Itin-1-ID is repeated for the number of possible itinerary (M)

#### Table 10-5 "General-Data" Data

#### 10.4.2 OTI-2 Wagons-Data

When a train journey, with the train carrying dangerous goods, is created, FRU publish the details of the wagons carrying dangerous goods and characteristics of the dangerous goods to the Integration Layer, available for the OTI module.

# 10.4.2.1 Wagons-Data Properties

	Interface OTI-2 Properties
Interface ID	OTI-2
Interface Title	Wagons-Data
Publisher	The FRU shall be able to publish the data within section 0 to the integration
	layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the FRU publishes to
	IL main characteristics, number and details, of the wagons carrying dangerous
	goods and the physical details of the dangerous goods itself.
Expected	OTI-2 is published once for each train carrying dangerous goods created in TMS
Frequency	
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read
	"Wagons-Data" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Wagons-Data" until the "Max_arrival_time"
	is 48 hours in the past.

GA 777513 Page 86 |







Length of Validity	The Integration Layer shall identify the "Wagons-Data" data as Valid until it is
	deleted, which occurs once the train number ID has reached its final destination.
Historical Depth	The Integration Layer shall provide the last "Wagons-Data" data received when a
	read request is made.

# **Table 10-6 OTI-2 Wagons-Data Properties**

# 10.4.2.2 Wagons-Data Data (\*)

Wagons-Data		
Attribute	Attribute description	Admitted
		values
Wagon ID	ID or number of the wagon	Integer
Wagon_POS	Position of the wagon in the train	Integer
WTyp	Type of wagon	Integer (code)
DGTyp	Type of dangerous goods	Alphanumeric
DGQuant	Quantity or weight	Float
	of DG	
DGClass	Class of dangerous goods	Integer (code)
DGExpl	Flag to identify if explosive	True/False
DGEmerg	Emergency code related to dangerous goods	Integer (code)

<sup>(\*)</sup> There is one instance of this table for any wagon belonging to the train

# Table 10-7 "Wagons-Data" Data

#### 10.4.3 OTI-3 Itin-Infra

When a train journey, with the train carrying dangerous goods, is created, TMS publish the details of elements related to the infrastructures of the possible itineraries that the train can run across to go from point A to point B to the Integration Layer, available for the OTI module.

# 10.4.3.1 Itin-Infra Properties

	Interface OTI-3 Properties
Interface ID	OTI-3
Interface Title	Itin-Infra
Publisher	The TMS shall be able to publish the data within section 10.4.3.2 to the integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS publishes to IL full details of the elements related to the infrastructures of the itineraries that the train can pass through to go from point A (starting point) to point B (arrival point).
Expected	OTI-3 is published once for each train carrying dangerous goods created in TMS
Frequency	
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read "Itin-Infra" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Itin-Infra" until the "Max_arrival_time" is 48

GA 777513 Page 87 |







	hours in the past.
Length of Validity	The Integration Layer shall identify the "Itin-Infra" data as Valid until it is deleted
	, which occurs once the train number ID has reached its final destination.
Historical Depth	The Integration Layer shall provide the last "Itin-Infra" data received when a read
	request is made.

**Table 10-8 ITI-3 Itin-Infra Properties** 

# 10.4.3.2 Itin-Infra (\*)

Itin-Infra		
Attribute	Attribute description	Admitted values
Itin ID	Number of the itinerary	Integer (1M)
Itin_Volt_type	Voltage type	AC/DC
Itin_Volt_value	Voltage value [V]	Integer
Itin_NTracks	Number of tracks	Integer
Itin_Guage	Gauge [mm]	Integer
Itin_Slope	Maximum longitudinal slope [‰]	Integer
Itin_alt_min	Minimum altitude [m asl]	Integer
Itin_alt_max	Maximum altitude [m asl]	Integer
Itin_category	Line Category	Code
Itin_Speed_lim	Speed Limit [km/h]	Integer
Itin_Tr_type	type of railway traffic	Code
Itin_Veh_gau	Line vehicle gauge	Code
Itin_tunnel_num	Line tunnels number	Integer
Itin_bridge_num	Line bridges number	Integer
Itin_Station_num	Line bridges number	Integer
ltin_Inter_p_num	Line Intersection points number	Integer
Itin_Cross_num	Line level crossing number	Integer

<sup>(\*)</sup> There is one instance of this table for any possible itinerary

#### Table 10-9 "Itin-Infra" Data

#### 10.4.4 OTI-4 Itin-Social

When a train journey, with the train carrying dangerous goods, is created, TMS publish the details of social aspects related to possible itineraries that the train can run across to go from point A to point B to the Integration Layer, available for the OTI module.

#### 10.4.4.1 Itin-Social Properties

	Interface OTI-4 Properties
Interface ID	OTI-4
Interface Title	Itin-Social
Publisher	The TMS shall be able to publish the data within section 10.4.4.2 to the
	integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS publishes to

GA 777513 Page 88 |







	IL full details of the social aspects related to the itineraries that the train can pass through to go from point A (starting point) to point B (arrival point).
Expected	OTI-4 is published once for each train carrying dangerous goods created in TMS
Frequency	
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read "Itin-
	Social" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Itin-Social" until the "Max_arrival_time" is 48
	hours in the past.
Length of Validity	The Integration Layer shall identify the "Itin-Social" data as Valid until it is
	deleted, which occurs once the train number ID has reached its final destination.
Historical Depth	The Integration Layer shall provide the last "Itin-Social" data received when a
	read request is made.

**Table 10-10 OTI-4 Itin-Social Properties** 

# 10.4.4.2 Itin-Social (\*)

Itin-Social		
Attribute	Attribute description	Admitted values
Itin ID	Number of the itinerary	Integer (1M)
ltin_rangeInt	Range of interest [m]	Integer
Itin_town	Number of towns/villages near the railway	Integer
Itin_peo_dens	People average density [n/km²]	Integer
Itin_territ	Territorial context	String
Itin_Land_use	Land intended use	String
Itin_indust	Number of industrial sites with high accident risk	Integer
Itin_comm	Number of commercial/logistic sites	Integer
Itin_hosp	Number of hospitals	Integer
Itin_schools	Number of schools	Integer
Itin_Chur	Number of churches	Integer

# (\*) There is one instance of this table for any possible itinerary

Table 10-11 "Itin-Social" Data

# 10.4.5 OTI-5 Itin-Clima

When a train journey, with the train carrying dangerous goods, is created, TMS publish the details of climatic aspects related to possible itineraries that the train can run across to go from point A to point B to the Integration Layer, available for the OTI module.

# 10.4.5.1 Itin-Clima Properties

	Interface OTI-5 Properties		
Interface ID	OTI-5		

G A 777513 Page 89 |







Interface Title	Itin-Clima
Publisher	The TMS shall be able to publish the data within section 10.4.5.2 to the
	integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS publishes to
	IL full details of the climatic aspects related to the itineraries that the train can
	pass through to go from point A (starting point) to point B (arrival point).
Expected	OTI-5 is published once for each train carrying dangerous goods created in TMS
Frequency	
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read "Itin-
	Clima" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Itin-Clima" until the "Max_arrival_time" is 48
	hours in the past.
Length of Validity	The Integration Layer shall identify the "Itin-Clima" data as Valid until it is
	deleted, which occurs once the train number ID has reached its final destination.
Historical Depth	The Integration Layer shall provide the last "Itin-Clima" data received when a
	read request is made.

**Table 10-12 OTI-5 Itin-Clima Properties** 

# 10.4.5.2 Itin-Clima (\*)

Itin-Clima		
Attribute	Attribute description	Admitted values
Itin ID	Number of the itinerary	Integer (1M)
Itin_Temp_Max	Max Temperature about the itinerary area [°C]	Integer
Itin_Temp_Min	Min Temperature about the itinerary area [°C]	Integer
Itin_Temp_Med	Medium Temperature about the itinerary area [°C]	Integer
Itin_Press_Med	Medium Pressure about the itinerary area [mbar]	Integer
Itin_Solar_Med	Medium Solar Radiation about the itinerary area [kW/m²]	Integer
Itin_Hum_Med	Medium Humidity about the itinerary area [%]	Integer
Itin_Wind_dir	Wind direction about the itinerary area	string
Itin_Wind_speed	Wind speed about the itinerary area [m/s]	Integer
Itin_Cloud	Night cloud cover about the itinerary area [%]	Integer
Itin_Pasquill	Pasquill stability Class about the itinerary area	Integer (code)
Itin_Soil	Soil roughness about the itinerary area	Integer (code)

# (\*) There is one instance of this table for any possible itinerary

GA 777513 Page 90 |







#### Table 10-13 "Itin-Clima" Data

# 10.4.6 OTI-6 Itin-Emergency

When a train journey, with the train carrying dangerous goods, is created, TMS publish the details of emergency response related to possible itineraries that the train can run across to go from point A to point B to the Integration Layer, available for the OTI module.

# 10.4.6.1 *Itin-Emergency Properties*

	Interface OTI-6 Properties
Interface ID	OTI-6
Interface Title	Itin-Emergency
Publisher	The TMS shall be able to publish the data within section 10.4.6.2 to the integration layer.
Publish Trigger	When a train journey carrying dangerous goods is created, the TMS publishes to IL full details of the emergency response aspects related to the itineraries that the train can pass through to go from point A (starting point) to point B (arrival point).
Expected	OTI-6 is published once for each train carrying dangerous goods created in TMS
Frequency	
Subscribers	ОТІ
Filter	The Integration Layer shall provide the subscriber with the ability to read "Itin- Emergency" data related to a specified "Train ID"
Persistence	The Integration Layer shall persist "Itin-Emergency" until the "Max_arrival_time" is 48 hours in the past.
Length of Validity	The Integration Layer shall identify the "Itin-Emergency" data as Valid until it is deleted, which occurs once the train number ID has reached its final destination.
Historical Depth	The Integration Layer shall provide the last "Itin-Emergency" data received when a read request is made.

# **Table 10-14 OTI-6 Itin-Emergency Properties**

# 10.4.6.2 *Itin-Emergency (\*)*

Itin-Emergency			
Attribute	Attribute description	Admitted values	
Itin ID	Number of the itinerary	Integer (1M)	
ltin_rangeInt	Range of interest [m]	Integer	
Itin_fire_brig	Number of fire brigade headquarters	Integer	
Itin_Aid	Number of emergency first aid	Integer	
Itin_Vehi_speed	Medium speed emergency vehicles [Km/h]	Integer	
Itin_Trav_time	Medium travel time emergency vehicles [min]	Integer	

(\*) There is one instance of this table for any possible itinerary

Table 10-15 "Itin-Emergency" Data

G A 777513 Page 91 |







# 11 Timetable Optimization Module

# 11.1 Use Case summary

#### Use Case ID (D7.2 5.3.14) Optimize timetable region

In the annual (long-term) timetable planning process, FRUs submit train requests (delivery commitment requests) to a request system (RS) managed by the IM. Based on these requests and using a timetable planning system (TPS), the timetable planner at the IM creates a timetable draft for (a region of) the railway network. The timetable draft can include non-regulated conflicts and may also not be optimized according to relevant evaluation criteria. To tune the timetable, the planner at the IM uses a timetable optimization module (TOM), which calculates an optimal timetable based on the draft, while respecting the constraints in the requests. The optimization is based on some evaluation criteria. The planner can iteratively adjust the criteria and reoptimize until he/she is satisfied.

#### Use Case ID (D7.2 5.3.15) Add train to timetable

In ad hoc timetable planning, the IM must add a new train request (delivery commitment request) from an FRU to an existing timetable. When planning for the new request, the IM cannot change established delivery commitments, but there can nevertheless exist some flexibility in the timetable, allowing changes that do not violate the established delivery commitments. Thus, the new request should be added utilizing the available free capacity and the flexibility in the existing timetable. The planner at the IM uses the timetable optimization module to find a way to insert the new train request that is feasible with respect to capacity restrictions from infrastructure, the existing timetable, and selected timetable optimization criteria. The planner can iteratively adjust the criteria and reoptimize until he/she is satisfied.

#### 11.2 Interface Summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side.

GA 777513 Page 92 |










Figure 11-1 Interface Overview – Timetable Optimization Module







The table below shows a summary of the interfaces related to the timetable optimization module and the use cases.

Interface ID	Puhlisher	Subscriber	Interface Title	Interface Description	Data	Related Hse Case	Prototyped
		300			Description		
TOM Publishing							
TOM-1	MOT	SAL	Optimized Timetable	A timetable optimized by the	11.3.1	D7.2 5.3.14 Step 5,	
				Timetable Optimization Module.		D7.2 5.3.15 Step 5	
TOM Subscribing	lg						
TOM-2	RS	MOT	Delivery Commitment	A request for a train.	11.4.1	D7.2 5.3.14 Step 1,	
			Request			D7.2 5.3.15 Step 1	
TOM-3	TPS	TOM	Planning Conditions	Infrastructure data, time separation	11.4.2	D7.2 5.3.14 Step 1,	
				of train events, and possessions.		D7.2 5.3.15 Step 1	
TOM-4	TPS	TOM	Input Timetable	A timetable that is to be optimized	11.4.3	D7.2 5.3.14 Step 1,	
				or to which a new train is to be		D7.2 5.3.15 Step 1	
				added.			

Table 11-1 Timetable Optimization Module Interface Summary

GA 777513 Page 94 | 157







# 11.3 Data Published by Timetable Optimization Module to Integration Layer

This is the data published by the Timetable Optimization Module to the Integration Layer available for a Timetable Planning System and other systems to use.

Any "admitted values" surrounded in curly braces "{ }" is an instance of a different table in this chapter.

### 11.3.1 TOM-1 Optimized Timetable

These data describe a timetable (for a certain railway network and a certain period of time) that has been optimized by the Timetable Optimization Module. This includes details such as the arrival and departure times of the trains in the timetable.

#### 11.3.1.1 Optimized Timetable Properties

	Interface TOM-1 Properties
Interface ID	TOM-1
Interface Title	Optimized Timetable
Publisher	The TOM shall be able to publish the data within sections 11.3.1.2, 11.3.1.3, and
	11.3.1.4 to the integration layer.
Publish Trigger	When an optimized timetable has been created (and the timetable planner has
	approved it), the TOM shall publish it to the Integration Layer.
Expected	Dynamic
Frequency	May be published 1 time per 5 minutes if the planners use the TOM frequently.
Subscribers	TPS
Filter	The Integration Layer shall provide the subscriber with the ability to read
	"Optimized Timetable" data related to a specified train assignment or train
	number, control point or pair of control points, and/or period of time.
Persistence	The Integration Layer shall persist "Optimized Timetable" data at least until
	every Date of every Train Timetable has passed or until the data are deleted on
	request by the planner or replaced by a new version.
Length of Validity	The Integration Layer shall identify "Optimized Timetable" data as valid until
	they are deleted on request by the planner or replaced by a new version.
Historical Depth	The Integration Layer shall provide the last "Optimized Timetable" data received
	when a read request is made.

**Table 11-2 TOM-1 Optimized Timetable Properties** 

#### 11.3.1.2 Timetable Control Point

Arrival and departure times and their related parameters for a train at a control point of the route. Based on Table 8.26 (Timetable Control Point) in X2Rail-2 D6.1.

Timetable Control Point		
Attribute	Attribute description	Admitted values
Control Point	Reference to an identified location (node) where it is allowed to define a time value for a train movement (stop or pass).	String
Committed Arrival Time	Arrival time of the train at the control point, stated as a delivery commitment from the IM	Time

GA 777513 Page 95 |







		1
	to the FRU. Only defined if an arrival time has	
	been included in the corresponding delivery	
	commitment request from the FRU.	
Technical Arrival Time	Arrival time of the train at the control point.	Time
	This time is internal to the IM.	
Committed Departure Time	Departure time of the train from the control	Time
	point, stated as a delivery commitment from	
	the IM to the FRU. Only defined if a	
	departure time has been included in the	
	corresponding delivery commitment request	
	from the FRU.	
Technical Departure Time	Departure time of the train from the control	Time
	point. This time is internal to the IM.	
Movement Type	Defines if the train stops or passes at the	Listed [Stop, Pass]
	control point.	
Arrival Track	Identification of the control point track where	String
	it is defined that the train arrives at the	
	control point.	
Departure Track	Identification of the control point track where	String
	it is defined that the train leaves the control	
	point.	
Stop Type	Scheduled kind of stop defined for a train.	Listed [Commercial stop,
		Technical stop,]

Table 11-3 TOM-1 "Optimized Timetable" (Timetable Control Point) Data

# 11.3.1.3 *Train Timetable*

Timetable for a single train, potentially running on several dates. Based on Table 8.27 (Scheduled Timetable) in X2Rail-2 D6.1.

Train Timetable		
Attribute	Attribute description	Admitted values
Train number	Train number	Numeric
N x Date	The start dates of the train.	Complex [Date]
Train Assignment	Concept to keep together trains that run on different dates and have timetables that are similar but include variations in routes, traffic exchange, times or other characteristics.	Numeric
N x Timetable Control Point	Set of ordered Timetable Control Points defining the complete timetable for the train.	Complex [{Timetable Control Point}]

Table 11-4 TOM-1 "Optimized Timetable" (Train Timetable) Data

### 11.3.1.4 Full Timetable

This is the full timetable for the railway network and period.

Full Timetable		
Attribute Attribute description Admitted values		
N x Train Timetable	All included timetables for single trains.	Complex [{Train Timetable}]

GA 777513 Page 96 |







# Table 11-5 TOM-1 "Optimized Timetable" (Full Timetable) Data

# 11.4 Data Read or Subscribed to by the TOM from the Integration Layer

This is the data read or subscribed to by the Timetable Optimization Module from the Integration Layer.

Any "admitted values" surrounded in curly braces "{ }" is an instance of a different table in this chapter.

# 11.4.1 TOM-2 Delivery Commitment Request

These data describe a request for a train. This includes requested arrival and departure times as well as restrictions modelling situations that require the linking of the departure or arrival of two trains.

#### 11.4.1.1 Delivery Commitment Request Properties

	Interface TOM-2 Properties		
Interface ID	TOM-2		
Interface Title	Delivery Commitment Request		
Publisher	The RS shall be able to publish the data in sections 11.4.1.2, 11.4.1.3, 11.4.1.4,		
	and 11.4.1.5 to the integration layer.		
Publish Trigger	When an FRU has submitted a delivery commitment request, the RS shall publish		
	it to the Integration Layer.		
Expected	Dynamic		
Frequency	May be published 1 time per 5 minutes if delivery commitment requests are		
	submitted frequently.		
Subscribers	TOM		
Filter	The Integration Layer shall provide the subscriber with the ability to read		
	"Delivery Commitment Request" data related to a specified train assignment or		
	variant number, control point or pair of control points, and/or period of time.		
Persistence	The Integration Layer shall persist "Delivery Commitment Request" data until		
	they are deleted on request by the FRU or replaced by a new version.		
Length of Validity	The Integration Layer shall identify the "Delivery Commitment Request" data as		
	valid until they are deleted on request by the FRU or replaced by a new version.		
Historical Depth	The Integration Layer shall provide the last "Delivery Commitment Request" data		
	received (for a certain train assignment or variant number and a certain period		
	of time) when a read request is made.		

**Table 11-6 TOM-2 Delivery Commitment Request Properties** 

#### 11.4.1.2 Requested Timetable Control Point

This is the requested arrival and departure times and their related parameters for a train at a control point of the route. Based on Table 8.26 (Timetable Control Point) in X2Rail-2 D6.1.

Requested Timetable Control Point		
Attribute Attribute description Admitted values		Admitted values
Control Point	Reference to an identified location (node)	String
	where it is allowed to define a time value for	

GA 777513 Page 97 |







	a train movement (stop or pass).	
Requested Arrival Time	The arrival time at the control point	Time
	requested by the FRU.	
Earliest Arrival Time	The earliest arrival time at the control point	Time
	accepted by the FRU.	
Latest Arrival Time	The latest arrival time at the control point	Time
	accepted by the FRU.	
Requested Departure Time	The departure time from the control point	Time
	requested by the FRU.	
Earliest Departure Time	The earliest departure time from the control	Time
	point accepted by the FRU.	
Latest Departure Time	The latest departure time from the control	Time
	point accepted by the FRU.	
Minimum Dwell Time	Minimum stop duration for the train.	Numeric

Table 11-7 TOM-2 "Delivery Commitment Request" (Requested Timetable Control Point)

Data

# 11.4.1.3 Requested Train Timetable Part

A Requested Train Timetable Part is a part of a Requested Train Timetable where a certain timing load (which is associated with a group of train types characterized by their rolling stock, weight, and maximum speed) is used. Based on Table 8.27 (Scheduled Timetable) in X2Rail-2 D6.1.

Requested Train Timetable Part		
Attribute	Attribute description	Admitted values
Timing Load Name	The name of the timing load.	String
N x Requested Timetable Control	Set of ordered Requested Timetable Control	Complex [{Requested
Point	Points defining the requested timetable part	Timetable Control Point}]
	for the train.	
Length	The length of the train.	Numeric

Table 11-8 TOM-2 "Delivery Commitment Request" (Requested Train Timetable Part) Data

# 11.4.1.4 Requested Train Timetable

This is the requested timetable for a single train, potentially running on several dates.

Requested Train Timetable		
Attribute	Attribute description	Admitted values
Variant Number	Identifies the train variant, of which there might be several belonging to the same Train Assignment.	Numeric
N x Date	The start dates of the train.	Complex [Date]
Train Assignment	Concept to keep together trains that run on different dates and have timetables that are similar but include variations in routes, traffic exchange, times or other characteristics.	Numeric

GA 777513 Page 98 |







Category	Category describing the train and the priority	Listed [Freight fast,
	of the train.	Freight flexibility, Trunk
		commuter, Regional max,
		Distant standard,]
N x Requested Train Timetable	Set of ordered Requested Train Timetable	Complex [{Requested
Part	Parts defining the requested timetable for	Train Timetable Part}]
	the train.	
Anchor Point	The Control Point where the deviations in the	String
	timetable from the requested arrival and	
	departure times will usually be the smallest.	

Table 11-9 TOM-2 "Delivery Commitment Request" (Requested Train Timetable) Data

#### 11.4.1.5 Trains Restriction

The restrictions model situations that require linking the departure or arrival of two trains at a point because of operating reasons or because of transfers of rolling stock, crew members or passengers between the trains. Based on Table 8.64 (Trains Restriction) in X2Rail-2 D6.1.

Trains Restriction		
Attribute	Attribute description	Admitted values
Control Point	Reference to an identified Node where the	String
	restriction is defined.	
Train 1	The first train (timetable) involved in the	{Requested Train
	restriction.	Timetable}
Train 2	The second train (timetable) involved in the	{Requested Train
	restriction.	Timetable}
Category	Category describing the priority of the	Listed [Connection
	restriction.	Freight transport high,
		Connection Passenger
		service high,]
Restriction Type	Type of restriction according to the affected	Listed [Rolling stock,
	element.	Crew, Passengers,]
Train 1 Event	Event affected by the restriction of the first	Listed [Arrival,
	Train.	Departure]
Train 2 Event	Event affected by the restriction of the	Listed [Arrival,
	second train.	Departure]
Lapse	Minimum time between both events.	Numeric

Table 11-10 TOM-2 "Delivery Commitment Request" (Trains Restriction) Data

# 11.4.2 TOM-3 Planning Conditions

These data describe infrastructure, time separation of train events, and possessions.

G A 777513 Page 99 |







# 11.4.2.1 Planning Conditions Properties

Interface TOM-3 Properties		
Interface ID	TOM-3	
Interface Title	Planning Conditions Properties	
Publisher	The TPS shall be able to publish the data in sections 11.4.2.2, 11.4.2.3, 11.4.2.4,	
	11.4.2.5, 11.4.2.6, and 11.4.2.7 to the integration layer.	
Publish Trigger	When planning conditions have been entered in a TPS, it shall publish them to	
	the Integration Layer.	
Expected	Rather static	
Frequency	Base version is published 1 time per year, updates are published more	
	frequently.	
Subscribers	TOM	
Filter	The Integration Layer shall provide the subscriber with the ability to read	
	"Planning Conditions" data related to specified nodes or tracks, and/or a	
	specified period of time.	
Persistence	The Integration Layer shall persist "Planning Conditions" data until they are	
	deleted on request by the planner or replaced by a new version.	
Length of Validity	The Integration Layer shall identify the "Planning Conditions" data as valid until	
	they are deleted on request by the planner or replaced by a new version, or until	
	the end of their validity period (as indicated in the data).	
Historical Depth	The Integration Layer shall provide the last "Planning Conditions" data received	
	(for a certain railway network and a certain period of time) when a read request	
	is made.	

**Table 11-11 TOM-3 Planning Conditions Properties** 

# 11.4.2.2 *Track*

This is a physical track (one of potentially several) in a link between two nodes (stations or similar) in a railway network.

Track		
Attribute	Attribute description	Admitted values
Origin	References one of the endpoints (nodes) of the track, namely the one that is reached first by a train travelling in the preferred direction of the track.	{Node}
Destination	References one of the endpoints (nodes) of the track, namely the one that is reached last by a train travelling in the preferred direction of the track.	{Node}
Length	Length of track.	Numeric
Track ID	Unique identifier of the track.	String
Start of validity period	The start of validity for these data	Datetime
End of validity period	The end of validity for these data	Datetime

Table 11-12 TOM-3 "Planning Conditions" (Track) Data

G A 777513 Page 100 |







# 11.4.2.3 *Timing Link*

A Timing Link provides the minimum run time between two subsequent nodes for a certain timing load. The minimum run time is different depending on the stop pattern of the train.

Timing Link			
Attribute	Attribute description	Admitted values	
Timing Load Name	The name of the timing load.	String	
Track	References the track that the timing link is for.	{Track}	
Preferred direction	Indicates if this timing link is for the preferred direction of the track.	Boolean	
Stop-stop time	Minimum run time between the two endpoints if the train stops at both of them.	Numeric	
Stop-full speed time	Minimum run time between the two endpoints if the train stops at the first one but moves at full speed at the second one.	Numeric	
Full speed-stop time	Minimum run time between the two endpoints if the train moves at full speed at the first one but stops at the second one.	Numeric	
Full speed-full speed time	Minimum run time between the two endpoints if the train moves at full speed at both of them.	Numeric	
Start of validity period	The start of validity for these data	Datetime	
End of validity period	The end of validity for these data	Datetime	

Table 11-13 TOM-3 "Planning Conditions" (Timing Link) Data

### 11.4.2.4 *Node*

A location (station, stopping point, signal ...) where it is allowed to define a time value for a train movement (stop or pass).

Node		
Attribute	Attribute description	Admitted values
Name	A unique name for the node.	String
Node ID	A unique identifier (signature) for the	String
	node.	
Туре	Type of the node.	Listed [Station,
		Stopping point,
		Signal,]
N x Node Track	The tracks that make up the node.	Complex [{Node
		Track}]
Start of validity period	The start of validity for these data	Datetime

G A 777513 Page 101 |







End of validity period	The end of validity for these data	Datetime

Table 11-14 TOM-3 "Planning Conditions" (Node) Data

#### 11.4.2.5 *Node Track*

This is a track that is part of a node.

Node Track			
Attribute	Attribute description	Admitted values	
Track ID	Unique identifier of the track.	String	
Length	Length of track.	Numeric	
Platform Length	Length of platform.	Numeric	
Start of validity period	The start of validity for these data	Datetime	
End of validity period	The end of validity for these data	Datetime	

Table 11-15 TOM-3 "Planning Conditions" (Node Track) Data

# 11.4.2.6 Time separation of train events at nodes

When the timetable is constructed, two arrival or departure events, associated one-to-one with two trains, must often be appropriately separated in time. The purpose of the separation can be to enforce headways on double tracks or buffer times at meeting/overtaking nodes. The time separation required sometimes depends on which node tracks that the trains are scheduled to arrive at/depart from, on the types of the trains, and on the order in which the trains arrive at/depart from the node.

	Time Separation	
Attribute	Attribute description	Admitted values
First Event	The type of the event that happens first.	Listed [Arrival,
		Departure]
Second Event	The type of the event that happens	Listed [Arrival,
	second.	Departure]
N x Node Track 1	Identifies the group of node tracks to	Complex [{Node
	which the track used by the train involved	Track}]
	in the first event belongs.	
N x Node Track 2	Identifies the group of node tracks to	Complex [{Node
	which the track used by the train involved	Track}]
	in the second event belongs.	
N x Timing Load Name 1	Identifies the group of train types to	Complex [String]
	which the train involved in the first event	
	belongs.	
N x Timing Load Name 2	Identifies the group of train types to	Complex [String]
	which the train involved in the second	
	event belongs.	
Direction	Indicates if the two trains travel in the	Listed [Same,
	same direction or in different directions.	Different]
First Train Stops	Indicates if the train involved in the first	Boolean

GA 777513 Page 102 |







	event stops.	
Second Train Stops	Indicates if the train involved in the	Boolean
	second event stops.	
Separation Time	The minimum time between the first	Numeric
	event and the second event.	
Start of validity period	The start of validity for these data	Datetime
End of validity period	The end of validity for these data	Datetime

Table 11-16 TOM-3 "Planning Conditions" (Time Separation) Data

#### 11.4.2.7 **Possession**

Data related to a possession. Based on Table 8.98 (Scheduled Data) in X2Rail-2 D6.1.

Possession		
Attribute	Attribute description	Admitted values
Related Restriction	Whether the possession causes a	Listed [Temporary
	restriction in speed or a closure.	Speed Restriction,
		Close]
N x Track	The track(s) affected by the possession.	Complex [{Track}]
Maximum Speed	Limit of speed when the possession is	Numeric
	running.	
Possession Start Time	Scheduled datetime for the activation of	Datetime
	the possession.	
Possession End Time	Scheduled datetime for the deactivation	Datetime
	of the possession.	

Table 11-17 TOM-3 "Planning Conditions" (Possession) Data

#### 11.4.3 TOM-4 Input Timetable

These data describe a timetable (for a certain railway network and a certain period of time) that is to be optimized or to which a new train is to be added. This includes details such as the arrival and departure times of the trains in the timetable.

# 11.4.3.1 Input Timetable Properties

	Interface TOM-4 Properties		
Interface ID	TOM-4		
Interface Title	Input Timetable		
Publisher	The TPS shall be able to publish the data within sections 11.4.3.2, 11.4.3.3, and		
	11.4.3.4 to the integration layer.		
Publish Trigger	When a timetable has been created (and the timetable planner has approved it),		
	the TPS shall publish it to the Integration Layer.		
Expected	Dynamic		
Frequency	May be published 1 time per 5 minutes if the planners make timetable changes		
	frequently.		
Subscribers	ТОМ		
Filter	The Integration Layer shall provide the subscriber with the ability to read "Input		
	Timetable" data related to a specified train assignment or train number, control		

G A 777513 Page 103 |







	point or pair of control points, and/or period of time.
Persistence	The Integration Layer shall persist "Input Timetable" data at least until every
	Date of every Train Timetable has passed or until the data are deleted on
	request by the planner or replaced by a new version.
Length of	The Integration Layer shall identify the "Input Timetable" data as valid until they
Validity	are deleted on request by the planner or replaced by a new version.
Historical Depth	The Integration Layer shall provide the last "Input Timetable" data received
	when a read request is made.

**Table 11-12 TOM-4 Input Timetable Properties** 

#### 11.4.3.2 Timetable Control Point

Arrival and departure times and their related parameters for a train at a control point of the route. The data for the timetable control point is the same as Table 11-3 TOM-1 "Optimized Timetable" (Timetable Control Point) Data.

#### 11.4.3.3 Train Timetable

This is the timetable for a single train, potentially running on several dates. The data for the train timetable is the same as Table 11-4 TOM-1 "Optimized Timetable" (Train Timetable) Data.

#### 11.4.3.4 Full Timetable

This is the full timetable for the railway network and period. The data for the full timetable is the same as Table 11-5 TOM-1 "Optimized Timetable" (Full Timetable) Data.

GA 777513 Page 104 |







# 12 Conflict Detection and Resolution

# 12.1 Use Case summary

Use Case ID (D7.2 5.3.17) Conflict Detection

Use Case ID (D7.2 5.3.18) Conflict Resolution

The use case describes an innovative scenario for interaction between TMS and operators among each other with the goal to reduce delays and increase the network throughput. The TMS provides the operators with services for management of local solutions (each operator can handle his part of the network) and algorithms for conflict detection and resolution. For this purpose, the algorithms must be provided with the current state of the infrastructure and operations.

# **12.2** Interface summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and the interfaces with ".S" are the subscribing side. The interfaces belonging to this use case are annotated with DSS (Decision Support System) to show the integrated workflow of the use case.

The Operator's workstation is used for representation of the conflicts and resolution proposals to the operator, ATT provides the Conflict Detection and resolution module with the current train positions, Automatic Route Setting uses the resulting timetable for automatic route settings, and ATO uses the forecasted trips for calculation of the optimised journey profiles.

GA 777513 Page 105 |










Figure 12-1 Interface overview - Decision Support System







The table below shows the summary of the interfaces related to the Decision support system and the use case.

Note that where there are multiple publishers these are separate logical interfaces, both publishing the same data to the same subscriber.

Interface ID	Publisher	Subscriber	Interface Title	Interface Description	Data	Prototyped
DSS-1	WS, CRS	SMS	Change requests	Requests for modification of the Real Time Traffic plan   13.3.1	13.3.1	~
				(RTTP).		
DSS-2	SMS	FCDS, CRS, WS	Sandbox content	Sandbox data as a snapshot and set of delta	13.3.2	Υ ,
				modifications.		
DSS-3	SMS	ARS, ATO	RTTP	Representation of the Real Time Traffic Plan as a set of   13.3.2	13.3.2	`Y
				objects (restrictions, trips).		
DSS-4	ATT	FCDS, CRS	Train positions and	Unified train positions and speeds on the abstract	13.3.4	Υ
		ARS, ATO	speeds.	network graph.		
DSS-5	FCDS	WS, CRS	Detected conflicts	Conflicts detected on each sandbox (operator-specific).	13.3.5	Υ

Table 12-1 Conflict Detection and Resolution Interface Summary

GA 777513 Page 107 | 157







#### 12.3 Interface details

This is the data published by the listed services involved into the use case.

#### 12.3.1 DDS-1 Change requests

This data defines modifications the source system wants to apply on some sandbox (partial version of the RTTP). Normally these requests are issued by the operators to be analysed (simulated, conflict detection etc) before activation.

The same interface is used by the conflict resolution service, which plays the same role as a human operator – it is constructing modified RTTP to resolve conflicts.

#### 12.3.1.1 Change request Properties

<b>J</b>	Interface DCC 1 December 2
	Interface DSS-1 Properties
Interface ID	DSS-1
Interface Title	Change requests
Publisher	The operator's workstation and conflict resolution service.
Publish Trigger	When operator modifies a future operational task, e.g. increase the loading time of the train in harbour due to a delay of the ship.
	When the operator modifies the state of the infrastructure by inserting or modifying a temporal speed restriction.
	When conflict resolution module creates a new solution, it publishes required modifications on ILayer
Expected	Dynamic
Frequency	Approx. published 1 time per minute.
Subscribers	TMS, Conflict detection
Filter	The Integration Layer shall provide the Sandbox-management-service with the ability to read "Change requests" data related to a specified "Sandbox". This is achieved by assignment of a separated topic per sandbox.
Persistence	The Integration Layer shall not persist the Change Requests, as they become quickly invalid.
Length of Validity	The validity of the message identifies the sandbox management system, which is responsible for its removal after handling (acceptance or rejection).
Historical Depth	The Integration Layer shall provide the last "Change request" data received when a read request is made.

**Table 12-2 Change request Properties** 

#### 12.3.1.2 Change request data

	Change request	
Attribute	Attribute description	Admitted values
Next change set ID	ID of the next free Change Set in the sandbox.	Numeric
ChangeSet	Object containing modification commands.	Object ChangeSet
UpdateOffsetId	If the value is > 0, represents the ID =	Numeric

GA 777513 Page 108 |







	nextChangeSetId – UpdateOffsetId, which	
	shall be updated by this ChangeRequest	
Undo	If true, the ChangeRequest requires to	boolean
	"remove" (undo) all ChangeSets after	
	nextChangeSetId – UpdateOffsetId	
Timestamp	UTC time offset to epoch in microseconds,	UInt64
	when the ChangeSet was created.	
ChangeSet.Sender	ID of the sending application, optional if the	Alphanumeric
	sender is not the sandbox user.	
ChangeSet.Commands	Objects representing atomic modification	Object Command
	of the RTTP.	
Command.ObjectRef	Reference to the object to be modified	String
Command.AttributeId	Id of the attribute of the object to be integer	
	modified	
Command.OperationType	Type of command to be applied to the	SET/REMOVE/INSERT
	attribute.	
Command.index	If the modified attribute is a sequence, the	Uint32
	index represents the position of the field to	
	be modified.	
Command.value	Union representing the new value of the	Object Any
	attribute	
Command.invalid	If true annotates, that this command is not	boolean
	valid	

Table 12-3 Change request data

## 12.3.2 DDS-2 Sandbox content

The sandbox content consists of a list of ChangeSet-Objects.

# 12.3.2.1 Sandbox content properties

Interface DSS-2 Properties	
Interface ID	DSS-2
Interface Title	Sandbox content
Publisher	Sandbox management service
Publish Trigger	When sandbox management service receives a ChangeRequest it evaluates it and applies to the sandbox content by appending or updating a ChangeSet-object into the sandbox-topic.
Expected	Dynamic
Frequency	Approx. published 1 time minute.
Subscribers	Forecast and conflict detection service, Conflict resolution service, Operator's workstations.
Filter	No filtering is required.
	The Integration Layer shall handle the sandboxes as configured – some of the
Persistence	must be persisted (e.g. the final published sandbox), some of them can be
	transient (e.g. private sandbox of the Conflict-resolution-service).
Length of Validity	The Integration Layer shall identify the published "ChangeSets" data as valid until
Length of Validity	the proposals are in the past.

G A 777513 Page 109 |







**Historical Depth** 

The Integration Layer shall provide the last "ChangeSet" data received when a read request is made.

## **Table 12-4 Sandbox content properties**

The ChangeSet-Objects are already specified in the table "change request data".

## 12.3.3 DSS-3 Representation of the Real Time Traffic Plan

The RTTP is published in two ways:

- As a master sandbox collecting all modifications since last snapshot
- As a set of objects: Trips, planned Possessions etc.

In this section only Trips are defined. The sandbox service applies all modifications to the data model and publishes the trips on configured topic in the IL.

### 12.3.3.1 Trip properties

Interface DSS-3 Properties		
Interface ID	DSS-3	
Interface Title	Trips	
Publisher	Sandbox management service	
Publish Trigger	When sandbox management service modifies the master sandbox.	
Expected	Dynamic	
Frequency	Approx. published 1 time per minute.	
Subscribers	ATO, ARS, Operator's workstations.	
Filter	No filtering is required.	
Persistence	The Integration Layer shall handle trips transient.	
Longth of Validity	The Integration Layer shall identify the published "ChangeSets" data as valid until	
Length of Validity	the proposals are in the past.	
Historical Donth	The Integration Layer shall provide the last "ChangeSet" data received when a	
Historical Depth	read request is made.	

#### **Table 12-5 Trip properties**

#### 12.3.3.2 Trip Data

Trip data		
Attribute	Attribute description	Admitted values
Trip ID	ID for full journey related to the train.	Alphanumeric
Tasks	A set of operational tasks to be	Object Task (and
	implemented on the trip.	inherited)
Path	A list of NetElements with their direction	Object
	representing the way of the trip in the DirNetElement	
	abstract railway network.	
Description	Basic information about the train – start	Object
	and end points of the network, published	TripDescription
	name etc.	
Task.ID	Id of the task	Alphanumeric

GA 777513 Page 110 |







Task.OpPoint	Operational point, in which the task must be implemented.	Reference (string)
Task.startTime	Time at which the task shall start	DateTime
Task.durationTime	Planned task duration in seconds	Numeric
Task.netElement	NetElement on which the task must be implemented	Reference (string)
Task.pos	Position on the NetElement, on which the task must be implemented	Numeric in [cm]
Task.taskUnion	Union containing additional information	Object
	to the task type.	OpTaskUnion

**Table 12-6 Trip Data** 

Further objects (OpTaskUnion, DirNetElement, inherited classes from TaskType) are defined in D6.2 in X2Rail-2.

## 12.3.4 DSS-4 Train positions and speeds.

There are different sources of the train position, which depend on the technical implementation. Here a generalized representation is required.

## 12.3.4.1 Train position properties

The state of the s		
Interface DSS-3 Properties		
Interface ID	DSS-4	
Interface Title	Train position	
Publisher	Automatic train tracking	
Publish Trigger	Time based every 3-10 seconds if the train is moving.	
Expected	Dynamic	
Frequency	Approx. published 100 times per second	
Subscribers	ATO, ARS, Operator's workstations, FCDS, CRS.	
Filter	No filtering is required.	
Persistence	The Integration Layer shall handle trip positions transient (without persistence).	
Length of Validity	The Integration Layer shall identify the published "Train positions" data as valid	
Length of Validity	for 1 minute.	
Historical Donth	The Integration Layer shall provide the last "Train position" data received when a	
Historical Depth	read request is made.	

**Table 12-7 Train position properties** 

#### 12.3.4.2 Train position data

Train position		
Attribute Attribute description		Admitted values
trip	Reference to the trip	Reference (string)
netElement	NetElement on which the train front was.	Reference (string)
Timestamp	UTC time in microseconds since epoch.	UInt64
estimatedFrontPos	Position of the front of the train on the Uint32 [cm]	
	NetElement	
estimatedRearOffset	Represents the estimated offset of the rear	Uint32 [cm]
	compared to the front.	

GA 777513 Page 111 |







mostRestrictiveFrontOffset	Represent secure front position as offset to	
	the estimatedFrontPos forwared	
mostRestrictiveRearOffset	Represent secure rear position as offset to	
	the estimatedFronPos backwards	
direction	Movement direction based on the Nominal/Reverse	
	NetElement	
speed	Estimated train speed in [km/h]	Uint32
trainLength	Estimated train length	Numeric in [cm]
integrityConfirmed	Defines, if the train integrity is confirmed in	boolean
	a safe manner.	

**Table 12-8 Train position data** 

## 12.3.5 DSS-5 Detected conflicts.

Detected conflicts represent a list of conflicts for dedicated sandbox (each sandbox has its own conflicts).

### 12.3.5.1 Conflicts properties

Interface DCC E Desperties	
	Interface DSS-5 Properties
Interface ID	DSS-5
Interface Title	Conflict
Publisher	Forecast and conflict detection service
	Train movement
Publish Trigger	Modification of the Trip-Task
	Modification of the infrastructure
Expected	Dynamic
Frequency	Approx. published 1 time per second
Subscribers	Operator's workstations, CRS.
Filter	No filtering is required.
Persistence	The Integration Layer shall handle trip positions transient (without persistence).
Length of Validity	The Integration Layer shall identify the published "Conflict" data as valid the
Length of Validity	conflict is in the past.
Historical Depth	The Integration Layer shall provide the last "Conflict" data received when a read
Historical Depth	request is made.

**Table 12-9 Conflicts properties** 

#### 12.3.5.2 Conflict data

Conflict definition		
Attribute	Admitted values	
Id	Id of the conflict which shall be referenced by conflict resolution.	String
IssuedTimestamp	Time of validity of conflict definition. If one of the objects defined in this conflict changed afterwards, the conflict	Timestamp

GA 777513 Page 112 |







	definition is assumed as invalid.	
ConflictType	Defines the type of the conflict.	Listed [InvalidLink, InvalidValue, LimitedResource]
Object	Defines the path to the main object of the conflict:	Object Path according to CDM definition.
	<ul> <li>Containing invalid data link or</li> <li>Containing invalid data value or</li> <li>Limited resource (e.g. track)</li> </ul>	
InvalidAttributeId	Defines the attribute id in Object providing invalid link or invalid value.	Integer
ExpectedAttrValue	Hint for the expected value for the invalid-object-value.	Any (double, string, int, enumerator)
ConflictingObjectLinks	The limited-resource conflict occurs if several objects use shared object concurrently. Usage can be identified as "linking". In this attribute paths with conflicting links are stored.	Object-Attribute Path according to CDM definition with maxOccurs="unbounded". The order of conflicting objects is according to the planned sequence of limited-resource-occupation.
Severity	Defines the severity of the conflict. In case of Error the train operation will be impossible, in case of warning probably not optimal.	Listed [Warning, Error]
ExpectedResolutionTime	Most of the conflicts can be solved short before operation – so the operator can structure his work as required.	Timestamp
InvalidLinkReason	There are several reasons for invalidity of a link – it could be	Listed [TemporaryNotAvailable, NotAvailable,
	<ul> <li>temporary not available</li> <li>(e.g. a track due to maintenance)</li> <li>Not available (e.g. due to</li> </ul>	NotExisting]







	cancellation)  - Not existing in IL (e.g. reference to the not yet planned or imported trip)	
ObjectType	The type of the main object as defined by CDM. It can be used to associate conflict resolution to different systems in a customer specific installation. The object type is implicitly encoded in the Object path.	String [Module.ClassName]
JustificationRef	Reference to Object with justification. It replaces the common used error-codes.	String [reference]

**Table 12-10 Conflict data** 







# 13 Container Management System

### 13.1 Use Case summary

Use Case ID (D7.2 5.3.19) Optimizing container delivery to ports

The use case describes an innovative scenario for interaction between a Container Management System (CMS) and TMS with the goal to provide smooth and fast delivery of containers to ports. The TMS provides the CMS with up to date and accurate information on train status which enables the CMS to provide up to date and accurate information on container status at any time. The CMS provides TMS with additional information of containers, wagons and train by putting this data on the Integration Layer.

### 13.2 Interface Summary

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side. Although some of the interfaces belong to TMS or the FRU, as these are described from the perspective of this use case, they are all currently identified as "CMS" interfaces.




Figure 13-1 Interface Overview - Container management System

GA 777513 Page 115 |







The table below shows a summary of the interface related to the container management system and the use case.

		Reference					
	Steps 4,6,7	or!	locations.				
<b>Y</b>	D7.2 5.3.19	13.4.3.2 <b>Err</b>	Data on forecasted times a train will be at major	Train Forecast	CMS	SML	CMS-8
	Steps 6,7	4.3.1	reporting locations.	Position			
~	D7.2 5.3.19	13.4.2.213.	Data on the actual position of a train at	Actual Train	CMS	TMS	CMS-7
	1		assigned to travel on.	Assignment			
	D7.2 5.3.19 Step	13.4.1.2	Data on which train service the container is	Train to Container	CMS	FRU	CMS-6
						ing	CMS Subscribing
	8	10.0.2	train plan in TMS.	Modification			
	D7.2 5.3.19 Step	13357	Data required for requesting a modification to a	Request Schedule	SMT	CMS	CMS-5
			transport vehicle.				
	Steps 1		times. Assignment of journey leg to a specific	Leg	DAS, ATO		
~	D7.2 5.3.19	13.3.4.2	Origin and destination of a journey leg, including	Container Journey	TMS, S&C,	CMS	CMS-4
	Steps 1,2		container.	Details	DAS, ATO		
	D7.2 5.3.19	13.3.3.2	Data on physical size, type and weight of	Physical Container	TMS, S&C,	CMS	CMS-3
	Steps 1,2		dangerous goods etc.		DAS, ATO		
	D7.2 5.3.19	13.3.2.2	Data on the contents of a container, weigh,	Container Contents	TMS, S&C,	CMS	CMS-2
	2	3.1	which may involve multiple journey legs.				
	D7.2 5.3.19 Step	13.3.1.213.	Data on the overall journey of a container,	Container Journey	TMS	CMS	CMS-1
						ng	CMS Publishing
d	Case Steps	Description					
Prototype	Related Use	Data	Interface Description	Interface Title	Subscriber	Publisher	Interface ID

GA 777513







1		
	found.	source not

Table 13-1 Container Management System Interface Summary







## 13.3 Data Published by CMS system to Integration Layer

This is the data published by the Container Management System to the Integration Layer available for a TMS and other systems to use.

Any "admitted values" surrounded in curly braces "{ }" is an instance of a different table in this chapter.

# 13.3.1 CMS-1 Container Journey

This is the data for the overall container journey from origin to final destination. This includes details such as the overall start time and location, and end time and location of the containers journey. This also contains data on the current status of the journey and which container journey leg is currently in progress.

### 13.3.1.1 Container Journey Properties

	Interface CMS-1 Properties
Interface ID	CMS-1
Interface Title	Container Journey
Publisher	The CMS shall be able to publish the data within section 13.3.1.2 to the integration layer.
Publish Trigger	When a container journey is created, the CMS shall publish the "Container Journey" data to the Integration Layer
	When the value of any "Container Journey" attributes, except for "Forecasted Journey Departure" and "Forecasted Journey Arrival Time" change, CMS shall publish the "Container Journey" data to the Integration Layer
	When the value for "Forecasted Journey Departure Time" or "Forecasted Journey Arrival Time" change by 5 minutes or more, in comparison to the last published value for those attributes, the CMS shall publish the "Container Journey" data to the Integration Layer
	If the Previously published value for "Forecasted Journey Departure Time" or "Forecasted Journey Arrival Time" is NULL, when any change to the value of these attributes occurs, the CMS shall publish the "Container Journey" data to the Integration Layer
Expected Frequency	Dynamic  Approx. published 1 time per 5 minutes per container if forecast changes frequently.

GA 777513 Page 118 |







Subscribers	TMS, Conflict detection
Filter	The Integration Layer shall provide the subscriber with the ability to read "Container Journey" data related to a specified "Container Journey ID"
Persistence	The Integration Layer shall persist "Container Journey" data until the "Audited Journey Arrival Time" is 24 hours in the past.
Length of Validity	The Integration Layer shall identify the "Container Journey" data as Valid until the "Audited Journey Arrival Time" is 24 hours in the past.
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-2 CMS-1 Container Journey Properties** 

# 13.3.1.2 Container Journey Data

Container Journey			
Attribute	Attribute description	Admitted values	
Container Journey ID	ID for full journey related to a container. This may involve multiple journey legs using different modes of transport.	Alphanumeric	
Container Journey Status	Status of the container journey	List [e.g. planned, in progress, cancelled, complete, loaded, etc]	
Current container Journey Leg	The ID of the Current container Journey Leg	Alphanumeric	
Journey Origin Location	Origin location of the journey.	Alphanumeric	
Planned Journey Departure Time	Planned start time of the journey.	DateTime	
Forecasted Journey Departure Time	Forecasted start time of the journey.	DateTime	
Audited Journey Departure Time	Real time the journey started.	DateTime	
Journey Destination Location	Destination Location of the journey.	String	
Planned Journey Destination Time	Planned time of arrival at destination.	DateTime	
Forecasted Journey Arrival Time	Forecasted time of arrival at destination	DateTime	
Audited Journey Arrival Time	Real time of arrival at destination.	DateTime	

Table 13-3 CMS-1 "Container Journey" Data

G A 777513 Page 119 |







# 13.3.2 CMS-2 Container Contents

These are the details of the container contents. This can be used to inform whether dangerous goods are being transported.

### 13.3.2.1 Container Contents Properties

Interface CMS-2 Properties		
Interface ID	CMS-2	
Interface Title	Container Contents	
Publisher	The CMS shall be able to publish the data in section 13.3.2.2 to the integration layer.	
Publish Trigger	When Container Contents are assigned to a container journey the CMS shall publish "Container Contents" data to the Integration Layer  When any attributes within "Container Contents" change value, the CMS shall publish the "Container Contents" data to the Integration Layer	
Expected Frequency	Dynamic	
	Approx. published 1 time per 24 hours per container.	
Subscribers	TMS, S&C	
Filter	The Integration Layer shall provide the subscriber with the ability to read "Container Contents" data related to a specified "Container Journey ID"	
Persistence	The Integration Layer shall persist the published "Container Contents" data until the "Container Journey" has ended or the "Container Contents" data is overwritten for the same "Container Journey ID".	
Length of Validity	The Integration Layer shall identify the published "Container Contents" data as valid until the "Container Journey" has ended.	
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.	

**Table 13-4 CMS-2 Container Contents Properties** 

### 13.3.2.2 Container Contents Data

Container Contents			
Attribute	Attribute description	Admitted values	
Container Journey ID	ID for full journey related to a container. This may involve multiple journey legs using different modes of transport.	Alphanumeric	

G A 777513 Page 120 |







Contents class	Class of contents	Alphanumeric
Contents Description	Description of contents	Alphanumeric
Weight	Weight of contents	UnitOfMeasurem ent: Alphanumeric Value: Numeric
Dangerous Goods Flag	Flag to identify if contents are dangerous goods	True/False
Dangerous Goods Class	Class of dangerous goods	Alphanumeric
Dangerous Goods Explosive Flag	Flag to identify if explosive	True/False
Dangerous Goods Emergency Code	Emergency code related to dangerous goods	Alphanumeric
Additional Information	Additional Information can be required depending on port of destination or national customs requirements	Alphanumeric

**Table 13-5 CMS-2 Container Contents Data** 

# **13.3.3 CMS-3 Physical Container Details**

This is the physical container details of the container. This can be used to understand the weight and size of each container.

# 13.3.3.1 *Physical Container Details Properties*

Interface CMS-3 Properties		
Interface ID	CMS-3	
Interface Title	Physical Container Details	
Publisher	The CMS shall be able to publish the data in section 13.3.3.2 to the integration layer.	
Publish Trigger	When "Physical Container Details" are assigned to a container journey the CMS shall publish the "Physical Container Details" data to the Integration Layer.  When any attributes within "Physical Container Details" change value, the CMS shall publish the "Physical Container Details" data to the Integration Layer	
Expected Frequency	Dynamic  Approx. published 1 time per 24 hours per container.	

GA 777513 Page 121 |







Subscribers	TMS, S&C, ATO, DAS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Physical Container Details" data related to a specified "Container Journey ID"
Persistence	The Integration Layer shall persist the published "Physical Container Details"
	data until the "Container Journey" has ended or the "Physical Container Details" data is overwritten for the same "Container Journey ID".
Length of Validity	The Integration Layer shall identify the published "Physical Container Details" data as valid until the "Container Journey" has ended.
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-6 CMS-3 Physical Container Details Properties** 

# 13.3.3.2 Physical Container Details Data

Physical Container Details			
Attribute	Attribute description	Admitted values	
Container Journey ID	ID for full journey related to a container. This may involve multiple journey legs using different modes of transport.	Alphanumeric	
Physical Container ID	ID of physical Container	Alphanumeric	
Container Type	Code to identify container type	Alphanumeric Code	
Container Length	Length of Container	UnitOfMeasurem ent: Alphanumeric  Value: Numeric	
Container Height	Container Height	UnitOfMeasurem ent: Alphanumeric	
		Value: Numeric	
Container Width	Container Width	UnitOfMeasurem ent: Alphanumeric  Value: Numeric	
Unloaded Weight	Weight of the container when unloaded.	UnitOfMeasurem ent:	

G A 777513 Page 122 |







		Alphanumeric
		Value: Numeric
Loaded Weight	Weight of the container when loaded.	UnitOfMeasurem ent: Alphanumeric  Value: Numeric
Additional Information	Additional Information can be required depending on port of destination or national customs requirements	Alphanumeric

Table 13-7 CMS-3 Physical Container Details Data

## 13.3.4 CMS-4 Container Journey Leg

This is the data for each journey leg. This is used for each vehicle the container travels on. A specific transport ID such as a train service is assigned to each container leg. The Container Journey Leg Status could feed other processes that rely on confirmation of loading.

## 13.3.4.1 Container Journey Leg Properties

13.3.4.1 Container Journey Leg Properties		
Interface CMS-4 Properties		
Interface ID	CMS-4	
Interface Title	Container Journey Leg	
Publisher	The CMS shall be able to publish the data in section 13.3.4.2 to the integration layer.	
Publish Trigger	When a "Container Journey Leg" is created, the CMS shall publish the "Container Journey Leg" data to the Integration Layer.	
	When the value of any "Container Journey Leg" attributes, except for "Forecasted Journey Leg Departure Time" and "Forecasted Journey Leg Arrival Time" change, CMS shall publish the "Container Journey Leg" data to the Integration Layer	
	When the value for "Forecasted Journey Leg Departure Time" or "Forecasted Journey Leg Arrival Time" change by 5 minutes or more, in comparison to the last published value for those attributes, the CMS shall publish the data in "Container Journey Leg" data to the Integration Layer	

G A 777513 Page 123 |







	If the Previously published value for "Forecasted Journey Leg Departure Time" or "Forecasted Journey Leg Arrival Time" is NULL, when any change to the value of these attributes occurs, the CMS shall publish the "Container Journey Leg" data to the Integration Layer
Expected	Dynamic
Frequency	Approx. published 1 time per 5 minutes per container.
Subscribers	TMS, Stock&Crew, DAS, ATO
Filter	The Integration Layer shall provide the subscriber with the ability to read "Container Journey Leg" data related to a particular "Container Journey ID" or "Transport Operational ID"
Persistence	The Integration Layer shall persist the published "Container Journey Leg" data until the "Container Journey" has ended or the "Container Journey Leg" data is overwritten for the same "Container Journey ID".
Length of Validity	The Integration Layer shall identify the published "Container Journey Leg" data as valid until the "Container Journey" has ended.
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-8 CMS-4 Container Journey Leg Properties** 

# 13.3.4.2 Container Journey Leg Data

Container Journey Leg			
Attribute	Attribute description	Admitted values	
Container Journey ID	ID for full journey related to a container. This may involve multiple journey legs using different modes of transport.	Alphanumeric	
Container Journey Leg ID	ID of this container journey leg	Alphanumeric	
Container Journey Leg Status	Status of the container journey leg	List [e.g. planned, in progress, cancelled, complete etc]	
Journey Leg Origin Location	Location of the start of this journey leg e.g. depot name.	Alphanumeric	
Planned Journey Leg Departure Time	Planned time for departure from the journey leg origin location.	DateTime	
Forecasted Journey Leg Departure Time	Forecasted start time of the journey leg.	DateTime	

G A 777513 Page 124 |







Audited Journey Leg Departure Time	Real time of departure from the journey leg origin location.	DateTime
Journey Leg Destination Location	Location of the End of this journey leg e.g. depot name.	Alphanumeric
Planned Journey Leg Arrival Time	Planned time for arrival from the journey leg origin location.	DateTime
Forecasted Journey Leg Arrival Time	Forecasted time of arrival at destination	DateTime
Audited Journey Leg Arrival Time	Real time of arrival from the journey leg origin location.	DateTime
Transportation mode	Mode of Transport, e.g. Train/Ship	List
Transport Operational ID	For Train this will be the Operational Train Identifier.	Alphanumeric
Loaded Location on transport vehicle	This is the location of the container on the loaded vehicle.	{Container Loaded Position}

**Table 13-9 CMS-4 Container Journey Leg Data** 

This table is the data used to locate the container on each vehicle.

Container Loaded Position			
Attribute	Attribute description	Admitted values	
ID of loaded location	ID of specific location container is loaded. i.e. Wagon ID for Freight Trains.	Alphanumeric	
Container Position on loaded vehicle	Distance of container front of loaded location.	UnitOfMeasurement: Alphanumeric  Value: Numeric	

**Table 13-10 CMS-4 Container Loaded Position Data** 

## 13.3.5 CMS-5 Request Schedule Modification

This is the data used by the CMS to request a modification to the plan of the transport service that is used for a particular "Container Journey Leg". This is intended to request a delay to a service if there are problems related to containers being available when scheduled.

#### 13.3.5.1 Request Schedule Modification Properties

13.3.3.1 Request Schedule Wodification 1 Toperties		
Interface CMS-5 Properties		
Interface ID	CMS-5	

GA 777513 Page 125 |







Interface Title	Request Schedule Modification
Publisher	The CMS shall be able to publish the data in section 13.3.5.2 to the integration layer.
Publish Trigger	When the CMS requires a schedule change for an "Operational Transport ID" assigned to a "Container Journey Leg" it shall publish the "Request Schedule Modification" data to the Integration Layer.
Expected	Dynamic
Frequency	Approx. published 10 times per 24 hours per container.
Subscribers	TMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Request Schedule Modification" data related to a particular "Transport Operational ID"
Persistence	The Integration Layer shall persist the published "Request Schedule Modification" data the "New requested time" is in the past.
Length of Validity	The Integration Layer shall identify the published "Request Schedule modification" data as valid until the "New requested time" is in the past.
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-11 CMS-5 Request Schedule Modification Properties** 

#### 13.3.5.2 Request Modification to Plan Data

The data for this interface can be found in Chapter 8.2.2.2 "Modify Train" of "X2Rail-2 D6.1 System Requirement Specification (SRS) for the Integration Layer"[3]

#### 13.4 Data Read or Subscribed by CMS system to Integration Layer

This is the data read or subscribed to by the Container Management System from the Integration Layer.

The diagram below shows the relationship between the tables in this section. Any "admitted values" surrounded in curly braces "{ }" is an instance of a different table in this chapter.

#### 13.4.1 CMS-6 Train to Container Assignment

This is the data that assigns a transport ID to a particular "Container Journey Leg" and therefore to a specific container. This triggers many of the other data exchanges and is used by the CMS to identify which train service the "Container Journey Leg" will be assigned to.

G A 777513 Page 126 |







# 13.4.1.1 Train to Container Assignment Properties

Interface CMS-6 Properties		
Interface ID	CMS-6	
Interface Title	Train Assignment	
Publisher	The FRU system shall be able to publish the data in section 13.4.1.2 to the integration layer.	
Publish Trigger	When a container is assigned to a train service, the FRU system shall publish the "Train to Container Assignment" data to the Integration Layer.	
	When a container assigned to a train service is unassigned to a train service, the FRU system shall publish the "Train to Container Assignment" data to the Integration Layer.	
	When a container currently assigned to a train service, is assigned to a different train service, the FRU system shall publish the "Train to Container Assignment" data to the Integration Layer.	
Expected	Dynamic	
Frequency	Approx. published 1 time per 24 hours per container.	
Subscribers	CMS, TMS, S&C	
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train to Container Assignment" data related to a particular "Transport Operational ID"	
	The Integration Layer shall provide the subscriber with the ability to read "Train to Container Assignment" data related to a particular "Container Journey Leg ID"	
Persistence	The Integration Layer shall persist the published "Train to Container Assignment" data until the "Planned Unloading Location Arrival Time" is 24 hours in the past.	
Length of Validity	The Integration Layer shall identify the published "Train to Container Assignment" data as valid until the "Planned Unloading Location Arrival Time" is 24 hours in the past.	
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.	

**Table 13-12 CMS-6 Train to Container Assignment Properties** 

GA 777513 Page 127 |







## 13.4.1.2 Train to Container Assignment Data

Train Service ID assigned to Container			
Attribute	Attribute description	Admitted values	
FRU Company	UIC Company Code for Freight Company	UIC Company Code	
Operational Train Number	UK = Train ID  Mainland Europe = Operational  Train Number	Alphanumeric	
Operational Train Identifier	Further details used to identify the train service.	{TransportOperationalIdentifiers}	
Loading Location	Location the container will be loaded onto the train service	Alphanumeric	
Planned Loading Location Departure Time	Time the train will depart the loading location.	DateTime	
Unloading Location	Location the container will be unloaded from the train service.	Alphanumeric	
Planned Unloading Location Arrival Time	Time the train will arrive at the unloading location.	DateTime	
Order ID/container journey Leg ID		Alphanumeric	

Table 13-13 CMS-6 Train to Container Assignment Data

#### 13.4.2 CMS-7 Actual Train Position

CMS will subscribe to updates of the actual train position of any train service that a "Container Journey Leg" is subscribed to. This will allow it to track the progress of the container.

## 13.4.2.1 Actual Train Position Properties

Interface CMS-7 Properties		
Interface ID	CMS-2	
Interface Title	Container Contents	
Publisher	The TMS shall be able to publish the data in section 13.4.2.2 to the integration layer.	
Publish Trigger	When Train Position Data is generated for Stations or Depots, TMS shall publish the "Actual Train Position" data to the integration layer.	

GA 777513 Page 128 |







Expected	Dynamic
Frequency	Approx. published 2 times per 5 minutes per train.
Subscribers	CMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Actual Train Position" data related to a particular "Transport Operational ID"
Persistence	The Integration Layer shall persist the published "Actual Train Position" data until the "Actual Time" is 24 hours in the past.
Length of Validity	The Integration Layer shall identify the published "Actual Train Position" data as valid until the "Actual Time" is 24 hours in the past.
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-14 CMS-7 Actual Train Position Properties** 

# 13.4.2.2 Actual Position of Train Data

Actual Position Update of Train			
Attribute	Attribute description	Admitted values	
Reporting IM	UIC code of reporting Infrastructure manager	Numeric	
Operational Train Number	Train service number/headcode	Alphanumeric	
Train Operational Identification	Further details used to identify the train service.	{TransportOper ationalIdentifier s}	
ReportingPointAbbr	Abbreviated form of Location that reporting time is relevant to. (e.g. operating point/control point)	Alphanumeric	
ReportingPointLong	Long form of Location that reporting time is relevant to. (e.g. operating point/control point)	Alphanumeric	
ActivityType	Description of activity/movement type at related locations. E.g. arrival, departure, pass-through.	Numeric Code	
ActualTime	DateTime of the time the train reported at the location.	DateTime	

GA 777513 Page 129 |







DeviationReason	Reason for deviation from targeted	Numeric Code
	schedule.	

Table 13-15 CMS-7 Actual Position of Train Data

#### 13.4.3 CMS-8 Train Forecast

CMS will subscribe to the forecast of any train that is assigned to a container. This will allow it to provide a more accurate ETA for other systems, and stakeholders.

#### 13.4.3.1 Train Forecast Properties

	Interface CMS-8 Properties
Interface ID	CMS-8
Interface Title	Train Forecast
Publisher	The TMS shall be able to publish the data in section 13.4.3.2 to the Integration Layer.
Publish Trigger	When the value for "Forecast Time" for a Station or Depot is 5 or more minutes different from the previous published time, TMS shall publish the "Train Forecast" data to the Integration Layer.
Expected	Dynamic
Frequency	Approx. published 30 times per 5 minutes per container. (i.e. if there are 30 stations in trip and all are 5 minutes late)
Subscribers	CMS
Filter	The Integration Layer shall provide the subscriber with the ability to read "Train Forecast" data related to a particular "Train Operational Identifier" and "Forecast Location Abbr".
Persistence	The Integration Layer shall persist published "Train Forecast" data until "Actual Train Position" for the same location is received for the same "Train Operational Identifier".
	The Integration Layer shall identify the "Train Forecast" data as valid until
Length of Validity	"Actual Train Position" for the same location is received for the same "Train Operational Identifier".
Historical Depth	The Integration Layer shall provide the last "Container Journey" data received when a read request is made.

**Table 13-16 CMS-8 Train Forecast Properties** 

GA 777513 Page 130 |







#### 13.4.3.2 Train Forecast Data

	Train Forecast	
Attribute	Attribute description	Admitted values
Reporting IM	UIC code of reporting Infrastructure manager	Numeric
Operational Train Number	Train service number/headcode	Alphanumeric
Train Operational Identification	Further details used to identify the train service.	{TransportOperati onalIdentifiers}
Forecast Location Abbr	Abbreviated form of Location that Forecast is relevant to. (e.g. operating point/control point)	Alphanumeric
Forecast location Long	Long form of Location that Forecast is relevant to. (e.g. operating point/control point)	Alphanumeric
Activity Type	Description of activity/movement type at related locations. E.g. arrival, departure, pass-through.	Numeric Code
Forecast Time	DateTime of the new forecast time	DateTime
Deviation Reason	Reason for deviation from targeted schedule.	Numeric Code

Table 13-17 CMS-8 Train Forecast Data

G A 777513 Page 131 |







# 14 Automated Mining Train Operation

#### 14.1 Use Case summary

The use cases describe the life cycle of the automated operation of mining trains with moving block.

### Use Case ID (D7.1 18.1) Automated dispatch of an Available Train

A train that is available for a Mission is assigned a mission by the TCC, based on the data provided by the CPS. The train then proceeds to the mission target location. The train is operated fully automatic, driverless and with moving blocks, managed by the TCC. In the path the train is checked for integrity; profile and derailment and weighed. When the train arrives at the target location it awaits further instruction to proceed with the mission or receive a new/follow on mission.

### Use Case ID (D7.2 5.3.20 - D7.1 18.2) Remote Controlled Train Loading

A train moves to the correct starting location in a loading area and informs the operator that it is ready for remote control. The operator takes possession of the train for remote control. The operator drives the train remotely and loads the train as it moves. This is done until the train is fully loaded or the loading area runs out of bulk material. The operator confirms that loading is complete, putting the train back in automatic mode and ready for next mission.

#### Use Case ID (D7.2 5.3.21 - D7.1 18.3) Automated Train unloading

The train approaches a loading area. As the unloader takes over movement of the train, the AOS disengages traction and odometer and re-engages both when unloading is complete. The train then leaves the loading area, proceeds to predefined waiting point, and is ready for a new mission.

#### **14.2 Interface Summary**

The diagram below shows the direction of each interface described in this chapter. Interfaces with ".P" are the publish side and interfaces with ".S" are the subscribe side.

GA 777513 Page 132 |







Page 133 |




Figure 14-1 - Interface Overview - Automated Mining Train Operation







The table below shows a summary of the interface related to the container management system and the use case.

		_					
ID			וונמומכס וונוס	ווונפו ומכם מפסטו (מנוסו)	Description	Case Steps	
TCC Publishing	shing						
11-001	TCC	CPS	Loading-Unloading Status	Quantity loaded in each car, and if estimated or weighed.	14.3.1	BT_NEW:4, D7.2.5.3.20:8, D7.2.5.3.21:5	~
TCC-T2	TCC	CPS	Loading Area in Use	If the loading area is in use by a train or not	0	D7.2.5.3.20:2, D7.2.5.3.20:8	~
TCC-T3	тсс	OPCS	Mission Status	Which trains have a mission and which loading and unloading areas they are assigned.	0	BT_NEW:2,6, D7.2.5.3.20:3,8, D7.2.5.3.21:7	~
TCC-T4	TCC	AOS	ATO Remote Control	Remote control command to train, with direction speed and when load is completed.	0	D7.2.5.3.20:4	~
51-331	TCC	SOV	Movement Authority	Where the train can move, including all data needed to do so.	0	BT_NEW, D7.2.5.3.20, D7.2.5.3.21	~
ТСС-Т6	ТСС	AOS	Position Report Request	Request for train position, as well as radio check	0	BT_NEW, D7.2.5.3.20,	~







TCC-I6	TCC-I5	TCC-I4	TCC-13	TCC-12	TCC-I1	TCC Subscribing	тсс-т9	TCC-T8	TCC-T7	
OPCS	OPCS	OPCS	OPCS	OPCS	CPS	cribing	ТСС	TCC	TCC	
TCC	TCC	TCC	TCC	TCC	TCC		AOS	AOS	AOS	
Loading Finished	Train Status	Movement Request	Desk in Control	Location Status	Loading Area Data		Revoke Emergency Alert	Emergency Alert	Stop Train	
Flag that train can resume mission in	Request train speed.	Set speed and direction of train.	Settings which desk is in control of which train during loading.	If loading or unloading area is available for mission and entry.	Amount and quality of ore in loading area for mission assignment.		Command to revoke Emergency Alert	Request immediate stop of train.	Command to for train to stop as appropriate. Requires new MA to start. Used to change sent MA.	
0	0	0	0	0	14.4.1		0	0	0	
D7.2.5.3.20:8	D7.2.5.3.20:4-7	D7.2.5.3.20:4	D7.2.5.3.20	BT_NEW, D7.2.5.3.20, D7.2.5.3.21	BT_NEW		BT_NEW, D7.2.5.3.20, D7.2.5.3.21	BT_NEW, D7.2.5.3.20, D7.2.5.3.21	BT_NEW	D7.2.5.3.21
~	~	Υ	~	~	~		~	~	~	

GA 777513







	D7.2.5.3.21						
~	BT_NEW, D7.2.5.3.20,	0	Present position, speed and train status	Position Report	TCC	AOS	TCC-18
	D7.2.5.3.20		is things sticking out.				
Υ	BT_NEW,	0	If the train has the correct profile or if there 0	Load Profile	TCC	OPCS	TCC-I7
			Automatic mode when loading is finished.				

Table 14-1 Automated Mining Train Operation Interface Summary

GA 777513







# 14.3 Data Published by TCC to Integration Layer

# 14.3.1 TCC-T1 Loading-Unloading Status

	Interface Properties	
Interface ID	TCC-T1	
Interface Title	Loading-Unloading Status	
Publisher	TCC	
Publish Trigger	Change in load status, i.e. loading, weighing or unloading is complete.	
Expected	Dynamic - Depending on route length, and the number of trains. Every 10 minutes to 10	
Frequency	hours per train.	
Subscribers	CPS	
Filter	N/A	
Persistence	5 days	
Length of	Until train service is in the past.	
Validity	Onth train service is in the past.	
Historical Depth	As defined in Persistence.	
Safety-Related	N/A	

**Table 14-2 TCC-T1 Loading-Unloading Status Properties** 

Attribute	Attribute description	Admitted values
cycleNumber	Counter, set by IL	Integer
engineld	Engine Identity	String
Carld	Id of Carts	String
loadId	Loading Area Identity	String
quality	Product quality	String
unloadId	Unloading Area Identity	String
weight	Train weight	Integer
weighted	Estimated weight or not	Boolean
noCars	Number ore cars	Integer
date	Date time	Timestamp

Table 14-3 TCC-T1 Loading-Unloading Status Data

# 14.3.2 TCC-T2 Loading Area in Use

	Interface Properties
Interface ID	TCC-T2
Interface Title	Loading Area in Use
Publisher	TCC
Publish Trigger	Loading commences and finishes
Expected	Dynamic – hourly to multiple time per hour
Frequency	, ,
Subscriber	CPS
Filter	N/A
Persistence	Until updated.

GA 777513 Page 137 |







Length of Validity	Until updated. Valid for approximately 1 hour after final update.
Historical Depth	Snapshot
Safety-Related	N/A

# **Table 14-4 TCC-T2 Loading Area in Use Properties**

Attribute	Attribute description	Admitted values
loadId	Loading Area Identity	String
Status	Ore pass status (in use, not in use)	Boolean

## Table 14-5 TCC-T2 Loading Area in Use Data

#### 14.3.3 TCC-T3 Mission Status

	Interface Properties
Interface ID	TCC-T3
Interface Title	Mission Status
Publisher	TCC
Publish Trigger	Start of mission
Expected	Dynamic – hourly to multiple times per hour
Frequency	Dynamic – nouny to multiple times per noul
Subscriber	OPCS
Filter	N/A
Persistence	Until the end of mission
Length of	Until the end of mission
Validity	Office and of fillssion
Historical Depth	Snapshot
Safety-Related	N/A

## **Table 14-6 TCC-T3 Mission Status Properties**

Attribute	Attribute description	Admitted values
LocationName	Name of the Location (Loading and Unloading)	Integer
TrainID	Locomotive Id	Integer
DeskInControl	1 if operators desk allocated, otherwise 0	Boolean
MissionStatus	Code for how the mission proceed	Integer

#### Table 14-7 TCC-T3 Mission Status Data

## 14.3.4 TCC-T4 ATO Remote Control

Interface Properties		
Interface ID	TCC-T4	
Interface Title	ATO Remote Control	
Publisher	TCC	
Publish Trigger	Movement Request or before time-limit for new speed order.	
Expected	Dynamic – Multiple times per minute	
Frequency		

G A 777513 Page 138 |







Subscriber	AOS
Filter	None
Persistence	None
Length of	T_REMOTE - Defined time-limit for new speed order otherwise train stops
Validity	
Historical Depth	None
Safety Related	Yes

**Table 14-8 TCC-T4 ATO Remote Control Properties** 

Attribute	Attribute description	Admitted values	
NID_MESSAGE_TYPE	7	Integer	
V_SPEED	Requested speed (0 for stop)	Integer	
T REMOTE	Time-limit for new speed order otherwise	se	
1_KEIVIOTE	train stops	Integer	
B_DIRECTION	Direction of movement	Bitmap	
[01]	Profile control triggered or released	{ATO PROFILE CONTROL}	
ATO_PROFILE_CONTROL	Frome control triggered of released	(ATO_PROFILE_CONTROL)	
[01] LOAD_FINISHED	Indicates load process completion	{int : 15}	

**Table 14-9 TCC-T4 ATO Remote Control Data** 

#### 14.3.5 TCC-T5 Movement Authority

Interface Properties		
Interface ID	TCC-T5	
Interface Title	Movement Authority	
Publisher	TCC	
Publish Trigger	New route/mission for train	
Expected	Dynamic - multiple per hour	
Frequency		
Subscriber	AOS	
Filter	None	
Persistence	Until end of Movement Authority, or as indicated in KEEP_TRACK_DATA	
Length of	Until end of Movement Authority, or until Stop Train or Emergency Alert is issued, or the	
Validity	train experiences an emergency.	
Historical Depth	None	
Safety Related	Yes	

**Table 14-10 TCC-T5 Movement Authority Properties** 

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	4	Integer
T_VALID	Time out for the execution of MA	Integer
V_SPEED	Ceiling speed at the beginning of this MA.	Integer
G_GRADIENT	The gradient at the beginning of this MA.	Integer

GA 777513 Page 139 |







A_BRAKEABILITY	Deceleration capability	Integer
B_DIRECTION	Travel direction and train orientation	Bitmap
Q_ROUTE_TYPE	Type of route.	Integer
NID_TRACK	End of MA position, Track	Integer
D_POSITION	End of MA position, Distance	Integer
D_MA_MARGIN	The allowed margin for the vehicle to stop before the end of the MA.	Integer
[01] KEEP_TRACK_DATA	Do not delete any track data until on Location	{int : 25}
[01] LOCATION_DATA	Always present in a LocationEnd MA. May be present in normal MA, to inform of current destination	{LOCATION_DATA}
[01] ATO_STOP_POSITION	May be present in LocationEnd MA	{ATO_STOP_POSITION}
[01] PANTO_START_POSITION	Pantograph position to use from start. It can be present in an MA to an idling train or in other situations where an MA from scratch is sent.	{PANTO_START_POSITION}
[0n] TRACK_DATA	One block for each new Track in this MA. If the direction has changed since the last MA: one block for every Track from the (new) rear end of the train.	{TRACK_DATA}
[0n] BALISE_DATA	One block for each new balise	{ BALISE_DATA }
[0n] GRADIENT_DATA	One block for each new gradient change	{ GRADIENT_DATA }
[0n] CEILING_SPEED_DATA	One block for each new ceiling speed change	{ CEILING_SPEED_DATA }
[0n] ACOUSTIC_SIGNAL	One block for each new signal instruction	{ ACOUSTIC_SIGNAL }
[0n] PANTOGRAPH_SHIFT	One block for each new pantograph shift position	{ PANTOGRAPH_SHIFT }
[0n] TRACK_DATA_ITEM	Various track data items like free rolling, and odometer disabled	{TRACK_DATA_ITEM}

# Table 14-11 TCC-T5 Movement Authority Data

# 14.3.6 TCC-T6 Position Report Request

Interface Properties		
Interface ID	TCC-T6	
Interface Title	Position Report Request	
Publisher	TCC	
Publish Trigger	Timer, regular updates required.	
Expected	Dynamic – Every few seconds	
Frequency		
Subscriber	AOS	
Filter	None	
Persistence	None	
Length of	Until replied or failed	
Validity		

GA 777513 Page 140 |







Historical Depth	None
Safety Related	Yes

**Table 14-12 TCC-T6 Position Report Request Properties** 

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	1	Integer

Table 14-13 TCC-T6 Position Report Request Data

# 14.3.7 TCC-T7 Stop Train

Interface Properties		
Interface ID	TCC-T7	
Interface Title	Stop Train	
Publisher	TCC	
Publish Trigger	Route change that requires change in Movement Authority Issued	
Expected	Dynamic – Infrequent	
Frequency		
Subscriber	AOS	
Filter	None	
Persistence	Validity	
Length of	Until new Movement Authority is issued.	
Validity		
Historical Depth	None	
Safety Related	Yes	

## **Table 14-14 TCC-T7 Stop Train Properties**

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	8	Integer
Q_STOP	Reason for stop	Integer

# **Table 14-15 TCC-T7 Stop Train Data**

# 14.3.8 TCC-T8 Emergency Alert

Interface Properties	
Interface ID	TCC-T8
Interface Title	Emergency Alert
Publisher	TCC
Publish Trigger	Any safety critical incident
Expected	Dynamic - Infrequent
Frequency	
Subscriber	AOS
Filter	None
Persistence	Validity

GA 777513 Page 141 |







Length of	Until Revoke Emergency Alert is sent
Validity	
Historical Depth	None
Safety Related	Yes

**Table 14-16 TCC-T8 Emergency Alert Properties** 

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	3	Integer
Q_ALERT	Alert code	Integer

#### **Table 14-17 TCC-T8 Emergency Alert Data**

## 14.3.9 TCC-T9 Revoke Emergency Alert

Interface Properties	
Interface ID	TCC-T9
Interface Title	Revoke Emergency Alert
Publisher	TCC
Publish Trigger	Emergency resolved
Expected	Dynamic - After Emergency Alert
Frequency	
Subscriber	AOS
Filter	None
Persistence	None
Length of	None (as not persisted)
Validity	
Historical Depth	None
Safety Related	Yes

## **Table 14-18 TCC-T9 Revoke Emergency Alert Properties**

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	9	Integer

## Table 14-19 TCC-T9 Revoke Emergency Alert Data

# 14.4 Data Read or Subscribed by TCC from the Integration Layer

# 14.4.1 TCC-I1 Loading Area Data

Interface Properties	
Interface ID	TCC-I1
Interface Title	Loading and Unloading Area Data
Publisher	CPS
Publish Trigger	Change in loading station level or quality
Expected	Dynamic, few times per hour.
Frequency	Dynamic, few times per nour.
Subscriber	TCC

G A 777513 Page 142 |







Filter	N/A
Persistence	Until Area is no longer used.
Length of Validity	Until changed. Valid for approximately 1 hour after final update.
Historical Depth	Non- snapshot data.
Safety-Related	No

**Table 14-20 TCC-I1 Loading Area Data Properties** 

Attribute	Attribute description	Admitted values
loadId	Loading Area Identity	String
quality	Product quality	String
level	Level in the loading area	Integer

**Table 14-21 TCC-I1 Loading Area Data Data** 

#### 14.4.2 TCC-I2 Location Status

	Interface Properties	
Interface ID	TCC-12	
Interface Title	Location Status	
Publisher	OPCS	
Publish Trigger	After inspection and other events such as cleaning, that make the area available or unavailable	
Expected Frequency	Dynamic – Many times per hour.	
Subscriber	TCC	
Filter	None	
Persistence	Until sequence number restarts	
Length of Validity	Until new status is published	
Historical Depth	See persistence	
Safety-Related	Yes	

**Table 14-22 TCC-I2 Location Status Properties** 

Attribute	Attribute description	Admitted values
SeqNo	Sequence number	Integer
LocationName	Name of the Location	String
Status	Status of location if the train has access to proceed or not	Integer
Text	Text field for TCC log	String

## **Table 14-23 TCC-I2 Location Status Data**

## 14.4.3 TCC-I3 Desk In Control

Interface Properties	
Interface ID	TCC-13
Interface Title	Desk in Control

G A 777513 Page 143 |







Publisher	OPCS
Publish Trigger	Operator is informed of Train at the Loading area and takes control.
Expected	Dynamic – At least ones per loading unloading cycle.
Frequency	
Subscriber	TCC
Filter	None
Persistence	Until Loading Finished
Length of	Valid as long as Customer operations centre (OPCS) is running.
Validity	
Historical Depth	None
Safety Related	Yes

**Table 14-24 TCC-I3 Desk In Control Properties** 

Attribute	Attribute description	Admitted values
TrainID	Locomotive unique ID	Integer
LocationName	Name of the Location	String
DeskID	The ID of the operator desk user	String
StatusCode	Return code to indicate if the request went through	Integer

Table 14-25 TCC-I3 Desk In Control Data

## 14.4.4 TCC-I4 Movement Request

Interface Properties		
Interface ID	TCC-14	
Interface Title	Movement Request	
Publisher	OPCS	
Publish Trigger	Change to speed, or before time-out	
Expected	Dynamic – Every few seconds	
Frequency		
Subscriber	TCC	
Filter	None	
Persistence	Defined in SpeedTimeout	
Length of	Defined in SpeedTimeout ("In seconds, if no new request is sent before the train	
Validity	stops."), or until new message	
Historical Depth	None	
Safety Related	Yes	

**Table 14-26 TCC-I4 Movement Request Properties** 

Attribute	Attribute description	Admitted values
TrainId	Locomotive unique ID	Integer
LocationName	Name of the Location	String
Speed	In % of maximum speed. Driving backward is indicated with	Integer

GA 777513 Page 144 |







	a minus (-) sign. 0 = stop.	
SpeedTimeout	In seconds, if no new request is sent before the train stops.	Integer
CarUnderShute	Returned by TCC, the number of the car under the shute.	Integer
StatusCode	Return code to indicate if the request went through	Integer

# **Table 14-27 TCC-I4 Movement Request Data**

#### 14.4.5 TCC-I5 Train Status

Interface Properties		
Interface ID	TCC-15	
Interface Title	Train Status	
Publisher	OPCS	
Publish Trigger	OPCS needs updated train status	
	Dynamic – multiple times per minute	
Expected	Dynamic – multiple times per minute	
Frequency		
Subscriber	TCC	
Filter	None	
Persistence	Until replied	
Length of	Until next request	
Validity		
Historical Depth	For Validity period	
Safety Related	Yes	

## **Table 14-28 TCC-I5 Train Status Properties**

Attribute	Attribute description	Admitted values
TrainID	Locomotive unique ID	Integer
LocationName	Name of the Location	String
CurrentSpeed	Train reported speed (1/10 km/h) returned by TCC	Integer
StatusCode	Return code to indicate train status	Integer

#### Table 14-29 TCC-I5 Train Status Data

# 14.4.6 TCC-I6 Loading Finished

Interface Properties		
Interface ID	TCC-I6	
Interface Title	Loading Finished	
Publisher	OPCS	
Publish Trigger	Operator presses Loading Finished button	
Expected	Once per loading cycle, every few minutes	
Frequency		
Subscriber	TCC	
Filter	None	
Persistence	Until replied	
Length of	Until replied	
Validity		

GA 777513 Page 145 |







Historical Depth	None
Safety Related	Yes

# **Table 14-30 TCC-I6 Loading Finished Properties**

Attribute	Attribute description	Admitted values
TrainId	Locomotive unique ID	Integer
LocationName	Name of the Location	String
LoadedStatus	Load status of the train.	Integer
StatusCode	Return code to indicate train status	Integer

## Table 14-31 TCC-I6 Loading Finished Data

#### 14.4.7 TCC-I7 Load Profile

THE PERSON TO SERVICE STATE OF THE PERSON SERVICE STATE SE		
Interface Properties		
Interface ID	TCC-17	
Interface Title	Load Profile	
Publisher	OPCS	
Publish Trigger	Load Profile check triggered	
Expected	Dynamic – Infrequent	
Frequency		
Subscriber	TCC	
Filter	None	
Persistence	Validity	
Length of	Until new message issued	
Validity		
Historical Depth	None	
Safety Related	Yes	

## **Table 14-32 TCC-I7 Load Profile Properties**

Attribute	Attribute description	Admitted values
TrainId	Locomotive unique ID	Integer
LocationName	Name of the Location	String
LoadProfileStatus	Load Profile code.	Integer

Table 14-33 TCC-I7 Load Profile Data

## 14.4.8 TCC-I8 Position Report

Interface Properties		
Interface ID	TCC-18	
Interface Title	Position Report	
Publisher	AOS	
Publish Trigger	Any communication from TCC	
Expected	Dynamic – Every few seconds	

G A 777513 Page 146 |







Frequency	
Subscriber	TCC
Filter	Nonce
Persistence	Validity
Length of	Until next Position Report Request or failure to thereof.
Validity	
Historical Depth	None
Safety Related	Yes

## **Table 14-34 TCC-I8 Position Report Properties**

Attribute	Attribute description	Admitted values
NID_MESSAGE_TYPE	132	Integer
NID_TRACK	Position, Track	Integer
D_POSITION	Position of trailing end of the train.	Integer
B_DIRECTION	Travel direction and train orientation	Bitmap
V_SPEED	The velocity of the train in cm/s	Integer
B_TRAIN_STATUS	Status of the train as a bitmap.	Bitmap
D_WINDOW	Current position confidence interval	Integer
NID_TRACK	Current MA target, Track	Integer
D_POSITION	Current MA target, distance on Track.	Integer
Q_ATP_MODE	Current ATP mode	Integer
Q_ATO_MODE	Current ATO mode	Integer

**Table 14-35 TCC-I8 Position Report Data** 

## 14.5 Blocks for TCC and AOS

Blocks/Objects within the above data sets, marked with {} in type.

# 14.5.1 ACOUSTIC\_SIGNAL

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	12	Integer
NID_TRACK	Identification of Track	Integer
D_POSITION	Position of train front when signalling	Integer
Q_SIGNAL	Type of signal	Integer

## Table 14-36 ACOUSTIC\_SIGNAL Data

# 14.5.2 ATO\_PROFILE\_CONTROL

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	13	Integer
Q_PROFILE	Triggered or released	Integer
D_REVERSE	Maximum distance to move, if triggered	Integer
B_DIRECTION	Permitted movement direction, if triggered.	Bitmap

Table 14-37 ATO\_PROFILE\_CONTROL Data

G A 777513 Page 147 |







## 14.5.3 ATO\_STOP\_POSITION

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	11	Integer
NID_TRACK	Identification of Track	Integer
D POSITION	Position of train front when stopped	Integer

## Table 14-38 ATO\_STOP\_POSITION Data

## 14.5.4 BALISE\_DATA

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	4	Integer
NID_TRACK	Identification of Track	Integer
D_POSITION	Position of the balise	Integer
NID_BG	Identification of balise	Integer

## Table 14-39 BALISE\_DATA Data

## 14.5.5 CEILING\_SPEED\_DATA

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	6	Integer
NID_TRACK	Identification of Track	Integer
D_POSITION	Position of speed change.	Integer
V_SPEED	New ceiling speed cm/s (0 65535)	Integer
Q_TRAIN_END	If the ceiling speed-change is valid at the front or rear of the train.	Boolean
Q_SPEED	Reason for change in ceiling speed.	Integer

## Table 14-40 CEILING\_SPEED\_DATA Data

# 14.5.6 GRADIENT\_DATA

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	5	Integer
NID_TRACK	Identification of Track	Integer
D_POSITION	Position of gradient change	Integer
G GRADIENT	Gradient.	Integer

## Table 14-41 GRADIENT\_DATA Data

## 14.5.7 LOCATION\_DATA

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	1	Integer
TID_LOCATION	Location name	Integer
NID_LOCATION_TYPE	Location type	Integer

#### Table 14-42 LOCATION\_DATA Data

#### 14.5.8 PANTOGRAPH\_SHIFT

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	17	Integer
NID_TRACK	Identification of Track	Integer

GA 777513 Page 148 |







D_POSITION	Position of pantograph change.	Integer
Q_PANTO_POSITION	Requested position of the pantograph, valid when traveling towards leg 1 on Track.	Integer
Q_SUPERVISION	Type of supervision, valid when traveling towards leg 1 on Track.	Integer
Q_PANTO_POSITION	Requested position of the pantograph, valid when traveling towards leg 0 on Track.	Integer
Q_SUPERVISION	Type of supervision, valid when traveling towards leg 0 on Track.	Integer

# Table 14-43 PANTOGRAPH\_SHIFT Data

# 14.5.9 PANTO\_START\_POSITION

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	26	Integer
Q_PANTO_POSITION	Wanted position of the pantograph	Integer

# Table 14-44 PANTO\_START\_POSITION Data

# **14.5.10** TRACK\_DATA

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	3	Integer
NID_TRACK	Identification of Track	Integer
D_POSITION	The distance at leg 0	Integer
D_POSITION	The distance at leg 1	Integer
B_DIRECTION	Travel direction and orientation.	Integer
NID_PREVIOUS_TRACK	Identification of previous Track.	Integer

## Table 14-45 TRACK\_DATA Data

## 14.5.11 TRACK\_DATA\_ITEM

Attribute	Attribute description	Admitted values
NID_BLOCK_TYPE	22	Integer
Q_TRACK_DATA_TYPE	Type of track data	Integer
NID_TRACK	Identification of Track	Integer
D POSITION	Position of the item in Track	Integer

Table 14-46 TRACK\_DATA\_ITEM Data

G A 777513 Page 149 |







#### 15 Conclusions

The aim of this report was to identify functional and non-functional requirements for freight related topics integrated into the Integration Layer. A wide spectrum of use cases covering interactions between TMS and Freight Management Systems have been explored to provide data structures for Freight related data Topics on an Integration Layer, as well as properties of those topics to aid the continuing development of the CDM. These have been built on top of the data structures gathered as part of the Deliverable 6.1 "System Requirement Specification (SRS) for the Integration Layer" from X2Rail2 [3].

This deliverable is intended as an input for Impact-2 Prototypes, and will provide the basis for carrying out the activities in FINE-2. It is recommended the data topics defined in this deliverable are taken further in both the FINE-2 and X2Rail-4 projects, utilising feedback from prototypes to assess any modifications or additions required. It is key that any amendments to the data structures of X2Rail2 D6.1 made in X2Rail-4 take this deliverable into consideration.







## 16 References

- [1] D7.2 Use cases for advanced freight operations, Impact-2, grant agreement: 777513
- [2] D8.4 Interface Control Document for Integration Layer Interfaces, external/Web interfaces and Dynamic Demand Service, In2Rail, grant agreement: 635900
- [3] D6.1 System Requirement Specification (SRS) for the Integration Layer, X2Rail-2, grant agreement: 777465. Draft Version Dated 11.12.2019.
- [4] D8.3 Description of Integration Layer and Constituents, In2Rail, grant agreement: 635900
- [5] In2Smart European Project (shift2rail.org/project/in2smart/), GA ID: 730569.







## 17 Antitrust Statement

While some activities among competitors are both legal and beneficial to the industry, group activities of competitors are inherently suspect under the antitrust/ competition laws of the countries in which our companies do business.

Agreements between or among competitors need not be formal to raise questions under antitrust laws. They may include any kind of understanding, formal or informal, secretive or public, under which each of the participants can reasonably expect that another will follow a particular course of action or conduct. Each of the participants in this initiative is responsible for seeing that topics which may give an appearance of an agreement that would violate the antitrust laws are not discussed. It is the responsibility of each participant in the first instance to avoid raising improper subjects for discussion, notably such as those identified below.

It is the sole purpose of any meeting of this initiative to provide a forum for expression of various points of view on topics

- (i) that are strictly related to the purpose or the execution of the initiative,
- (ii) that need to be discussed among the participants of the initiative,
- (iii) that are duly mentioned in the agenda of this meeting and
- (iv) that are extensively described in the minutes of the meeting.

Participants are strongly encouraged to adhere to the agenda. Under no circumstances shall this meeting be used as a means for competing companies to reach any understanding, expressed or implied, which restricts or tends to restrict competition, or in any way impairs or tends to impair the ability of members to exercise independent business judgment regarding matters affecting competition.

As a general rule, participants may not exchange any information about any business secret of their respective companies. In particular, participants must avoid any agreement or exchange of information on topics on the following non-exhaustive list:

- 1. Prices, including calculation methodologies, surcharges, fees, rebates, conditions, freight rates, marketing terms, and pricing policies in general;
- 2. any kind of market allocation, such as the allocation of territories, routes, product markets, customers, suppliers, and tenders;
- 3. production planning; marketing or investment plans; capacities; levels of production or sales; customer base; customer relationships; margins; costs in general; product development; specific R&D projects;
- standards setting (when its purpose is to limit the availability and selection of products, limit competition, restrict entry into an industry, inhibit innovation or inhibit the ability of competitors to compete);
- 5. codes of ethics administered in a way that could inhibit or restrict competition;
- 6. group boycotts;
- 7. validity of patents;
- 8. ongoing litigations.

GA 777513 Page 152 |







# 18 APPENDIX A: Updated Use Cases

The following use cases are new, and therefore not included in Impact-2 Deliverable D7.2 [1], or are updated from use cases in D7.2.

#### 18.1 Automated dispatch of an Available Train

This is a new use case, not previously included in Impact-2 D7.2 [1], to extend the related use cases (D7.2 5.3.20 and 5.3.21).

Title	Automated dispatch of a train to loading, unloading or waiting location
Actors	AOS (ATO+ATP), TCC (incl. ATTM),
Output	Success: Train arrives at loading, unloading area
	Minimal: Train arrives at waiting location
Input	Train ready for Mission

#### Description

A train that is available for a Mission is assigned a mission by the TCC, based on the data provided by the CPS. The train then proceeds to the mission target location. The train is operated fully automatic, driverless and moving blocks, managed by the TCC. In the path the train is checked for integrity; profile and derailment and weighed. When the train arrives at the target location it awaits further instruction to proceed with the mission or receive a new/follow on mission.

#### Flow

- 1. TCC/ATTM receives train ready for Mission
- 2. TCC/ATTM identifies where to send train (loading, unloading or waiting location) based on data CPS and calculates the route
- 3. TCC transmits MA to AOS on the train with all relevant parameters
- 4. Train proceeds within set parameters and reports location and speed
- 5. 2-4 repeats until the train reaches its destination
- 6. Train reaches destination
  - a. The train is handed over to loading/unloading area
  - b. The train arrives at the waiting area, stops and waits for new dispatch

#### Alternate Flows

- 4.1 Integrity Check
  - a) Train passes Derailment Detector or Profile Check

GA 777513 Page 153 |







- b) Derailment Detector or Profile Check fails
- c) TCC requests an immediate stop by an emergency alert from the AOS and informs the operator
- d) AOS stops the train
- e) The fault is checked and/or rectified
- f) The Operator acknowledges the emergency alert and train proceeds from 2.
- 4.2 Weighing
  - a) The train passes a weighing bridge and each individual car is weighed

#### Data Register (specific application data only)

OPCS →TCC

OpLevel

GroupStatus

LocationStatus

MissionStatus

LoadProfile

TCC →CPS

WeighedCarLoad

TCC → AOS

MovementAuthority

Position Report Request

AOS →TCC

PositionReport

#### Result

The entire operation is done fully automated, with moving blocks. There is no need for human intervention/cost, and the trains can run tighter together than with fixed blocks with more effective mission assignments.

#### Related KPIs

#### Higher throughout of Ore:

- Higher utilization of trains
- Higher utilization of loading and unloading areas
- Faster accommodation of changes i.e. blocked loading and unloading stations.
- Train density

#### Savings in cost of drivers:

- Less risk for drivers, as well as less hazard pay, therefore
- Time for a driver to get to a from trains

Savings in track equipment installation and maintenance

GA 777513 Page 154 |







#### **18.2** Remote Controlled Train Loading

This is an updated version of use case "5.3.20 Movement Control in Train Dispatch Area" in Impact-2 D7.2 [1].

Title	Train movement control in the loading area for bulk materials.
Actors	AOS, TCC, Loading Operator
Output	Success: All cars of the train are loaded, and the train is ready to start its train service
	Minimal: Some or none of the cars of the train are loaded, and the train is ready to be assigned a new Loading Area.
Input	Train with empty cars assigned to the Loading Area for loading, the train route has reached the Loading Areas border.
Description	

A train moves to the correct starting location in a loading area and informs the operator that it is ready for remote control. The operator takes possession of the train for remote control. The operator drives the train remotely and loads the train as it moves. This is done until the train is fully loaded or the loading area runs out of bulk material. The operator confirms that loading is complete, putting the train back in automatic mode and ready for next mission.

#### Flow

- 1. Train Loading Operator is informed of the train at the Loading Area border and inspects the Train Loading Area for readiness
- 2. TCC Extend the train route into the Train Loading Area allowing the train to move to a position with the first empty car under the shaft.
- 3. Train moves to the stopping point.
- 4. Loading Operator takes control of the train, sets train speed, which TCC sends to ATO
- 5. ATO moves train at the set speed.
- 6. Loading Operator operates the chute, so the cars are loaded
- 7. 6 is repeated until the last car is loaded, or the chute runs out of ore
- 8. Loading Operator confirms the train is loaded and ready for Mission.

GA 777513 Page 155 |







## Data Register (specific application data only)

OPCS→TCC

MissionStatus

GroupStatus

LocationStatus

DeskInControl

MovementRequest

LoadingFinished

TCC → CPS

PreliminaryCarLoad

SetOrePassStatus

TCC →AOS

MovementAuthority

ATORemoteControl

PositionReportRequest

AOS →TCC

PositionReport

#### Result

The entire process is managed remotely by a single operator, that is immediately available for the next loading station.

#### **Related KPIs**

#### Savings in cost of drivers:

- Less risk for drivers, as well as less hazard pay consequently
- Time for a driver to get to a from trains

## 18.3 Automated Train Unloading

This is an updated version of use case "5.3.21 Movement control in unloading area (Car Dumper)" in Impact-2 D7.2 [1].

Title	Movement control of the train driving through an Unloading Area
Actors	AOS, TCC
Output	All cars of the train consist will be unloaded and the train is ready for a new Mission.
Input	Fully or partially loaded assigned to the unloading area. The train route has reached the unloading area border.

GA 777513 Page 156 |







## Description

The train approaches a loading area. As the unloader takes over movement of the train, the AOS disengages traction and odometer and re-engages both when unloading is complete. The train then leaves the loading area, proceeds to predefined waiting point, and is ready for a new mission.

#### Flow

- 1. TCC Extend the train route into the unloading area to the commence unloading position.
- 2. Train moves to the commence unloading position.
- 3. TCC requests free-roll from AOS
- 4. Unloading commences until the train is unloaded.
- 5. ATO to disengages free-roll.
- 6. TCC sends the train to holding point and sets train for new Mission

## Data Register (specific application data only)

OPCS → TCC

GroupStatus

LocationStatus

MissionStatus

TrainStatus

TCC → CPS

UnloadEvent

TCC →AOS

MovementAuthority

PositionReportRequest

AOS →TCC

PositionReport

#### Result

Completely automated unloading.

#### Related KPIs

#### Savings in cost of drivers:

- Less risk for drivers, as well as less hazard pay consequently
- Time for a driver to get to a from trains

GA 777513 Page 157 |